

This design submission has been carried out using Approved SAP software. It has been prepared from plans and specifications and may not reflect the property as constructed.

Assessor name	Mr Philip French	Assessor number	687
Client		Last modified	29/03/2013
Address	Flat 4, 210 Kingston Road, Teddington, TW11 9JF		

1. Overall dwelling dimensions

	Area (m ²)	Average storey height (m)	Volume (m ³)
Lowest occupied	<input type="text" value="82.00"/> (1a)	<input type="text" value="2.70"/> (2a)	<input type="text" value="221.40"/> (3a)
Total floor area	(1a) + (1b) + (1c) + (1d)...(1n) = <input type="text" value="82.00"/> (4)		
Dwelling volume	(3a) + (3b) + (3c) + (3d)...(3n) =		<input type="text" value="221.40"/> (5)

2. Ventilation rate

		m ³ per hour
Number of chimneys	<input type="text" value="0"/> x 40 =	<input type="text" value="0"/> (6a)
Number of open flues	<input type="text" value="0"/> x 20 =	<input type="text" value="0"/> (6b)
Number of intermittent fans	<input type="text" value="2"/> x 10 =	<input type="text" value="20"/> (7a)
Number of passive vents	<input type="text" value="0"/> x 10 =	<input type="text" value="0"/> (7b)
Number of flueless gas fires	<input type="text" value="0"/> x 40 =	<input type="text" value="0"/> (7c)

Infiltration due to chimneys, flues, fans, PSVs	(6a) + (6b) + (7a) + (7b) + (7c) = <input type="text" value="20"/>	÷ (5) =	<input type="text" value="0.09"/> (8)
---	--	---------	---------------------------------------

If a pressurisation test has been carried out or is intended, proceed to (17), otherwise continue from (9) to (16)

Air permeability value, q ₅₀ , expressed in cubic metres per hour per square metre of envelope area	<input type="text" value="3.00"/> (17)
--	--

If based on air permeability value, then (18) = [(17) ÷ 20] + (8), otherwise (18) = (16)	<input type="text" value="0.24"/> (18)
--	--

Air permeability value applies if a pressurisation test has been done, or a design or specified air permeability is being used

Number of sides on which dwelling is sheltered	<input type="text" value="2"/> (19)
Shelter factor	1 - [0.075 x (19)] = <input type="text" value="0.85"/> (20)
Adjusted infiltration rate	(18) x (20) = <input type="text" value="0.20"/> (21)

Infiltration rate modified for monthly wind speed:

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Monthly average wind speed from Table 7 (22)m	<input type="text" value="5.40"/>	<input type="text" value="5.10"/>	<input type="text" value="5.10"/>	<input type="text" value="4.50"/>	<input type="text" value="4.10"/>	<input type="text" value="3.90"/>	<input type="text" value="3.70"/>	<input type="text" value="3.70"/>	<input type="text" value="4.20"/>	<input type="text" value="4.50"/>	<input type="text" value="4.80"/>	<input type="text" value="5.10"/>
	Σ(22)1...12 = <input type="text" value="54.10"/> (22)											

Wind Factor (22a)m = (22)m ÷ 4

(22a)m	<input type="text" value="1.35"/>	<input type="text" value="1.27"/>	<input type="text" value="1.27"/>	<input type="text" value="1.12"/>	<input type="text" value="1.02"/>	<input type="text" value="0.98"/>	<input type="text" value="0.92"/>	<input type="text" value="0.92"/>	<input type="text" value="1.05"/>	<input type="text" value="1.12"/>	<input type="text" value="1.20"/>	<input type="text" value="1.27"/>
	Σ(22a)1...12 = <input type="text" value="13.52"/> (22a)											

Adjusted infiltration rate (allowing for shelter and wind speed) = (21) × (22a)m

(22b)m	<input type="text" value="0.28"/>	<input type="text" value="0.26"/>	<input type="text" value="0.26"/>	<input type="text" value="0.23"/>	<input type="text" value="0.21"/>	<input type="text" value="0.20"/>	<input type="text" value="0.19"/>	<input type="text" value="0.19"/>	<input type="text" value="0.21"/>	<input type="text" value="0.23"/>	<input type="text" value="0.25"/>	<input type="text" value="0.26"/>
	Σ(22b)1...12 = <input type="text" value="2.76"/> (22b)											

Calculate effective air change rate for the applicable case:

If mechanical ventilation: air change rate through system	<input type="text" value="N/A"/> (23a)
---	--

If exhaust air heat pump using Appendix N, (23b) = (23a) × Fmv (equation (N5)), otherwise (23b) = (23a)	<input type="text" value="N/A"/> (23b)
---	--

If balanced with heat recovery: efficiency in % allowing for in-use factor (from Table 4h) =

N/A (23c)

d) If natural ventilation or whole house positive input ventilation from loft

if $(22b)_m \geq 1$, then $(24d)_m = (22b)_m$; otherwise $(24d)_m = 0.5 + [(22b)_m^2 \times 0.5]$

(24d)m	0.54	0.53	0.53	0.53	0.52	0.52	0.52	0.52	0.52	0.53	0.53	0.53
--------	------	------	------	------	------	------	------	------	------	------	------	------

Effective air change rate - enter (24a) or (24b) or (24c) or (24d) in box (25)

(25)m	0.54	0.53	0.53	0.53	0.52	0.52	0.52	0.52	0.52	0.53	0.53	0.53
-------	------	------	------	------	------	------	------	------	------	------	------	------

3. Heat losses and heat loss parameter

The κ -value is the heat capacity per unit area, see Table 1e.

Element	Gross Area, m ²	Openings, m ²	Net area A, m ²	U-value, W/m ² K	A x U, W/K	κ -value, kJ/m ² .K	A x κ , kJ/K
Window*			11.97	1.15	13.71	N/A	N/A
External wall			47.97	0.16	7.68	N/A	N/A
Party Wall			29.97	0.00	0.00	N/A	N/A
Total area of external elements $\Sigma A, m^2$			59.94	(31)			

* for windows and roof windows, effective window U-value is calculated using formula $1/[(1/U_{Value})+0.04]$ paragraph 3.2

Fabric heat loss, W/K = $\Sigma(A \times U)$ (26)...(30) + (32) = 21.38 (33)

Heat capacity Cm = $\Sigma(A \times \kappa)$ (28)...(30) + (32) + (32a)...(32e) = N/A (34)

Thermal mass parameter (TMP) in kJ/m²K Calculated separately = 100.00 (35)

Thermal bridges: $\Sigma(L \times \Psi)$ calculated using Appendix K 9.89 (36)

if details of thermal bridging are not known then (36) = $0.15 \times (31)$

Total fabric heat loss (33) + (36) = 31.27 (37)

Ventilation heat loss calculated monthly $0.33 \times (25)_m \times (5)$

(38)m	39.31	39.01	39.01	38.46	38.13	37.98	37.84	37.84	38.21	38.46	38.73	39.01
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Heat transfer coefficient, W/K (37)m + (38)m

(39)m	70.58	70.28	70.28	69.73	69.41	69.25	69.11	69.11	69.49	69.73	70.00	70.28
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Average = $\Sigma(39)1...12/12 = 69.77$ (39)

Heat loss parameter (HLP), W/m²K (39)m ÷ (4)

(40)m	0.86	0.86	0.86	0.85	0.85	0.84	0.84	0.84	0.85	0.85	0.85	0.86
-------	------	------	------	------	------	------	------	------	------	------	------	------

Average = $\Sigma(40)1...12/12 = 0.85$ (40)

4. Water heating energy requirement

kWh/year

Assumed occupancy, N 2.50 (42)

If TFA > 13.9, $N = 1 + 1.76 \times [1 - \exp(-0.000349 \times (TFA - 13.9)^2)] + 0.0013 \times (TFA - 13.9)$

If TFA ≤ 13.9, N = 1

Annual average hot water usage in litres per day $V_{d,average} = (25 \times N) + 36$ 93.57 (43)

Annual average hot water usage has been reduced by 5% if the dwelling is designed to achieve a water use target of not more than 125 litres per person per day (all water use, hot and cold)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Hot water usage in litres per day for each month $V_{d,m} = \text{factor from Table 1c} \times (43)$	102.93	99.18	95.44	91.70	87.95	84.21	84.21	87.95	91.70	95.44	99.18	102.93

$\Sigma(44)1...12 = 1122.82$ (44)

Energy content of hot water used - calculated monthly = $4.190 \times V_{d,m} \times n_m \times T_m/3600$ kWh/month (see Tables 1b, 1c 1d)

(45)m	153.00	133.81	138.08	120.39	115.51	99.68	92.37	105.99	107.26	125.00	136.45	148.17
-------	--------	--------	--------	--------	--------	-------	-------	--------	--------	--------	--------	--------

$\Sigma(45)1...12 = 1475.71$ (45)

If instantaneous water heating at point of use (no hot water storage), enter 0 in boxes (46) to (61)

For community heating include distribution loss whether or not hot water tank is present

Distribution loss $0.15 \times (45)_m$

(46)m	22.95	20.07	20.71	18.06	17.33	14.95	13.86	15.90	16.09	18.75	20.47	22.23
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Water storage loss:

b) If manufacturer's declared cylinder loss factor is not known:

Cylinder volume (litres) including any solar storage within same cylinder (50)

If community heating and no tank in dwelling, enter 110 litres in box (50)

Otherwise if no stored hot water (this includes instantaneous combi boilers) enter '0' in box (50)

Hot water storage loss factor from Table 2 (kWh/litre/day) (51)

If community heating see SAP 2009 section 4.3

Volume factor from Table 2a (52)

Temperature factor from Table 2b (53)

Energy lost from water storage, kWh/day (50) x (51) x (52) x (53) (54)

Enter (49) or (54) in (55) (55)

Water storage loss calculated for each month = (55) x (41)m

(56)m

54.57	49.29	54.57	52.81	54.57	52.81	54.57	54.57	52.81	54.57	52.81	54.57
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

 (56)

If cylinder contains dedicated solar storage, = (56)m x [(50) - (H11)] ÷ (50), else = (56)m where (H11) is from Appendix H

(57)m

54.57	49.29	54.57	52.81	54.57	52.81	54.57	54.57	52.81	54.57	52.81	54.57
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

 (57)

Primary circuit loss (annual) from Table 3 (58)

Primary circuit loss for each month (58) ÷ 365 x (41)m

(modified by factor from Table H5 if there is solar water heating and a cylinder thermostat)

(59)m

0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
------	------	------	------	------	------	------	------	------	------	------	------

 (59)

Combi loss for each month from Table 3a, 3b or 3c (enter '0' if not a combi boiler)

(61)m

6.37	5.71	6.08	5.65	5.60	5.19	5.36	5.60	5.65	6.08	6.11	6.37
------	------	------	------	------	------	------	------	------	------	------	------

 (61)

Total heat required for water heating calculated for each month 0.85 x (45)m + (46)m + (57)m + (59)m + (61)m

(62)m

213.94	188.81	198.74	178.85	175.69	157.68	152.30	166.17	165.72	185.65	195.37	209.11
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

 (62)

Solar DHW input calculated using Appendix H (negative quantity) ('0' entered if no solar contribution to water heating)

(63)m

0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
------	------	------	------	------	------	------	------	------	------	------	------

Σ(63)1...12 = (63)

Output from water heater for each month, kWh/month (62)m + (63)m

(64)m

213.94	188.81	198.74	178.85	175.69	157.68	152.30	166.17	165.72	185.65	195.37	209.11
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

Σ(64)1...12 = (64)

if (64)m < 0 then set to 0

Heat gains from water heating, kWh/month 0.25 x [0.85 x (45)m + (61)m] + 0.8 x [(46)m + (57)m + (59)m]

(65)m

96.12	85.35	91.09	83.69	83.47	76.69	75.71	80.30	79.33	86.74	89.15	94.52
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

 (65)
include (57)m in calculation of (65)m only if cylinder is in the dwelling or hot water is from community heating

5. Internal gains (see Table 5 and 5a)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Metabolic gains (Table 5), Watts												
(66)m	149.98	149.98	149.98	149.98	149.98	149.98	149.98	149.98	149.98	149.98	149.98	149.98

 (66)

Lighting gains (calculated in Appendix L, equation L9 or L9a), also see Table 5												
(67)m	51.09	45.37	36.90	27.94	20.88	17.63	19.05	24.76	33.24	42.20	49.25	52.51

 (67)

Appliances gains (calculated in Appendix L, equation L13 or L13a), also see Table 5												
(68)m	333.69	337.15	328.42	309.85	286.40	264.36	249.64	246.17	254.90	273.48	296.92	318.96

 (68)

Cooking gains (calculated in Appendix L, equation L15 or L15a), also see Table 5												
(69)m	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50	52.50

 (69)

Pumps and fans gains (Table 5a)												
(70)m	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00

 (70)

Losses e.g. evaporation (negative values) (Table 5)												
(71)m	-99.99	-99.99	-99.99	-99.99	-99.99	-99.99	-99.99	-99.99	-99.99	-99.99	-99.99	-99.99

 (71)

Water heating gains (Table 5)												
(72)m	129.20	127.01	122.43	116.24	112.19	106.51	101.76	107.93	110.17	116.59	123.81	127.04

 (72)

Total internal gains (66)m + (67)m + (68)m + (69)m + (70)m + (71)m + (72)m	(73)m	626.46	622.03	600.25	566.51	531.96	501.00	482.94	491.36	510.80	544.75	582.48	611.00	(73)
--	-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	------

6. Solar gains

Solar gains are calculated using solar flux from Table 6a and associated equations to convert to the applicable orientation.

Rows (74) to (82) are used 12 times, one for each month, repeating as needed if there is more than one window type.

Details for month of January and annual totals are shown below:

	Access factor Table 6d		Area m ²		Solar flux W/m ²		g Specific data or Table 6b		FF Specific data or Table 6c		Gains (W)	
Northeast	1.00	x	4.32	x	11.51	x 0.9	0.63	x	0.70	=	19.73	(75)
Southwest	1.00	x	3.96	x	37.39	x 0.9	0.63	x	0.70	=	58.76	(79)
Southeast	1.00	x	3.69	x	37.39	x 0.9	0.63	x	0.70	=	54.76	(77)

Solar gains in watts, calculated for each month $\sum(74)m \dots (82)m$

(83)m	133.25	233.91	326.22	430.47	498.04	516.48	501.89	449.16	369.93	270.46	161.01	113.06	(83)
-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	------

Total gains - internal and solar (73)m + (83)m

(84)m	759.72	855.93	926.47	996.98	1029.99	1017.48	984.83	940.52	880.73	815.22	743.49	724.06	(84)
-------	--------	--------	--------	--------	---------	---------	--------	--------	--------	--------	--------	--------	------

7. Mean internal temperature (heating season)

Temperature during heating periods in the living area from Table 9, Th1(°C)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	21.00	(85)
--	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-------	------

Utilisation factor for gains for living area, $\eta_{1,m}$ (see Table 9a)

(86)m	0.89	0.85	0.79	0.70	0.57	0.42	0.28	0.30	0.49	0.71	0.85	0.90	(86)
-------	------	------	------	------	------	------	------	------	------	------	------	------	------

Mean internal temp of living area T1 (steps 3 to 7 in Table 9c)

(87)m	19.82	20.04	20.35	20.61	20.85	20.96	20.99	20.99	20.92	20.67	20.16	19.83	(87)
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Temperature during heating periods in the living area from Table 9, Th2(°C)

(88)m	20.20	20.21	20.21	20.21	20.21	20.22	20.22	20.22	20.21	20.21	20.21	20.21	(88)
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Utilisation factor for gains for rest of dwelling $\eta_{2,m}$ (see Table 9a)

(89)m	0.88	0.84	0.77	0.67	0.53	0.37	0.23	0.24	0.44	0.67	0.84	0.88	(89)
-------	------	------	------	------	------	------	------	------	------	------	------	------	------

Mean internal temperature in the rest of dwelling T2 (follow steps 3 to 7 in Table 9c)

(90)m	19.14	19.35	19.64	19.89	20.10	20.19	20.21	20.21	20.16	19.95	19.47	19.15	(90)
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Living area fraction $f_{LA} = \frac{31.00}{(4)} = 0.38$ (91)

Mean internal temperature for the whole dwelling $f_{LA} \times T1 + (1 - f_{LA}) \times T2$

(92)m	19.39	19.61	19.91	20.16	20.38	20.48	20.51	20.51	20.45	20.22	19.73	19.41	(92)
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Apply adjustment to the mean internal temperature from Table 4e, where appropriate

(93)m	19.39	19.61	19.91	20.16	20.38	20.48	20.51	20.51	20.45	20.22	19.73	19.41	(93)
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

8. Space heating requirement

Set T_i to the mean internal temperature obtained at step 11 of Table 9b, so that $t_{im} = (93)m$ and recalculate the utilisation factor for gains using Table 9a

(94)m	0.87	0.82	0.76	0.67	0.54	0.39	0.25	0.26	0.46	0.67	0.82	0.87	(94)
-------	------	------	------	------	------	------	------	------	------	------	------	------	------

Useful gains, $\eta_m G_m$, W = (94)m x (84)m

(95)m	657.46	705.08	701.83	669.08	551.92	393.71	246.99	246.61	404.35	548.88	612.64	630.35	(95)
-------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	------

Monthly average external temperature from Table 8

(96)m	4.50	5.00	6.80	8.70	11.70	14.60	16.90	16.90	14.30	10.80	7.00	4.90	(96)
-------	------	------	------	------	-------	-------	-------	-------	-------	-------	------	------	------

Heat loss rate for mean internal temperature, L_m , W

(97)m	1051.28	1026.90	921.33	799.41	602.54	407.11	249.30	249.25	427.47	657.03	891.25	1019.55	(97)
-------	---------	---------	--------	--------	--------	--------	--------	--------	--------	--------	--------	---------	------

Space heating requirement for each month, kWh/month = $0.024 \times [(97)m - (95)m] \times (41)m$

(98)m	293.00	216.27	163.31	93.84	37.67	0.00	0.00	0.00	0.00	80.47	200.60	289.56	(98)
-------	--------	--------	--------	-------	-------	------	------	------	------	-------	--------	--------	------

Total per year (kWh/year) = $\sum(98)1 \dots 5, 10 \dots 12 = 1374.71$ (98)

Space heating requirement in kWh/m²/year $(98) \div (4) = 16.76$ (99)

9a. Energy Requirements - Individual heating systems including micro-CHP

Space heating:

Fraction of space heating from secondary/supplementary system (Table 11)	0.00	(201)
Fraction of space heating from main system(s) 1 - (201)	1.00	(202)
Fraction of main heating from main system 2	0.00	(203)
Fraction of total space heat from main system 1 (202) x [1 - (203)]	1.00	(204)
Fraction of total space heat from main system 2 (202) x (203)	0.00	(205)
Efficiency of main space heating system 1 (%)	90.80	(206)

(from database or Table 4a/4b, adjusted where appropriate by the amount shown in the 'space efficiency adjustment' column of Table 4c)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
Space heating requirement, kWh/month (as calculated above)													
(98)m	293.00	216.27	163.31	93.84	37.67	0.00	0.00	0.00	0.00	80.47	200.60	289.56	
Space heating fuel (main heating system 1), kWh/month = (98)m x (204) x 100 ÷ (206)													
(211)m	322.69	238.18	179.85	103.34	41.48	0.00	0.00	0.00	0.00	88.62	220.92	318.90	
Total per year (kWh/year) = Σ(211)1...5, 10...12 =												1513.99	(211)

Water heating:

Output from water heater, kWh/month (calculated above)													
(64)m	213.94	188.81	198.74	178.85	175.69	157.68	152.30	166.17	165.72	185.65	195.37	209.11	
Σ(64)1...12 =												2188.03	(64)
Efficiency of water heater per month													
(217)m	86.72	86.32	85.57	84.62	83.17	81.70	81.70	81.70	81.70	84.25	86.07	86.75	
Fuel for water heating, kWh/month = (64)m x 100 ÷ (217)m													
(219)m	246.69	218.74	232.25	211.36	211.23	193.00	186.42	203.39	202.84	220.35	226.99	241.06	
Total per year (kWh/year) = Σ(219)1...12 =												2594.33	(219)

Annual Totals Summary:

	kWh/year		kWh/year
Space heating fuel used, main system 1	1513.99		(211)
Water heating fuel used	2594.33		(219)
Electricity for pumps, fans and electric keep-hot (Table 4f):			
mechanical ventilation fans - balanced, extract or positive input from outside	0.00		(230a)
warm air heating system fans	0.00		(230b)
central heating pump	130.00		(230c)
oil boiler pump	0.00		(230d)
boiler flue fan	45.00		(230e)
maintaining electric keep-hot facility for gas combi boiler	0.00		(230f)
pump for solar water heating	0.00		(230g)
Total electricity for the above	Σ(230a)...(230g)	175.00	(231)
Electricity for lighting (calculated in Appendix L):		360.88	(232)
Energy saving/generation technologies (Appendices M, N and Q):			
Electricity generated by PVs (Appendix M) (negative quantity)		-3234.00	(233)

10a. Fuel costs - Individual heating systems including micro-CHP

	Fuel kWh/year		Fuel price (Table 12)		Fuel cost £/year
Space heating - main system 1	1513.99	x	3.10	x 0.01 =	46.93 (240)
Water heating cost (other fuel)	2594.33	x	3.10	x 0.01 =	80.42 (247)
Pumps, fans and electric keep-hot	175.00	x	11.46	x 0.01 =	20.06 (249)
Energy for lighting	360.88	x	11.46	x 0.01 =	41.36 (250)
Additional standing charges (Table 12)					106.00 (251)

Energy saving/generation technologies (Appendices M, N and Q):

PV savings (negative quantity)	-3234.00	x	11.46	x 0.01 =	-370.62	(252)
Total energy cost				(240)...(242) + (245)...(254)	-75.85	(255)

11a. SAP rating - Individual heating systems including micro-CHP

Energy cost deflator (Table 12)					0.47	(256)
Energy cost factor (ECF)				[(255) x (256)] ÷ [(4) + 45.0] =	-0.28	(257)
SAP value					103.92	
SAP rating					104	(258)
SAP band					A	

12a. Carbon dioxide emissions - Individual heating systems including micro-CHP

	Energy kWh/year		Emissions Factor	=	Emissions (kgCO2/year)	
Space heating - main system 1	1513.99	x	0.198	=	299.77	(261)
Water heating	2594.33	x	0.198	=	513.68	(264)
Space and water heating				(261) + (262) + (263) + (264) =	813.45	(265)
Pumps, fans and electric keep-hot	175.00	x	0.517	=	90.48	(267)
Lighting	360.88	x	0.517	=	186.58	(268)
Energy saving/generation technologies:						
PV emission savings (negative quantity)	-3234.00	x	0.529	=	-1710.79	(269)
Total carbon dioxide emissions				Σ(261)...(271) =	-620.29	(272)
Dwelling carbon dioxide emissions rate				(272) ÷ (4) =	-7.56	(273)
El value					106.54	
El rating (see section 14)					107	(274)
El band					A	

13a. Primary energy - Individual heating systems including micro-CHP

	Energy kWh/year		Primary Energy Factor	=	Primary Energy	
Space heating - main system 1	1513.99	x	1.02	=	1544.27	(261*)
Water heating	2594.33	x	1.02	=	2646.21	(264*)
Space and water heating				(261*) + (262*) + (263*) + (264*) =	4190.49	(265*)
Pumps, fans and electric keep-hot	175.00	x	2.92	=	511.00	(267*)
Lighting	360.88	x	2.92	=	1053.78	(268*)
Energy saving/generation technologies:						
PV primary energy savings (negative quantity)	-3234.00	x	2.92	=	-9443.28	(269*)
Total primary energy kWh/year				Σ(261*)...(271*) =	-3688.01	(272*)
Primary energy kWh/m2/year				(272*) ÷ (4) =	-44.98	(273*)