

Regulations Compliance Report

Approved Document L1A, 2013 Edition, England assessed by Stroma FSAP 2012 program, Version: 1.0.1.25
Printed on 03 November 2015 at 15:18:06

Project Information:

Assessed By: Joe Solti (STRO003946) **Building Type:** Semi-detached House

Dwelling Details:

NEW DWELLING DESIGN STAGE Total Floor Area: 209m²
Site Reference : TJ-34 **Plot Reference:** TJ3401
Address : Plots 1-4, 59 Ham Street, Richmond, TW10 7HR

Client Details:

Name: Ascot Design
Address :

**This report covers items included within the SAP calculations.
It is not a complete report of regulations compliance.**

1a TER and DER

Fuel for main heating system: Electricity
Fuel factor: 1.47 (electricity)
Target Carbon Dioxide Emission Rate (TER) 21.03 kg/m²
Dwelling Carbon Dioxide Emission Rate (DER) 13.65 kg/m² **OK**

1b TFEE and DFEE

Target Fabric Energy Efficiency (TFEE) 52.0 kWh/m²
Dwelling Fabric Energy Efficiency (DFEE) 47.8 kWh/m² **OK**

2 Fabric U-values

| Element | Average | Highest | |
|---------------|------------------|------------------|-----------|
| External wall | 0.22 (max. 0.30) | 0.22 (max. 0.70) | OK |
| Party wall | 0.00 (max. 0.20) | - | OK |
| Floor | 0.16 (max. 0.25) | 0.22 (max. 0.70) | OK |
| Roof | 0.12 (max. 0.20) | 0.16 (max. 0.35) | OK |
| Openings | 1.40 (max. 2.00) | 1.40 (max. 3.30) | OK |

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals 5.00 (design value)
Maximum 10.0 **OK**

4 Heating efficiency

Main Heating system: Database: (rev 383, product index 100013):
Heat pumps with radiators or underfloor heating - electric
Brand name:
Model:
Model qualifier:
()
Minimum 88.0 %

Secondary heating system: Room heaters - wood
Closed room heater
Efficiency 65.0 %
Minimum 65.0 % **OK**

Regulations Compliance Report

5 Cylinder insulation

Hot water Storage: Measured cylinder loss: 1.60 kWh/day
Permitted by DBSCG: 2.86 kWh/day

Primary pipework insulated: Yes

OK

6 Controls

Space heating controls TTZC by plumbing and electrical services

Hot water controls: Cylinderstat
Independent timer for DHW

Boiler interlock: Yes

OK

OK

OK

OK

7 Low energy lights

Percentage of fixed lights with low-energy fittings 100.0%

Minimum 75.0%

OK

8 Mechanical ventilation

Not applicable

9 Summertime temperature

Overheating risk (Thames valley): Not significant

OK

Based on:

Overshading: Average or unknown

Windows facing: North East 12m²

Windows facing: South East 12m²

Ventilation rate: 4.00

Blinds/curtains: None

Closed 100% of daylight hours

10 Key features

Thermal bridging 0.037 W/m²K

Roofs U-value 0.11 W/m²K

Party Walls U-value 0 W/m²K

Secondary heating (wood logs)

Secondary heating fuel wood logs

Predicted Energy Assessment




Plots 1-4
59 Ham Street
Richmond
TW10 7HR

Dwelling type:
Date of assessment:
Produced by:
Total floor area:

Semi-detached House
03 November 2015
Joe Solti
209 m²

This is a Predicted Energy Assessment for a property which is not yet complete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, an Energy Performance Certificate is required providing information about the energy performance of the completed property.

Energy performance has been assessed using the SAP 2012 methodology and is rated in terms of the energy use per square metre of floor area, energy efficiency based on fuel costs and environmental impact based on carbon dioxide (CO₂) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO₂) emissions. The higher the rating the less impact it has on the environment.

SAP Input

Property Details: TJ3401

Address: Plots 1-4, 59 Ham Street, Richmond, TW10 7HR
 Located in: England
 Region: Thames valley
 UPRN:
 Date of assessment: 03 November 2015
 Date of certificate: 03 November 2015
 Assessment type: New dwelling design stage
 Transaction type: New dwelling
 Tenure type: Unknown
 Related party disclosure: No related party
 Thermal Mass Parameter: Indicative Value Medium
 Water use <= 125 litres/person/day: True
 PCDF Version: 383

Property description:

Dwelling type: House
 Detachment: Semi-detached
 Year Completed: 2015
 Floor Location: Floor area: Storey height:
 Basement floor 71 m² 2.8 m
 Floor 1 69 m² 3 m
 Floor 2 69 m² 2.5 m
 Living area: 28 m² (fraction 0.134)
 Front of dwelling faces: North East

Opening types:

| Name: | Source: | Type: | Glazing: | Argon: | Frame: |
|-----------------|--------------|-------------|-----------------------------|--------|--------|
| Front Door | Manufacturer | Half glazed | low-E, En = 0.05, soft coat | Yes | Wood |
| Windows (NE/NW) | SAP 2012 | Windows | low-E, En = 0.05, soft coat | Yes | Wood |
| Windows (SE/SW) | SAP 2012 | Windows | low-E, En = 0.05, soft coat | Yes | Wood |

| Name: | Gap: | Frame Factor: | g-value: | U-value: | Area: | No. of Openings: |
|-----------------|-----------------|---------------|----------|----------|-------|------------------|
| Front Door | 16mm or more mm | 0.7 | 0.63 | 1.4 | 2.5 | 1 |
| Windows (NE/NW) | 16mm or more | 0.7 | 0.63 | 1.4 | 12 | 1 |
| Windows (SE/SW) | 16mm or more | 0.7 | 0.63 | 1.4 | 12 | 1 |

| Name: | Type-Name: | Location: | Orient: | Width: | Height: |
|-----------------|------------|-----------|------------|--------|---------|
| Front Door | | Wall | North East | 0 | 0 |
| Windows (NE/NW) | | Wall | North East | 0 | 0 |
| Windows (SE/SW) | | Wall | South East | 0 | 0 |

Overshading: Average or unknown

Opaque Elements:

| Type: | Gross area: | Openings: | Net area: | U-value: | Ru value: | Curtain wall: | Kappa: |
|--------------------------|-------------|-----------|-----------|----------|-----------|---------------|--------|
| <u>External Elements</u> | | | | | | | |
| Wall | 198 | 26.5 | 171.5 | 0.22 | 0 | False | N/A |
| Roof (loft) | 63 | 0 | 63 | 0.11 | 0 | | N/A |
| Roof (skeilings) | 10 | 0 | 10 | 0.16 | 0 | | N/A |
| Basement Floor | 71 | | | 0.16 | | | N/A |
| Exposed Upper Floor | 4 | | | 0.22 | | | N/A |
| <u>Internal Elements</u> | | | | | | | |
| <u>Party Elements</u> | | | | | | | |
| Party Walls | 90 | | | | | | N/A |

SAP Input

Thermal bridges:

| | | | | |
|------------------|-------------------------------------------------------|------------------|-----|------------------------------------------------------------|
| Thermal bridges: | User-defined (individual PSI-values) Y-Value = 0.0365 | | | |
| | Length | Psi-value | | |
| | 11 | 0.056 | E2 | Other lintels (including other steel lintels) |
| | 15 | 0.038 | E3 | Sill |
| | 52 | 0.042 | E4 | Jamb |
| | 24 | 0.061 | E5 | Ground floor (normal) |
| | 48 | 0 | E6 | Intermediate floor within a dwelling |
| [Approved] | 0 | 0.06 | E10 | Eaves (insulation at ceiling level) |
| [Approved] | 0 | 0.04 | E11 | Eaves (insulation at rafter level) |
| [Approved] | 11 | 0.24 | E12 | Gable (insulation at ceiling level) |
| [Approved] | 12.5 | 0.04 | E13 | Gable (insulation at rafter level) |
| | 16 | 0.052 | E16 | Corner (normal) |
| [Approved] | 0 | -0.09 | E17 | Corner (inverted internal area greater than external area) |
| [Approved] | 32 | 0.06 | E18 | Party wall between dwellings |
| | 6 | 0.32 | E20 | Exposed floor (normal) |

Ventilation:

| | |
|----------------------------|-------------------------------------|
| Pressure test: | Yes (As designed) |
| Ventilation: | Natural ventilation (extract fans) |
| Number of chimneys: | 0 |
| Number of open flues: | 1 (main: 0, secondary: 1, other: 0) |
| Number of fans: | 6 |
| Number of passive stacks: | 0 |
| Number of sides sheltered: | 2 |
| Pressure test: | 5 |

Main heating system:

| | |
|----------------------|--------------------------------------------------------------------|
| Main heating system: | Heat pumps with radiators or underfloor heating |
| | Electric heat pumps |
| | Fuel: Electricity |
| | Info Source: Boiler Database |
| | Database: (rev 383, product index 100013, SEDBUK 400%): |
| | Brand name: Daikin Altherma |
| | Model: ERHQ006BV3 + EKHBH008B |
| | Model qualifier: Underfloor |
| | (provides DHW all year) |
| | Underfloor heating and radiators, pipes in screed above insulation |
| | Central heating pump : 2012 or earlier |
| | Design flow temperature: Design flow temperature >45°C |
| | Unknown |
| | Boiler interlock: Yes |

Main heating Control:

| | |
|-----------------------|-----------------------------------------------------------------------------------------------|
| Main heating Control: | Time and temperature zone control by suitable arrangement of plumbing and electrical services |
| | Control code: 2207 |

Secondary heating system:

| | |
|---------------------------|-------------------------|
| Secondary heating system: | Room heaters |
| | Solid fuel room heaters |
| | Fuel :wood logs |
| | Info Source: SAP Tables |
| | Closed room heater |
| | HETAS Approved |

Water heating:

| | |
|----------------|--------------------------|
| Water heating: | From main heating system |
|----------------|--------------------------|

SAP Input

Water code: 901
Fuel :Electricity
Hot water cylinder
Cylinder volume: 300 litres
Cylinder insulation: Measured loss, 1.6kWh/day
Primary pipework insulation: True
Cylinderstat: True
Cylinder in heated space: True
Solar panel: False

Others:

| | |
|--------------------------|---------------------------|
| Electricity tariff: | Standard Tariff |
| In Smoke Control Area: | Unknown |
| Conservatory: | No conservatory |
| Low energy lights: | 100% |
| Terrain type: | Low rise urban / suburban |
| EPC language: | English |
| Wind turbine: | No |
| Photovoltaics: | None |
| Assess Zero Carbon Home: | No |

SAP WorkSheet: New dwelling design stage

User Details:

| | | | |
|-----------------------|------------------|--------------------------|-------------------|
| Assessor Name: | Joe Solti | Stroma Number: | STRO003946 |
| Software Name: | Stroma FSAP 2012 | Software Version: | Version: 1.0.1.25 |

Property Address: TJ3401

Address : Plots 1-4, 59 Ham Street, Richmond, TW10 7HR

1. Overall dwelling dimensions:

| | Area(m ²) | | Av. Height(m) | | Volume(m ³) |
|------------------------------------------------------|-----------------------|--------|---------------|--------------------------------------|-------------------------|
| Basement | 71 | (1a) x | 2.8 | (2a) = | 198.8 |
| Ground floor | 69 | (1b) x | 3 | (2b) = | 207 |
| First floor | 69 | (1c) x | 2.5 | (2c) = | 172.5 |
| Total floor area TFA = (1a)+(1b)+(1c)+(1d)+.....(1n) | 209 | (4) | | | |
| Dwelling volume | | | | (3a)+(3b)+(3c)+(3d)+(3e)+.....(3n) = | 578.3 |

2. Ventilation rate:

| | main heating | | secondary heating | | other | | total | | m ³ per hour |
|------------------------------|--------------|---|-------------------|---|-------|---|-------|--------|-------------------------|
| Number of chimneys | 0 | + | 0 | + | 0 | = | 0 | x 40 = | 0 |
| Number of open flues | 0 | + | 1 | + | 0 | = | 1 | x 20 = | 20 |
| Number of intermittent fans | | | | | | | 6 | x 10 = | 60 |
| Number of passive vents | | | | | | | 0 | x 10 = | 0 |
| Number of flueless gas fires | | | | | | | 0 | x 40 = | 0 |

Air changes per hour

| | | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|---------------|------|------|
| Infiltration due to chimneys, flues and fans = (6a)+(6b)+(7a)+(7b)+(7c) = | 80 | ÷ (5) = | 0.14 | (8) |
| <i>If a pressurisation test has been carried out or is intended, proceed to (17), otherwise continue from (9) to (16)</i> | | | | |
| Number of storeys in the dwelling (ns) | | | 0 | (9) |
| Additional infiltration | | [(9)-1]x0.1 = | 0 | (10) |
| Structural infiltration: 0.25 for steel or timber frame or 0.35 for masonry construction <i>if both types of wall are present, use the value corresponding to the greater wall area (after deducting areas of openings); if equal user 0.35</i> | | | 0 | (11) |
| If suspended wooden floor, enter 0.2 (unsealed) or 0.1 (sealed), else enter 0 | | | 0 | (12) |
| If no draught lobby, enter 0.05, else enter 0 | | | 0 | (13) |
| Percentage of windows and doors draught stripped | | | 0 | (14) |
| Window infiltration | 0.25 - [0.2 x (14) ÷ 100] = | | 0 | (15) |
| Infiltration rate | (8) + (10) + (11) + (12) + (13) + (15) = | | 0 | (16) |
| Air permeability value, q50, expressed in cubic metres per hour per square metre of envelope area | | | 5 | (17) |
| If based on air permeability value, then (18) = [(17) ÷ 20]+(8), otherwise (18) = (16) | | | 0.39 | (18) |
| <i>Air permeability value applies if a pressurisation test has been done or a degree air permeability is being used</i> | | | | |
| Number of sides sheltered | | | 2 | (19) |
| Shelter factor | (20) = 1 - [0.075 x (19)] = | | 0.85 | (20) |
| Infiltration rate incorporating shelter factor | (21) = (18) x (20) = | | 0.33 | (21) |

Infiltration rate modified for monthly wind speed

| | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|

Monthly average wind speed from Table 7

| | | | | | | | | | | | | |
|--------|-----|---|-----|-----|-----|-----|-----|-----|---|-----|-----|-----|
| (22)m= | 5.1 | 5 | 4.9 | 4.4 | 4.3 | 3.8 | 3.8 | 3.7 | 4 | 4.3 | 4.5 | 4.7 |
|--------|-----|---|-----|-----|-----|-----|-----|-----|---|-----|-----|-----|

SAP WorkSheet: New dwelling design stage

Wind Factor (22a)m = (22)m ÷ 4

| | | | | | | | | | | | | |
|---------|------|------|------|-----|------|------|------|------|---|------|------|------|
| (22a)m= | 1.27 | 1.25 | 1.23 | 1.1 | 1.08 | 0.95 | 0.95 | 0.92 | 1 | 1.08 | 1.12 | 1.18 |
|---------|------|------|------|-----|------|------|------|------|---|------|------|------|

Adjusted infiltration rate (allowing for shelter and wind speed) = (21a) x (22a)m

| | | | | | | | | | | | | |
|--|------|------|-----|------|------|------|------|------|------|------|------|------|
| | 0.42 | 0.41 | 0.4 | 0.36 | 0.35 | 0.31 | 0.31 | 0.31 | 0.33 | 0.35 | 0.37 | 0.39 |
|--|------|------|-----|------|------|------|------|------|------|------|------|------|

Calculate effective air change rate for the applicable case

If mechanical ventilation:

0 (23a)

If exhaust air heat pump using Appendix N, (23b) = (23a) x Fmv (equation (N5)) , otherwise (23b) = (23a)

0 (23b)

If balanced with heat recovery: efficiency in % allowing for in-use factor (from Table 4h) =

0 (23c)

a) If balanced mechanical ventilation with heat recovery (MVHR) (24a)m = (22b)m + (23b) x [1 - (23c) ÷ 100]

| | | | | | | | | | | | | |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|
| (24a)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|

b) If balanced mechanical ventilation without heat recovery (MV) (24b)m = (22b)m + (23b)

| | | | | | | | | | | | | |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|
| (24b)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|

c) If whole house extract ventilation or positive input ventilation from outside

if (22b)m < 0.5 x (23b), then (24c) = (23b); otherwise (24c) = (22b) m + 0.5 x (23b)

| | | | | | | | | | | | | |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|
| (24c)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|

d) If natural ventilation or whole house positive input ventilation from loft

if (22b)m = 1, then (24d)m = (22b)m otherwise (24d)m = 0.5 + [(22b)m² x 0.5]

| | | | | | | | | | | | | |
|---------|------|------|------|------|------|------|------|------|------|------|------|------|
| (24d)m= | 0.59 | 0.59 | 0.58 | 0.57 | 0.56 | 0.55 | 0.55 | 0.55 | 0.55 | 0.56 | 0.57 | 0.58 |
|---------|------|------|------|------|------|------|------|------|------|------|------|------|

Effective air change rate - enter (24a) or (24b) or (24c) or (24d) in box (25)

| | | | | | | | | | | | | |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|
| (25)m= | 0.59 | 0.59 | 0.58 | 0.57 | 0.56 | 0.55 | 0.55 | 0.55 | 0.55 | 0.56 | 0.57 | 0.58 |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|

3. Heat losses and heat loss parameter:

| ELEMENT | Gross area (m ²) | Openings m ² | Net Area A ,m ² | U-value W/m ² K | A X U (W/K) | k-value kJ/m ² -K | A X k kJ/K |
|----------------------------------------|------------------------------|-------------------------|----------------------------|----------------------------|-------------|------------------------------|------------|
| Doors | | | 2.5 | 1.4 | 3.5 | | (26) |
| Windows Type 1 | | | 12 | $1/[1/(1.4)+0.04]$ | 15.91 | | (27) |
| Windows Type 2 | | | 12 | $1/[1/(1.4)+0.04]$ | 15.91 | | (27) |
| Floor Type 1 | | | 71 | 0.16 | 11.36 | | (28) |
| Floor Type 2 | | | 4 | 0.22 | 0.88 | | (28) |
| Walls | 198 | 26.5 | 171.5 | 0.22 | 37.73 | | (29) |
| Roof Type1 | 63 | 0 | 63 | 0.11 | 6.93 | | (30) |
| Roof Type2 | 10 | 0 | 10 | 0.16 | 1.6 | | (30) |
| Total area of elements, m ² | | | 346 | | | | (31) |
| Party wall | | | 90 | 0 | 0 | | (32) |

* for windows and roof windows, use effective window U-value calculated using formula $1/[1/U\text{-value}+0.04]$ as given in paragraph 3.2

** include the areas on both sides of internal walls and partitions

Fabric heat loss, W/K = S (A x U) (26)...(30) + (32) = 93.82 (33)

Heat capacity Cm = S(A x k) ((28)...(30) + (32) + (32a)...(32e) = 36752 (34)

Thermal mass parameter (TMP = Cm ÷ TFA) in kJ/m²K Indicative Value: Medium 250 (35)

For design assessments where the details of the construction are not known precisely the indicative values of TMP in Table 1f can be used instead of a detailed calculation.

Thermal bridges : S (L x Y) calculated using Appendix K 12.65 (36)

SAP WorkSheet: New dwelling design stage

if details of thermal bridging are not known (36) = 0.15 x (31)

Total fabric heat loss (33) + (36) = (37)

Ventilation heat loss calculated monthly (38)m = 0.33 x (25)m x (5)

| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | |
|--------|--------|--------|--------|-----|--------|-------|-------|--------|--------|--------|--------|--------|------|
| (38)m= | 112.32 | 111.66 | 111.02 | 108 | 107.43 | 104.8 | 104.8 | 104.32 | 105.82 | 107.43 | 108.58 | 109.77 | (38) |

Heat transfer coefficient, W/K (39)m = (37) + (38)m

| | | | | | | | | | | | | | |
|--------------------------------------------|--------|--------|--------|--------|-------|--------|--------|--------|--------|-------|--------|------------------------------------------|--|
| (39)m= | 218.78 | 218.13 | 217.49 | 214.46 | 213.9 | 211.27 | 211.27 | 210.78 | 212.28 | 213.9 | 215.04 | 216.24 | |
| Average = Sum(39) _{1...12} / 12 = | | | | | | | | | | | | <input type="text" value="214.46"/> (39) | |

Heat loss parameter (HLP), W/m²K (40)m = (39)m ÷ (4)

| | | | | | | | | | | | | | |
|--------------------------------------------|------|------|------|------|------|------|------|------|------|------|------|----------------------------------------|--|
| (40)m= | 1.05 | 1.04 | 1.04 | 1.03 | 1.02 | 1.01 | 1.01 | 1.01 | 1.02 | 1.02 | 1.03 | 1.03 | |
| Average = Sum(40) _{1...12} / 12 = | | | | | | | | | | | | <input type="text" value="1.03"/> (40) | |

Number of days in month (Table 1a)

| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | |
|--------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| (41)m= | 31 | 28 | 31 | 30 | 31 | 30 | 31 | 31 | 30 | 31 | 30 | 31 | (41) |

4. Water heating energy requirement:

kWh/year:

Assumed occupancy, N (42)

if TFA > 13.9, N = 1 + 1.76 x [1 - exp(-0.000349 x (TFA - 13.9)²)] + 0.0013 x (TFA - 13.9)

if TFA ≤ 13.9, N = 1

Annual average hot water usage in litres per day V_{d,average} = (25 x N) + 36 (43)

Reduce the annual average hot water usage by 5% if the dwelling is designed to achieve a water use target of not more than 125 litres per person per day (all water use, hot and cold)

| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | |
|-------------------------------------|--------|--------|--------|--------|-------|------|------|-------|--------|--------|--------|-------------------------------------------|--|
| (44)m= | 116.35 | 112.12 | 107.89 | 103.66 | 99.43 | 95.2 | 95.2 | 99.43 | 103.66 | 107.89 | 112.12 | 116.35 | |
| Total = Sum(44) _{1...12} = | | | | | | | | | | | | <input type="text" value="1269.28"/> (44) | |

Energy content of hot water used - calculated monthly = 4.190 x V_{d,m} x nm x DT_m / 3600 kWh/month (see Tables 1b, 1c, 1d)

| | | | | | | | | | | | | | |
|-------------------------------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------------------------------------------|--|
| (45)m= | 172.55 | 150.91 | 155.72 | 135.76 | 130.27 | 112.41 | 104.17 | 119.53 | 120.96 | 140.97 | 153.88 | 167.1 | |
| Total = Sum(45) _{1...12} = | | | | | | | | | | | | <input type="text" value="1664.23"/> (45) | |

If instantaneous water heating at point of use (no hot water storage), enter 0 in boxes (46) to (61)

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (46)m= | 25.88 | 22.64 | 23.36 | 20.36 | 19.54 | 16.86 | 15.63 | 17.93 | 18.14 | 21.15 | 23.08 | 25.07 | (46) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

Water storage loss:

Storage volume (litres) including any solar or WWHRS storage within same vessel (47)

If community heating and no tank in dwelling, enter 110 litres in (47)

Otherwise if no stored hot water (this includes instantaneous combi boilers) enter '0' in (47)

Water storage loss:

a) If manufacturer's declared loss factor is known (kWh/day): (48)

Temperature factor from Table 2b (49)

Energy lost from water storage, kWh/year (48) x (49) = (50)

b) If manufacturer's declared cylinder loss factor is not known:

Hot water storage loss factor from Table 2 (kWh/litre/day) (51)

If community heating see section 4.3

Volume factor from Table 2a (52)

Temperature factor from Table 2b (53)

Energy lost from water storage, kWh/year (47) x (51) x (52) x (53) = (54)

Enter (50) or (54) in (55) (55)

SAP WorkSheet: New dwelling design stage

Water storage loss calculated for each month

$$((56)m = (55) \times (41)m$$

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (56)m= | 26.78 | 24.19 | 26.78 | 25.92 | 26.78 | 25.92 | 26.78 | 26.78 | 25.92 | 26.78 | 25.92 | 26.78 | (56) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

If cylinder contains dedicated solar storage, (57)m = (56)m x [(50) - (H11)] ÷ (50), else (57)m = (56)m where (H11) is from Appendix H

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (57)m= | 26.78 | 24.19 | 26.78 | 25.92 | 26.78 | 25.92 | 26.78 | 26.78 | 25.92 | 26.78 | 25.92 | 26.78 | (57) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

Primary circuit loss (annual) from Table 3

| | |
|---|------|
| 0 | (58) |
|---|------|

Primary circuit loss calculated for each month (59)m = (58) ÷ 365 × (41)m

(modified by factor from Table H5 if there is solar water heating and a cylinder thermostat)

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|---|---|---|---|-------|-------|-------|------|
| (59)m= | 23.26 | 21.01 | 23.26 | 22.51 | 23.26 | 0 | 0 | 0 | 0 | 23.26 | 22.51 | 23.26 | (59) |
|--------|-------|-------|-------|-------|-------|---|---|---|---|-------|-------|-------|------|

Combi loss calculated for each month (61)m = (60) ÷ 365 × (41)m

| | | | | | | | | | | | | | |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|
| (61)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | (61) |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|

Total heat required for water heating calculated for each month (62)m = 0.85 × (45)m + (46)m + (57)m + (59)m + (61)m

| | | | | | | | | | | | | | |
|--------|--------|--------|--------|-------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (62)m= | 222.59 | 196.11 | 205.77 | 184.2 | 180.32 | 138.33 | 130.95 | 146.32 | 146.88 | 191.01 | 202.31 | 217.15 | (62) |
|--------|--------|--------|--------|-------|--------|--------|--------|--------|--------|--------|--------|--------|------|

Solar DHW input calculated using Appendix G or Appendix H (negative quantity) (enter '0' if no solar contribution to water heating)

(add additional lines if FGHRs and/or WWHRs applies, see Appendix G)

| | | | | | | | | | | | | | |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|
| (63)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | (63) |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|

Output from water heater

| | | | | | | | | | | | | | | |
|-----------------------------------------------------|--------|--------|--------|-------|--------|---|---|---|---|--------|--------|--------|---------|------|
| (64)m= | 222.59 | 196.11 | 205.77 | 184.2 | 180.32 | 0 | 0 | 0 | 0 | 191.01 | 202.31 | 217.15 | 1599.46 | (64) |
| Output from water heater (annual) _{1...12} | | | | | | | | | | | | | | |

Output immersion

| | | | | | | | | | | | | | | |
|--------------------------------------------------|---|---|---|---|---|--------|--------|--------|--------|---|---|---|------------------|------|
| (64)m= | 0 | 0 | 0 | 0 | 0 | 138.33 | 130.95 | 146.32 | 146.88 | 0 | 0 | 0 | 562.480541922569 | (64) |
| Output from immersion (annual) _{1...12} | | | | | | | | | | | | | | |

Heat gains from water heating, kWh/month $0.25 \times [0.85 \times (45)m + (61)m] + 0.8 \times [(46)m + (57)m + (59)m]$

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|------|
| (65)m= | 97.41 | 86.34 | 91.82 | 83.89 | 83.35 | 58.11 | 56.06 | 61.17 | 60.96 | 86.91 | 89.91 | 95.6 | (65) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|------|

include (57)m in calculation of (65)m only if cylinder is in the dwelling or hot water is from community heating

5. Internal gains (see Table 5 and 5a):

Metabolic gains (Table 5), Watts

| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (66)m= | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | 180.82 | (66) |

Lighting gains (calculated in Appendix L, equation L9 or L9a), also see Table 5

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (67)m= | 92.75 | 82.38 | 66.99 | 50.72 | 37.91 | 32.01 | 34.59 | 44.96 | 60.34 | 76.61 | 89.42 | 95.33 | (67) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

Appliances gains (calculated in Appendix L, equation L13 or L13a), also see Table 5

| | | | | | | | | | | | | | |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|--------|--------|--------|------|
| (68)m= | 566.45 | 572.33 | 557.51 | 525.98 | 486.18 | 448.76 | 423.77 | 417.89 | 432.7 | 464.24 | 504.04 | 541.46 | (68) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|--------|--------|--------|------|

Cooking gains (calculated in Appendix L, equation L15 or L15a), also see Table 5

| | | | | | | | | | | | | | |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| (69)m= | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | 56.1 | (69) |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|

Pumps and fans gains (Table 5a)

| | | | | | | | | | | | | | |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|
| (70)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | (70) |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|

Losses e.g. evaporation (negative values) (Table 5)

| | | | | | | | | | | | | | |
|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|------|
| (71)m= | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | -120.55 | (71) |
|--------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|------|

Water heating gains (Table 5)

| | | | | | | | | | | | | | |
|--------|--------|--------|--------|--------|--------|-------|-------|-------|-------|--------|--------|--------|------|
| (72)m= | 130.93 | 128.48 | 123.41 | 116.51 | 112.03 | 80.71 | 75.35 | 82.22 | 84.66 | 116.81 | 124.87 | 128.49 | (72) |
|--------|--------|--------|--------|--------|--------|-------|-------|-------|-------|--------|--------|--------|------|

Total internal gains =

$$(66)m + (67)m + (68)m + (69)m + (70)m + (71)m + (72)m$$

| | | | | | | | | | | | | | |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (73)m= | 906.49 | 899.55 | 864.28 | 809.58 | 752.49 | 677.85 | 650.08 | 661.44 | 694.07 | 774.03 | 834.71 | 881.64 | (73) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|

SAP WorkSheet: New dwelling design stage

6. Solar gains:

Solar gains are calculated using solar flux from Table 6a and associated equations to convert to the applicable orientation.

| Orientation: | Access Factor Table 6d | Area m ² | Flux Table 6a | g_ Table 6b | FF Table 6c | Gains (W) |
|----------------|---------------------------|------------------------|------------------|----------------|----------------|--------------|
| Northeast 0.9x | 0.77 | 12 | 11.28 | 0.63 | 0.7 | 41.38 (75) |
| Northeast 0.9x | 0.77 | 12 | 22.97 | 0.63 | 0.7 | 84.23 (75) |
| Northeast 0.9x | 0.77 | 12 | 41.38 | 0.63 | 0.7 | 151.75 (75) |
| Northeast 0.9x | 0.77 | 12 | 67.96 | 0.63 | 0.7 | 249.22 (75) |
| Northeast 0.9x | 0.77 | 12 | 91.35 | 0.63 | 0.7 | 335 (75) |
| Northeast 0.9x | 0.77 | 12 | 97.38 | 0.63 | 0.7 | 357.14 (75) |
| Northeast 0.9x | 0.77 | 12 | 91.1 | 0.63 | 0.7 | 334.1 (75) |
| Northeast 0.9x | 0.77 | 12 | 72.63 | 0.63 | 0.7 | 266.35 (75) |
| Northeast 0.9x | 0.77 | 12 | 50.42 | 0.63 | 0.7 | 184.91 (75) |
| Northeast 0.9x | 0.77 | 12 | 28.07 | 0.63 | 0.7 | 102.93 (75) |
| Northeast 0.9x | 0.77 | 12 | 14.2 | 0.63 | 0.7 | 52.06 (75) |
| Northeast 0.9x | 0.77 | 12 | 9.21 | 0.63 | 0.7 | 33.79 (75) |
| Southeast 0.9x | 0.77 | 12 | 36.79 | 0.63 | 0.7 | 134.94 (77) |
| Southeast 0.9x | 0.77 | 12 | 62.67 | 0.63 | 0.7 | 229.85 (77) |
| Southeast 0.9x | 0.77 | 12 | 85.75 | 0.63 | 0.7 | 314.49 (77) |
| Southeast 0.9x | 0.77 | 12 | 106.25 | 0.63 | 0.7 | 389.66 (77) |
| Southeast 0.9x | 0.77 | 12 | 119.01 | 0.63 | 0.7 | 436.45 (77) |
| Southeast 0.9x | 0.77 | 12 | 118.15 | 0.63 | 0.7 | 433.3 (77) |
| Southeast 0.9x | 0.77 | 12 | 113.91 | 0.63 | 0.7 | 417.75 (77) |
| Southeast 0.9x | 0.77 | 12 | 104.39 | 0.63 | 0.7 | 382.84 (77) |
| Southeast 0.9x | 0.77 | 12 | 92.85 | 0.63 | 0.7 | 340.52 (77) |
| Southeast 0.9x | 0.77 | 12 | 69.27 | 0.63 | 0.7 | 254.03 (77) |
| Southeast 0.9x | 0.77 | 12 | 44.07 | 0.63 | 0.7 | 161.62 (77) |
| Southeast 0.9x | 0.77 | 12 | 31.49 | 0.63 | 0.7 | 115.48 (77) |

Solar gains in watts, calculated for each month (83)m = Sum(74)m ... (82)m

| | | | | | | | | | | | | | |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (83)m= | 176.31 | 314.07 | 466.24 | 638.88 | 771.45 | 790.44 | 751.85 | 649.19 | 525.43 | 356.96 | 213.69 | 149.27 | (83) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|

Total gains – internal and solar (84)m = (73)m + (83)m , watts

| | | | | | | | | | | | | | |
|--------|--------|---------|---------|---------|---------|---------|---------|---------|--------|------|---------|---------|------|
| (84)m= | 1082.8 | 1213.63 | 1330.52 | 1448.46 | 1523.94 | 1468.29 | 1401.92 | 1310.62 | 1219.5 | 1131 | 1048.39 | 1030.91 | (84) |
|--------|--------|---------|---------|---------|---------|---------|---------|---------|--------|------|---------|---------|------|

7. Mean internal temperature (heating season)

Temperature during heating periods in the living area from Table 9, Th1 (°C) 21 (85)

Utilisation factor for gains for living area, h1,m (see Table 9a)

| | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | |
|--------|-----|-----|------|------|------|------|------|-----|------|------|-----|-----|------|
| (86)m= | 1 | 1 | 0.99 | 0.98 | 0.93 | 0.81 | 0.64 | 0.7 | 0.91 | 0.99 | 1 | 1 | (86) |

Mean internal temperature in living area T1 (follow steps 3 to 7 in Table 9c)

| | | | | | | | | | | | | | |
|--------|----|----|----|----|----|----|----|----|----|----|----|----|------|
| (87)m= | 21 | 21 | 21 | 21 | 21 | 21 | 21 | 21 | 21 | 21 | 21 | 21 | (87) |
|--------|----|----|----|----|----|----|----|----|----|----|----|----|------|

Temperature during heating periods in rest of dwelling from Table 9, Th2 (°C)

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (88)m= | 20.04 | 20.05 | 20.05 | 20.06 | 20.06 | 20.07 | 20.07 | 20.08 | 20.07 | 20.06 | 20.06 | 20.05 | (88) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

SAP WorkSheet: New dwelling design stage

Utilisation factor for gains for rest of dwelling, h2,m (see Table 9a)

| | | | | | | | | | | | | | |
|--------|---|---|------|------|------|------|------|------|------|------|---|---|------|
| (89)m= | 1 | 1 | 0.99 | 0.97 | 0.91 | 0.73 | 0.52 | 0.58 | 0.86 | 0.98 | 1 | 1 | (89) |
|--------|---|---|------|------|------|------|------|------|------|------|---|---|------|

Mean internal temperature in the rest of dwelling T2 (follow steps 3 to 7 in Table 9c)

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (90)m= | 20.04 | 20.05 | 20.05 | 20.06 | 20.06 | 20.07 | 20.07 | 20.08 | 20.07 | 20.06 | 20.06 | 20.05 | (90) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

$fLA = \text{Living area} \div (4) =$

| |
|------|
| 0.13 |
|------|

 (91)

Mean internal temperature (for the whole dwelling) = $fLA \times T1 + (1 - fLA) \times T2$

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|------|------|------|-------|-------|-------|-------|------|
| (92)m= | 20.17 | 20.17 | 20.18 | 20.19 | 20.19 | 20.2 | 20.2 | 20.2 | 20.19 | 20.19 | 20.19 | 20.18 | (92) |
|--------|-------|-------|-------|-------|-------|------|------|------|-------|-------|-------|-------|------|

Apply adjustment to the mean internal temperature from Table 4e, where appropriate

| | | | | | | | | | | | | | |
|--------|-------|-------|-------|-------|-------|------|------|------|-------|-------|-------|-------|------|
| (93)m= | 20.17 | 20.17 | 20.18 | 20.19 | 20.19 | 20.2 | 20.2 | 20.2 | 20.19 | 20.19 | 20.19 | 20.18 | (93) |
|--------|-------|-------|-------|-------|-------|------|------|------|-------|-------|-------|-------|------|

8. Space heating requirement

Set T_i to the mean internal temperature obtained at step 11 of Table 9b, so that $T_{i,m}=(76)m$ and re-calculate the utilisation factor for gains using Table 9a

| Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|

Utilisation factor for gains, hm:

| | | | | | | | | | | | | | |
|--------|---|---|------|------|------|------|------|-----|------|------|---|---|------|
| (94)m= | 1 | 1 | 0.99 | 0.98 | 0.91 | 0.74 | 0.53 | 0.6 | 0.87 | 0.98 | 1 | 1 | (94) |
|--------|---|---|------|------|------|------|------|-----|------|------|---|---|------|

Useful gains, hmGm , $W = (94)m \times (84)m$

| | | | | | | | | | | | | | |
|--------|---------|---------|---------|---------|---------|---------|--------|--------|--------|---------|---------|---------|------|
| (95)m= | 1081.46 | 1210.44 | 1321.29 | 1412.89 | 1387.34 | 1092.08 | 748.56 | 780.31 | 1062.7 | 1111.66 | 1045.51 | 1029.95 | (95) |
|--------|---------|---------|---------|---------|---------|---------|--------|--------|--------|---------|---------|---------|------|

Monthly average external temperature from Table 8

| | | | | | | | | | | | | | |
|--------|-----|-----|-----|-----|------|------|------|------|------|------|-----|-----|------|
| (96)m= | 4.3 | 4.9 | 6.5 | 8.9 | 11.7 | 14.6 | 16.6 | 16.4 | 14.1 | 10.6 | 7.1 | 4.2 | (96) |
|--------|-----|-----|-----|-----|------|------|------|------|------|------|-----|-----|------|

Heat loss rate for mean internal temperature, $L_m , W = [(93)m - (96)m]$

| | | | | | | | | | | | | | |
|--------|---------|---------|---------|---------|---------|---------|--------|--------|---------|---------|--------|---------|------|
| (97)m= | 3472.66 | 3331.86 | 2974.53 | 2420.72 | 1815.84 | 1182.74 | 760.21 | 800.96 | 1293.81 | 2051.13 | 2813.9 | 3455.74 | (97) |
|--------|---------|---------|---------|---------|---------|---------|--------|--------|---------|---------|--------|---------|------|

Space heating requirement for each month, kWh/month = $0.024 \times [(97)m - (95)m] \times (41)m$

| | | | | | | | | | | | | | |
|--------|---------|---------|---------|--------|-------|---|---|---|---|--------|---------|---------|------|
| (98)m= | 1779.05 | 1425.59 | 1230.01 | 725.64 | 318.8 | 0 | 0 | 0 | 0 | 698.96 | 1273.24 | 1804.79 | (98) |
|--------|---------|---------|---------|--------|-------|---|---|---|---|--------|---------|---------|------|

Total per year (kWh/year) = $\text{Sum}(98)_{1...5,9...12} =$

| |
|---------|
| 9256.09 |
|---------|

 (98)

Space heating requirement in kWh/m²/year

| | |
|-------|------|
| 44.29 | (99) |
|-------|------|

9a. Energy requirements – Individual heating systems including micro-CHP

Space heating:

Fraction of space heat from secondary/supplementary system

| |
|---|
| 0 |
|---|

 (201)

Fraction of space heat from main system(s) (202) = $1 - (201) =$

| |
|---|
| 1 |
|---|

 (202)

Fraction of total heating from main system 1 (204) = $(202) \times [1 - (203)] =$

| |
|---|
| 1 |
|---|

 (204)

Efficiency of main space heating system 1

| |
|--------|
| 399.94 |
|--------|

 (206)

Efficiency of secondary/supplementary heating system, %

| |
|----|
| 65 |
|----|

 (208)

| Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec | kWh/year |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----------|
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----------|

Space heating requirement (calculated above)

| | | | | | | | | | | | |
|---------|---------|---------|--------|-------|---|---|---|---|--------|---------|---------|
| 1779.05 | 1425.59 | 1230.01 | 725.64 | 318.8 | 0 | 0 | 0 | 0 | 698.96 | 1273.24 | 1804.79 |
|---------|---------|---------|--------|-------|---|---|---|---|--------|---------|---------|

(211)m = $\{[(98)m \times (204)]\} \times 100 \div (206)$ (211)

| | | | | | | | | | | | |
|--------|--------|--------|--------|-------|---|---|---|---|--------|--------|--------|
| 444.83 | 356.45 | 307.55 | 181.44 | 79.71 | 0 | 0 | 0 | 0 | 174.77 | 318.36 | 451.27 |
|--------|--------|--------|--------|-------|---|---|---|---|--------|--------|--------|

Total (kWh/year) = $\text{Sum}(211)_{1...5,10...12} =$

| |
|---------|
| 2314.37 |
|---------|

 (211)

Space heating fuel (secondary), kWh/month

= $\{[(98)m \times (201)]\} \times 100 \div (208)$

| | | | | | | | | | | | | | |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|-------|
| (215)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | (215) |
|---------|---|---|---|---|---|---|---|---|---|---|---|---|-------|

Total (kWh/year) = $\text{Sum}(215)_{1...5,10...12} =$

| |
|---|
| 0 |
|---|

 (215)

SAP WorkSheet: New dwelling design stage

Water heating

Output from water heater (calculated above)

| | | | | | | | | | | | |
|--------|--------|--------|-------|--------|---|---|---|---|--------|--------|--------|
| 222.59 | 196.11 | 205.77 | 184.2 | 180.32 | 0 | 0 | 0 | 0 | 191.01 | 202.31 | 217.15 |
|--------|--------|--------|-------|--------|---|---|---|---|--------|--------|--------|

Efficiency of water heater

100 (216)

(217)m= 100 100 100 100 100 100 100 100 100 100 100 100 (217)

Fuel for water heating, kWh/month

(219)m = (64)m x 100 ÷ (217)m

(219)m=

| | | | | | | | | | | | |
|--------|--------|--------|-------|--------|---|---|---|---|--------|--------|--------|
| 222.59 | 196.11 | 205.77 | 184.2 | 180.32 | 0 | 0 | 0 | 0 | 191.01 | 202.31 | 217.15 |
|--------|--------|--------|-------|--------|---|---|---|---|--------|--------|--------|

Total = Sum(219a)_{1..12} =

1599.46 (219)

Water heating requirement (immersion)

| | | | | | | | | | | | |
|---|---|---|---|---|--------|--------|--------|--------|---|---|---|
| 0 | 0 | 0 | 0 | 0 | 138.33 | 130.95 | 146.32 | 146.88 | 0 | 0 | 0 |
|---|---|---|---|---|--------|--------|--------|--------|---|---|---|

Efficiency of water heater (Immersion)

100 (216)

(217)m= 0 0 0 0 0 100 100 100 100 0 0 0 (217)

Fuel for water heating (Immersion), kWh/month

(219)m = [(64)m + (218) m] x 100 ÷ (217)m

(219)m=

| | | | | | | | | | | | |
|---|---|---|---|---|--------|--------|--------|--------|---|---|---|
| 0 | 0 | 0 | 0 | 0 | 138.33 | 130.95 | 146.32 | 146.88 | 0 | 0 | 0 |
|---|---|---|---|---|--------|--------|--------|--------|---|---|---|

Total = Sum(219a)_{1..12} =

562.48 (219)

Annual totals

kWh/year

kWh/year

Space heating fuel used, main system 1

2314.37

Water heating fuel used

1599.46

Water heating fuel used (Immersion)

562.48

Electricity for pumps, fans and electric keep-hot

Total electricity for the above, kWh/year

sum of (230a)...(230g) =

0 (231)

Electricity for lighting

655.18 (232)

10a. Fuel costs - individual heating systems:

| | Fuel kWh/year | Fuel Price (Table 12) | Fuel Cost £/year |
|-------------------------------------------------------------------------------------------------------------------------|---------------------------------|--------------------------|---------------------|
| Space heating - main system 1 | (211) x | 13.19 x 0.01 = | 305.27 (240) |
| Space heating - main system 2 | (213) x | 0 x 0.01 = | 0 (241) |
| Space heating - secondary | (215) x | 4.23 x 0.01 = | 0 (242) |
| Water heating cost (other fuel) | (219) | 13.19 x 0.01 = | 210.97 (247) |
| Water heating cost (Immersion) | (219) | 0 x 0.01 = | 74.19 (247) |
| Pumps, fans and electric keep-hot | (231) | 13.19 x 0.01 = | 0 (249) |
| (if off-peak tariff, list each of (230a) to (230g) separately as applicable and apply fuel price according to Table 12a | | | |
| Energy for lighting | (232) | 13.19 x 0.01 = | 86.42 (250) |
| Additional standing charges (Table 12) | | | 0 (251) |
| Appendix Q items: repeat lines (253) and (254) as needed | | | |
| Total energy cost | (245)...(247) + (250)...(254) = | | 676.84 (255) |

11a. SAP rating - individual heating systems

Energy cost deflator (Table 12) 0.42 (256)

SAP WorkSheet: New dwelling design stage

| | | | |
|--------------------------------|--------------------------------------------|-------|-------|
| Energy cost factor (ECF) | $[(255) \times (256)] \div [(4) + 45.0] =$ | 1.12 | (257) |
| SAP rating (Section 12) | | 84.39 | (258) |

12a. CO2 emissions – Individual heating systems including micro-CHP

| | Energy kWh/year | | Emission factor kg CO2/kWh | | Emissions kg CO2/year |
|---------------------------------------------------|---------------------------------|--|-------------------------------|---|--------------------------|
| Space heating (main system 1) | (211) x | | 0.519 | = | 1201.16 (261) |
| Space heating (secondary) | (215) x | | 0.019 | = | 0 (263) |
| Water heating | (219) x | | 0.519 | = | 830.12 (264) |
| Water heating (Immersion) | (219) x | | 0.519 | = | 291.93 (264) |
| Space and water heating | (261) + (262) + (263) + (264) = | | | | 2323.21 (265) |
| Electricity for pumps, fans and electric keep-hot | (231) x | | 0.519 | = | 0 (267) |
| Electricity for lighting | (232) x | | 0.519 | = | 340.04 (268) |
| Total CO2, kg/year | | | sum of (265)...(271) = | | 2663.25 (272) |
| CO2 emissions per m² | | | (272) ÷ (4) = | | 12.74 (273) |
| El rating (section 14) | | | | | 86 (274) |

13a. Primary Energy

| | Energy kWh/year | | Primary factor | | P. Energy kWh/year |
|---------------------------------------------------|---------------------------------|--|------------------------|---|-----------------------|
| Space heating (main system 1) | (211) x | | 3.07 | = | 7105.13 (261) |
| Space heating (secondary) | (215) x | | 1.04 | = | 0 (263) |
| Energy for water heating | (219) x | | 3.07 | = | 4910.34 (264) |
| Energy for water heating (Immersion) | (219) x | | 3.07 | = | 1726.82 (264) |
| Space and water heating | (261) + (262) + (263) + (264) = | | | | 13742.28 (265) |
| Electricity for pumps, fans and electric keep-hot | (231) x | | 3.07 | = | 0 (267) |
| Electricity for lighting | (232) x | | 0 | = | 2011.42 (268) |
| Total Primary Energy | | | sum of (265)...(271) = | | 15753.69 (272) |
| Primary energy kWh/m²/year | | | (272) ÷ (4) = | | 75.38 (273) |