



LEGEND

	Phasing Boundary		Permeable block paving Aquaset Ecogranite In 'Combit' by Formpave in BS75332. Variable loading. 80mm thick mix of sizes: 150x100x150/250. Build ups to engineers specification.		Blimbrous meadow. Build ups to engineers specification.		External watering valve pit
	Acc multi-drain MD sliding channel 100mm. Black slot grating. Refer to engineers specification.		Permeable block paving Aquaflo Ecogranite 'Combit' by Formpave in BS75332. Variable loading. 200x100x80mm. Aquaflo 'Balmoral' blocks (dark grey) used to delineate parking bays. Build ups to engineers specification.		Textured concrete flag paving. 600x900x60mm to BS75332. Build ups to engineers specification.		Bollards (1.2m spacing). Removeable.
	Block paving (impermeable) Ecogranite combined block paving by Formpave in 'Combit' to BS75332. 80mm thick mix of sizes: 150x100x150/250mm.		Permeable block paving Aquaflo Ecogranite 'Balmoral' (dark grey) by Formpave in BS75332. Variable loading. 200x100x80mm. Light loading. 80mm thick mix of sizes: 150x100x150/250. Build ups to engineers specification.		Hard-binding gravel. Brewood. Build ups to engineers specification.		Lighting column, pole mounted luminaire. 6m height CHS posts RAL 9007 with driver halophosphate luminaire (or similar). Refer to M&E's specification.
	Block paving (impermeable) Formpave Ecogranite In 'Combit' by Formpave in BS75332. Variable loading. 100x200x80mm. Formpave 'Balmoral' blocks (dark grey) used to delineate parking bays. Build ups to engineers specification.		Permeable block paving Aquaset Ecogranite In 'Combit' by Formpave in BS75332. Light loading. 80mm thick mix of sizes: 150x100x150/250. Build ups to engineers specification.		2m High black galvanised steel weldmesh fence		Recessed or spike mount uplight. Refer to M&E's specification.
	Block paving (impermeable) Formpave Ecogranite longsets by Formpave in 'Combit' to BS75332. 80mm thick mix of sizes: 100x250/300/350mm. Build ups to engineers specification.		Permeable block paving Aquaflo Ecogranite 'Combit' by Formpave in BS75332. Light loading. 200x100x80mm. Aquaflo 'Balmoral' blocks (dark grey) used to delineate parking bays. Build ups to engineers specification.		Shelflife cycle stands. 800 x 715mm. 305 grade stainless steel on concrete pad foundations. Refer to LUC drawing 6377-LD-DET-606.		

1 Detail 1
Scale 1:25@A1

BP2 100x200x80mm Laid in herringbone pattern

2 Detail 2
Scale 1:25@A1

BP3 Long sets 100 x 250/300/350mm x 80mm Laid in combined stretcher course pattern

3 Detail 3
Scale 1:25@A1

BA2 100x200x80mm Laid in herringbone pattern

		43 Chalton Street London, NW1 1JD T: 020 7383 5784 F: 020 7383 4798 london@landuse.co.uk www.landuse.co.uk
Project Richmond Upon Thames College		
Client Atkins		
Title College, Parking & Plaza Hardworks Plan		
Scale 1:250@A1	Status for Planning	
Job No. 6377	Drawing No. 201	Issue A

Do not scale from this drawing
© Drawing & Design Copyright of LUC