



COUNTERWEIGHTS TO SUIT  
CUSTOMER REQUIREMENTS:  
I.E. LIGHT(S), SKIRT,  
STOP SIGNS, POGO.

05/2016/113

RECEIVED  
23 JUN 2006  
PLANNING

**NOTES:**

1. ELECTRO-MECHANICAL BARRIER EB450  
2. WINDING MOTOR 0.375KW 230V 50HZ  
3. ELECT DRIVE VIA GEARBOX, CONTROL  
4. VOLTAGE 24V DC. WINDING HANDLE  
5. AVAILABILITY IN THE EVENT OF A POWER  
6. FAILURE. HINGED TOP LID (OPTIONALLY  
7. REMOVABLE). LOCKABLE SIDE COVER.  
8. 112x160 CHEMICAL ANCHORS.

9. BOOM-RECTANGULAR SHAPED ALUM.  
10. 38mm, POWDER COATED WHITE,  
11. WITH REFLECTIVE STRIPES 60x350mm AT  
12. 125mm CENTRES WITH REINFORCEMENT  
13. AT FIXING POINT.

3. ALL DUCTING TO BE 50ø MIN. UNLESS  
OTHERWISE SPECIFIED.

**CABLE DETAILS**

X DENOTES MAINS SUPPLY  
230V 1PH 6AMP. 3x2.5mm<sup>2</sup>

Y DENOTES CONTROL CABLE  
PUSH BUTTONS 6x1.5mm<sup>2</sup>  
SUBJECT TO SITE CONDITIONS.



Avon Barrier Company Ltd.  
Nova House  
195 South Liberty Lane  
Ashton Vale Trading Estate  
Bristol BS3 2UJ  
Tel: (44) (0117) 953 5252  
Fax: (44) (0117) 953 5373  
E-mail: TECHNICAL@AVON-BARRIER.CO.UK

**Drawing Title**

AVON EB 450 PARKING BARRIER,  
FOUNDATION DETAIL  
(NO C/W NO END STEADY)  
GENERAL ARRANGEMENT.

ISSUE	REVISION	SIG.	DATE
A	MOD TO 50/5/010		15/11/05

1st ANGLE PROJECTION		Tolerances	Used on	Drawn	Traced	Checked	Approved	Date	S.
COMPUTER GENERATED DO NOT ALTER BY HAND		Material	Finish	M.J.	.	.	.	11/05	N
		Scale		Drawing No.		Sht.	of	Rev.	
		1:200		EB450-6-01		1	1	/	