




<u>Thames Water Utilities Ltd</u>, Property Searches, PO Box 3189, Slough SL1 4W, DX 151280 Slough 13 T 0845 070 9148 E <u>searches@thameswater.co.uk</u> I <u>www.thameswater-propertysearches.co.uk</u>



<u>Thames Water Utilities Ltd</u>, Property Searches, PO Box 3189, Slough SL1 4W, DX 151280 Slough 13 T 0845 070 9148 E searches@thameswater.co.uk I www.thameswater-propertysearches.co.uk



<u>Thames Water Utilities Ltd</u>, Property Searches, PO Box 3189, Slough SL1 4W, DX 151280 Slough 13 T 0845 070 9148 E searches@thameswater.co.uk I www.thameswater-propertysearches.co.uk



#### Water Pipes (Operated & Maintained by Thames Water)

**Distribution Main:** The most common pipe shown on water maps. With few exceptions, domestic connections are only made to distribution mains. Trunk Main: A main carrying water from a source of supply to a treatment plant or reservoir, or from one treatment plant or reservoir to another. Also a main transferring water in bulk to smaller water mains used for supplying individual customers. Supply Main: A supply main indicates that the water main is used as a supply for a single property or group of properties. Fire Main: Where a pipe is used as a fire supply, the word FIRE will 3" FIRE be displayed along the pipe. Metered Pipe: A metered main indicates that the pipe in question 3" METERED supplies water for a single property or group of properties and that quantity of water passing through the pipe is metered even though there may be no meter symbol shown. Transmission Tunnel: A very large diameter water pipe. Most

tunnels are buried very deep underground. These pipes are not expected to affect the structural integrity of buildings shown on the map provided.

**Proposed Main:** A main that is still in the planning stages or in the process of being laid. More details of the proposed main and its reference number are generally included near the main.

#### **Valves**

General PurposeValve

Air Valve

Pressure ControlValve

Customer Valve

#### **Hydrants**

Single Hydrant

#### Meters

Meter

#### **End Items**

Symbol indicating what happens at the end of <sup>L</sup> a water main.

Blank Flange

Capped End
Emptying Pit

O Undefined End

Customer Supply

Manifold

Fire Supply

#### DEPTH BELOW GROUND

Up to 300mm (12")	900mm (3')
300mm - 600mm (12" - 24")	1100mm (3' 8")
600mm and bigger (24" plus)	1200mm (4')

PIPE DIAMETER

#### **Operational Sites**

Booster Station
Other
Other (Proposed)
Pumping Station
Service Reservoir
Shaft Inspection
Treatment Works
Unknown
Water Tower

#### **Other Symbols**

Data Logger


#### Other Water Pipes (Not Operated or Maintained by Thames Water)

Other Water Company Main: Occasionally other water company water pipes may overlap the border of our clean water coverage area. These mains are denoted in purple and in most cases have the owner of the pipe displayed along them.

**Private Main:** Indiates that the water main in question is not owned by Thames Water. These mains normally have text associated with them indicating the diameter and owner of the pipe.



## C. Onsite Drainage Records





D. London Borough Richmond upon Thames (LBRuT) Correspondence

#### O'Donovan, Donal

From: Brian Humphris <bri>drian.humphris@richmond.gov.uk>

 Sent:
 03 March 2016 15:32

 To:
 O'Donovan, Donal

**Subject:** RE: WIE10667 160122 DOBH Stag Brewery Flood Risk Enquiry

**Attachments:** Gully reports.xlsx

#### Donal

In response to your questions below:-

- Not sure who would be the best contact but they have area teams, so any enquiry relating to Stag site would be referred to them.
- I can find no record of a name either. OS plan indicates that the culvert is fed by open ditches along both sides of Sheen Common, but nothing is indicated south of the common, within Richmond Park.
- 3 Please see attached reports as logged on our system.

#### Regards Brian

#### Brian Humphris Highway Asset Co-ordinator

#### 020 8891 7738

**From:** O'Donovan, Donal [mailto:donal.odonovan@watermangroup.com]

Sent: 03 March 2016 12:03

To: Brian Humphris

Subject: RE: WIE10667 160122 DOBH Stag Brewery Flood Risk Enquiry

Hi Brian.

Many thanks for the response, I have a few follow up queries that I hope you will be able to answer.

- 1. You mentioned that we would need to confirmed if the Site had passed the Sequential Test with the Planners. Do you have the contact details for the best person/team to contact in relation to this.
- 2. You provided plan showing a culverted watercourse that has an outlet adjacent to the Site. Do you know what this watercourse is called? I have had a look online but not had any luck.
- 3. You mentioned that there have been some records of flooding due to blocked gullies. Can you provide any further information in relation to these (ie. extent, date, location etc.).

If you have any queries please feel free to give me a call.

Cheers,

#### Donal

From: Brian Humphris [mailto:brian.humphris@richmond.gov.uk]

Sent: 24 February 2016 16:23

**To:** O'Donovan, Donal <<u>donal.odonovan@watermangroup.com</u>> **Subject:** RE: WIE10667 160122 DOBH Stag Brewery Flood Risk Enquiry

#### Hi Donal

Please accept my apologies for the delay in responding to your enquiry. Unfortunately some of the information that you requested has taken some time to obtain. Please see comments below.

#### Regards Brian

## Brian Humphris Highway Asset Co-ordinator

#### 020 8891 7738

From: O'Donovan, Donal [mailto:donal.odonovan@watermangroup.com]

Sent: 22 January 2016 14:34

To: Brian Humphris

Subject: WIE10667 160122 DOBH Stag Brewery Flood Risk Enquiry

Hi Brian,

Thanks for speaking to me earlier.

#### Stag Brewery - Flood Risk Enquiry

I'm writing regarding the proposed redevelopment of Stag Brewery, located within the London Borough of Richmond upon Thames. The Site is approximately 9ha in size, and is located at approximate postcode SW14 7ET, please find attached a location plan for your information. The proposals comprise construction of a residential led mixed use development.

We have been commissioned to investigate the risk of flooding to the proposed development. I would be grateful if you could provide information relating to the following:

- The Environment Agency mapping shows that the Site lies within Flood Zones 2 and 3, and is generally shown as being defended The River Thames defences are identified as being continuous in this location, please could you confirm that the Site is fully defended from tidal and fluvial flooding.
   We do not have detailed records of River Defences. However photographs on pages 24 & 25 of the SPD show that there are no defences at Ship Lane. Street View images from the river appear to show river levels approx. 1m below the towpath level, although there is no way of knowing what the Tide Status was at that time. There are defences at Bulls Alley, as indicated on Page 13 of the SPD.
- 2. The Stag Brewery SPD sets out the planning brief for potential development at the Site. Please could you confirm that the Sequential Test has been passed.

  This would need to be confirmed by our Planners.
- 3. As it is very early in the decision process it is currently unknown where development would be located. However, the design would ensure that appropriate mitigation steps would be incorporated. In line with other Sites within London we currently assume that commercial and retail ('less vulnerable') uses would be acceptable on the ground floor. We also assume that duplex residential uses would be acceptable on the ground and first floor (bedrooms location on the first floor), as a means of egress would be available to ensure safety. Please could you confirm this. We will further consul once the scheme plans have evolved. This approach is reasonable but Planners would make final approval. At other developments within Flood Zones floor levels are usually raised to at least 300mm above ground level to reduce flood risk.
- 4. Could you please provide a map showing the location of any Ordinary Watercourses near the Site, and note any development restrictions that would therefore apply.

Please note plans attached. Watercourses plan shows a watercourse under the site, although the alignment is probably only indicative. OS plan is marked with the known extents of relevant section – 'outlet' is marked on the plan.

- 5. Please could you confirm whether or not there are any 'lost rivers' in the vicinity of the Site. Please could you provide any information you have relating to this, to include a map.

  See above
- 6. Please could you provide your Risk of Flooding from Surface Water map in the vicinity of the Site, as the EA's online version is difficult to interpret due to the scale.

  Richmond does not have its own Flood risk maps, we use the EA plans.
- 7. Please provide us with details of any historic tidal, fluvial, groundwater, surface water or sewer flooding affecting or in the vicinity of the Site. Alternatively, please confirm that you have no records of flooding in the vicinity.
  - Our Highways Enquiry System has no record of any flooding reports at Mortlake High Street, Lower Richmond Road, Ship Lane or Williams Lane, other than blocked gully reports.
- 8. Please could you confirm the likely groundwater levels in the vicinity of the Site. Unfortunately we do not have records of likely Groundwater Levels.
- 9. It is still very early in the design process and at this stage the drainage strategy is still being developed. We are currently looking at all options available to drain surface water runoff from the Site. Our approach will follow the drainage hierarchy where possible, with the preference of draining the site to the River Thames (unrestricted due to the tidal nature of the River). Should it not be possible to drain to the River Thames due to Site constraints, we would connect to the public sewer network. Following the requirements of the London Plan, we would limit surface water runoff from the Site to 50% of the existing rate, for the 1 in 100 year event, including for the predicted increase in rainfall intensity over the lifetime of the development due to climate change. Please could you confirm that this approach is acceptable.

  This approach is acceptable.

We are also writing to the Environment Agency and Thames Water requesting details of recorded flooding incidents and relevant information. If you are aware of any other parties that may have useful information please let me know.

This information is required as soon as possible and we would be grateful if you could provide your written response by 5<sup>th</sup> February 2016. If this is unlikely to be achievable or you require any further information please feel free to get in contact.

Please feel free to give me a call if you wish to discuss the above.

Cheers,

Donal

C. Donal O'Donovan Engineer Waterman Infrastructure & Environment Ltd

Pickfords Wharf | Clink Street | London SE1 9DG t +44 207 928 7888 | d +44 3300 602 316 www.watermangroup.com | LinkedIn | Twitter

🍂 Please consider the environment before printing this e-mail. Thank you!

This message contains confidential information and is intended only for the individual named. If you are not the named addressee you should not disseminate, distribute or copy this email. Please notify the sender immediately if you have received this email by mistake and delete it from your system. Email transmission cannot be guaranteed to be secure or error-free as information could be intercepted, corrupted, delayed, lost, destroyed, incomplete, or contain viruses. The sender does not accept liability for any errors or omissions in the contents of this message, which arise as a result of email transmission. All reasonable precautions have been taken to see that no viruses are present in this email. Waterman Group cannot accept liability for loss, disruption or damage however caused, arising from the use of this email or attachments and recommend that you subject these to virus checking procedures prior to use. Email messages may be monitored and by replying to this message the recipient gives their consent to such monitoring.

Waterman Group Plc., Pickfords Wharf, Clink Street, London SE1 9DG, is a company registered in England and Wales with company registration number 2188844.

If you have received this message in error you must not print, copy, use or disclose the contents, but must delete it from your system and inform the sender of the error. You should be aware that all emails received and sent by the London Borough of Richmond upon Thames may be stored or monitored, or disclosed to authorised third parties, in accordance with relevant legislation.

If you have received this message in error you must not print, copy, use or disclose the contents, but must delete it from your system and inform the sender of the error. You should be aware that all emails received and sent by the London Borough of Richmond upon Thames may be stored or monitored, or disclosed to authorised third parties, in accordance with relevant legislation.



E. Port of London Authority (PLA) Tide Table

# CHART DATUMS & STANDARD LEVELS IN THE PORT OF LONDON

- Chart Datum is set to approximately the level of Lowest Astronomical Tide (L.A.T.)
- 2. Low Water levels in the upper reaches of the tidal Thames are greatly affected by the land water flow at Teddington Weir. They frequently fall below chart datum when this flow is significantly reduced, typically during the summer months.
- Maintained level and chart datum above Richmond half tide weir are both 1.72 metres above Ordnance Datum (Newlyn).
- 4. Trinity High Water (T.H.W.) is deemed, by the Port of London Act, 1968, to be a level having a value of 11.4 feet (i.e. 3.475 metres) above Ordnance Datum (Newlyn).

Tidal Station	Level of Chart Datum below	St	andard l	andard levels above local C.D.						
ridai Station	Ordnance Datum (Newlyn) m	Mean Low Water Springs MLWS	Mean Low Water Neaps MLWN	Mean High Water Neaps MHWN	Mean High Water Springs MHWS	Highest Astronomical Tide (HAT)				
WALTON	2.16	0.5	1.1	3.5	4.3	4.7				
MARGATE	2.50	0.6	1.3	4.0	4.8	5.1				
SHIVERING SAND	_	0.6	1.4	4.4	5.4	5.7				
SOUTHEND	2.90	0.6	1.4	4.8	5.9	6.3				
CANVEY	2.97	0.6	1.4	5.0	6.1	6.6				
CORYTON	3.05	0.6	1.5	5.1	6.2	6.7				
TILBURY	3.12	0.6	1.5	5.4	6.6	7.0				
GREENHITHE	3.20	0.6	1.6	5.6	6.7	7.2				
DAGENHAM	3.28	0.6	1.6	5.8	7.0	7.5				
NORTH WOOLWICH	3.35	0.6	1.6	5.9	7.2	7.7				
TOWER	3.20	0.5	1.5	5.9	7.1	7.6				
BLACKFRIARS	3.05	0.5	1.4	5.8	7.0	7.5				
WESTMINSTER	2.90	0.5	1.3	5.7	6.9	7.4				
VAUXHALL	2.59	0.3	1.0	5.4	6.6	7.1				
VICTORIA RAIL	2.44	0.3	0.9	5.3	6.5	6.9				
ALBERT BRIDGE	2.29	0.3	0.9	5.1	6.3	6.8				
WANDSWORTH	2.13	0.3	0.9	5.0	6.2	6.7				
PUTNEY	1.98	0.3	0.8	4.9	6.1	6.6				
HAMMERSMITH	1.68	0.3	0.7	4.7	5.8	6.4				
BARNES	1.37	0.2	0.6	4.4	5.5	6.1				
CHISWICK	1.22	0.2	0.5	4.3	5.3	6.0				
KEW	1.07	0.2	0.5	4.2	5.2	5.9				
BRENTFORD	0.91	0.1	0.4	4.0	5.0	5.7				
RICHMOND	0.61	0.1	0.2	3.8	4.8	5.5				
TWICKENHAM	Note 3	_		1.5	2.5	3.2				



## F. Tide Locking Calculations



Company: WIE Office: London

 Sheet No:
 1 of 1
 Project No:
 WIE10667

 By
 N Balboni
 Date
 27.09.2017

Checked: D O'Donovan Date 27.09.2017

Project Title: Former Stag Brewery, Mortlake
Calculations Title: Tide Locking Calculation

									CA	LCU	LAT	ONS												
Т	The 'rule	of t	welf	ths	' is a	a rul	le of	thuml	that	allov	vs th	e tide	leve	el to	be e	estir	nated	base	d on	the h	nigh	and	low v	vate
	evels. T						xiar	ntion a	ssum	ing s	six ho	urs t	etwe	en l	nigh	and	d low	water	, and	d doe	s no	t tak	e acc	ou
C	of geogr	aphi <sup>,</sup>	cal l	loca	atior	١.																		
	Sou	rce: I	Port	of	Lon	don	Au	thority,	2017	7. Tia	le Ta	bles	and I	Port	Info	rma	ation							
								es and																
		nes N						4.13																
		swick			•			4.08	+ +															1
	0	, more			· (	.,	,	1.00																
	Inpu	ıtc													Diil	0.01	f Twe	lfthc						+
	шрс	112	-	$\dashv$											Kui	<del>e</del> 0	iwe	111115						+
	N4	11:	ula V	A/-+	C	·!				F '	22	AOE				الما	_	Cha		10/	otor	1 01/4	.I	+
		ın Hiç						=								Hou	ſ	Cha	ige	VV		Leve	el .	
	Mea	ın Lo	w V	ate	er S	prin	g	=		-1.(	J∠ M	AOE				0		-	40		-1.0			4
																1			12		-0.5		$\perp$	4
	Inve	rt Le	vel	of C	Outf	all		=		2.6	i0 m	AOE				2		1/			0.5			_
			_													3		1/			2.1			4
																4		1/			3.6			
																5		1/			4.7			
																6		1/	12		5.2	23		
																7		1/	12		4.7	<b>'</b> 1		
																8		1/	6		3.6	67		
																9		1/	4		2.1	1		
																10		1/	4		0.5	54		
																11		1/	6		-0.5	50		
	Out	put														12		1/	12		-1.0	02		
		6 - 5 -												_										
	1004	3 -							/															
	Water Level (m AOD)	2 -																						
	Wate	0 -				/																		
		-1	0		1		2	3		4			6		7		8	9		10		11_	12	
		-2										Tim	e (Ho	urs)										
	Time	e tha	t ou	ıtfal	l he	com	es s	subme	raed i	(hrs)		=				3.3								
								unsubr	-			=	1			8.6							-	+
	l Im				·		, U U U	สถางนมโ	110190	,u (III	· • /	_	1			U.U			1	1 1		1		
								ubme	_	•	•	=				5.3								



## **G. WINDES Microdrainage Network Calculations**

Waterman Infrastructure & Enviro	nment	Page 1
Pickfords Wharf		
Clink Street		4
London SE1 9DG		Micco
Date 29/09/2017 11:44	Designed by CSNB2	Desipago
File 170926 CULVERT CHECK.MDX	Checked by	Drainage
Micro Drainage	Network 2017.1.2	

#### STORM SEWER DESIGN by the Modified Rational Method

#### Design Criteria for Storm

Pipe Sizes STANDARD Manhole Sizes STANDARD

FEH Rainfall Model Return Period (years) 100 FEH Rainfall Version 1999 Site Location GB 520450 176000 TQ 20450 76000 C (1km) -0.024 D1 (1km) 0.322 D2 (1km) 0.262 D3 (1km) 0.219 E (1km) 0.306 F (1km) 2.539 Maximum Rainfall (mm/hr) 0 Maximum Time of Concentration (mins) 5 0.000 Foul Sewage (1/s/ha) Volumetric Runoff Coeff. 0.750 PIMP (%) 100 Add Flow / Climate Change (%) 40 Minimum Backdrop Height (m) 0.200 Maximum Backdrop Height (m) 1.500 Min Design Depth for Optimisation (m) 1.200 Min Vel for Auto Design only (m/s) 1.00

500

Designed with Level Soffits

Min Slope for Optimisation (1:X)

#### Network Design Table for Storm

۱	EM	neng cn	rall	эторе	I.AIEa	1.6.	ь	156	ν.	птр	DIM	section Type	Auto
		(m)	(m)	(1:X)	(ha)	(mins)	Flow	(1/s)	(mm)	SECT	(mm)		Design
	1.000	124.000	0.012	10333.3	0.300	5.00		0.0	0.600	[]	-1	Pipe/Conduit	a
	1.001	2.949	0.590	5.0	0.000	0.00		0.0	0.600	0	675	Pipe/Conduit	Ā
	1.002	7.594	0.051	150.0	0.000	0.00		0.0	0.600	0	675	Pipe/Conduit	Ã
	1.003	25.890	1.295	20.0	0.000	0.00		0.0	0.600	0	675	Pipe/Conduit	•

#### Network Results Table

		•						-	
0.00	5.00	5.480	0.300	0.0	0.0	0.0	0.14	67.5	0.0
0.00	5.00	4.945	0.300	0.0	0.0	0.0	11.77	4211.0	0.0
0.00	5.00	4.355	0.300	0.0	0.0	0.0	2.14	765.0	0.0
0.00	5.00	4.305	0.300	0.0	0.0	0.0	5.88	2103.1	0.0
	(mm/hr) 0.00 0.00 0.00	(mm/hr) (mins)  0.00 5.00  0.00 5.00  0.00 5.00	(mm/hr)(mins)(m)0.005.005.4800.005.004.9450.005.004.355	(mm/hr)         (mins)         (m)         (ha)           0.00         5.00         5.480         0.300           0.00         5.00         4.945         0.300           0.00         5.00         4.355         0.300	(mm/hr)         (mins)         (m)         (ha)         Flow         (1/s)           0.00         5.00         5.480         0.300         0.0           0.00         5.00         4.945         0.300         0.0           0.00         5.00         4.355         0.300         0.0	(mm/hr)         (mins)         (m)         (ha)         Flow         (1/s)         (1/s)           0.00         5.00         5.480         0.300         0.0         0.0           0.00         5.00         4.945         0.300         0.0         0.0           0.00         5.00         4.355         0.300         0.0         0.0	(mm/hr)         (mins)         (m)         (ha)         Flow         (1/s)         (1/s)         (1/s)           0.00         5.00         5.480         0.300         0.0         0.0         0.0           0.00         5.00         4.945         0.300         0.0         0.0         0.0           0.00         5.00         4.355         0.300         0.0         0.0         0.0	(mm/hr)         (mins)         (m)         (ha)         Flow         (1/s)         (1/s)         (1/s)         (m/s)           0.00         5.00         5.480         0.300         0.0         0.0         0.0         0.14           0.00         5.00         4.945         0.300         0.0         0.0         0.0         11.77           0.00         5.00         4.355         0.300         0.0         0.0         0.0         2.14	0.00 5.00 5.480 0.300 0.0 0.0 0.0 0.14 67.5 0.00 5.00 4.945 0.300 0.0 0.0 0.0 11.77 4211.0 0.00 5.00 4.355 0.300 0.0 0.0 0.0 2.14 765.0

Waterman Infrastructure & Enviro	nment	Page 2
Pickfords Wharf		
Clink Street		٩
London SE1 9DG		Micco
Date 29/09/2017 11:44	Designed by CSNB2	Desipago
File 170926 CULVERT CHECK.MDX	Checked by	Drainage
Micro Drainage	Network 2017.1.2	

#### PIPELINE SCHEDULES for Storm

#### <u>Upstream Manhole</u>

PN	Hyd	Diam	MH	C.Level	I.Level	D.Depth	MH	MH DIAM., L*W
	Sect	(mm)	Name	(m)	(m)	(m)	Connection	(mm)
1.000	[]	-1	1	6.030	5.480	0.400	Open Manhole	3000
1.001	0	675	2	6.030	4.945	0.410	Open Manhole	3000
1.002	0	675	3	6.030	4.355	1.000	Open Manhole	1500
1.003	0	675	3	6.030	4.305	1.050	Open Manhole	2100

#### <u>Downstream Manhole</u>

PN	Length	Slope	MH	C.Level	I.Level	D.Depth	MH	MH DIAM., L*W
	(m)	(1:X)	Name	(m)	(m)	(m)	Connection	(mm)
1.000	124.000	10333.3	2	6.030	5.468	0.412	Open Manhole	3000
1.001	2.949	5.0	3	6.030	4.355	1.000	Open Manhole	1500
1.002	7.594	150.0	3	6.030	4.305	1.050	Open Manhole	2100
1.003	25.890	20.0		4.500	3.010	0.815	Open Manhole	675

#### Surcharged Outfall Details for Storm

Outfall	Outfall	c.	Level	I.	Level		Min	D,L	W
Pipe Number	Name		(m)		(m)	I.	Level	(mm)	(mm)
							(m)		

1.003 4.500 3.010 2.625 675 0

Datum (m) 0.000 Offset (mins) 0

Time	Depth										
(mins)	(m)										
30	5.230	90	5.230	150	5.230	210	5.230	270	5.230	330	5.230
60	5.230	120	5.230	180	5.230	240	5.230	300	5.230	360	5.230

#### Simulation Criteria for Storm

Volumetric Runoff Coeff 0.750 Additional Flow - % of Total Flow 0.000
Areal Reduction Factor 1.000 MADD Factor \* 10m³/ha Storage 2.000
Hot Start (mins) 0 Inlet Coefficient 0.800
Hot Start Level (mm) 0 Flow per Person per Day (1/per/day) 0.000
Manhole Headloss Coeff (Global) 0.500 Run Time (mins) 60
Foul Sewage per hectare (1/s) 0.000 Output Interval (mins) 1

Number of Input Hydrographs 0 Number of Storage Structures 0 Number of Online Controls 0 Number of Time/Area Diagrams 0 Number of Offline Controls 0 Number of Real Time Controls 0

#### Synthetic Rainfall Details

©1982-2017 XP Solutions

Waterman Infrastructure & Enviro	onment	Page 3
Pickfords Wharf		
Clink Street		ا ا
London SE1 9DG		Micco
Date 29/09/2017 11:44	Designed by CSNB2	Desinado
File 170926 CULVERT CHECK.MDX	Checked by	Drainage
Micro Drainage	Network 2017.1.2	

#### Synthetic Rainfall Details

Rainfall Model					FEH
Return Period (years)					100
FEH Rainfall Version					1999
Site Location	GB	520450	176000	TQ	20450 76000
C (1km)					-0.024
D1 (1km)					0.322
D2 (1km)					0.262
D3 (1km)					0.219
E (1km)					0.306
F (1km)					2.539
Summer Storms					Yes
Winter Storms					No
Cv (Summer)					0.750
Cv (Winter)					0.840
Storm Duration (mins)					30

Waterman Infrastructure & Enviro	onment	Page 4
Pickfords Wharf		
Clink Street		
London SE1 9DG		Micco
Date 29/09/2017 11:44	Designed by CSNB2	Desipago
File 170926 CULVERT CHECK.MDX	Checked by	Drainage
Micro Drainage	Network 2017.1.2	

#### Summary of Critical Results by Maximum Level (Rank 1) for Storm

#### Simulation Criteria

Areal Reduction Factor 1.000 Additional Flow - % of Total Flow 0.000 Hot Start (mins) 0 MADD Factor \*  $10m^3$ /ha Storage 2.000 Hot Start Level (mm) 0 Inlet Coefficient 0.800 Manhole Headloss Coeff (Global) 0.500 Flow per Person per Day (l/per/day) 0.000 Foul Sewage per hectare (l/s) 0.000

Number of Input Hydrographs 0 Number of Storage Structures 0 Number of Online Controls 0 Number of Time/Area Diagrams 0 Number of Offline Controls 0 Number of Real Time Controls 0

#### Synthetic Rainfall Details

Rainfall	Model						FEH
FEH Rainfall V	ersion						1999
Site Lo	cation	GB	520450	176000	TQ	20450	76000
C	(1km)					-	-0.024
D1	(1km)						0.322
D2	(1km)						0.262
D3	(1km)						0.219
F	(1km)						0.306
F	(1km)						2.539
Cv (5	Summer)						0.750
Cv (V	Minter)						0.840

Margin for Flood Risk Warning (mm) 300.0 DVD Status OFF
Analysis Timestep Fine Inertia Status OFF
DTS Status ON

Profile(s)						Sui	mmer a	and W:	inter
Duration(s) (mins)	15,	30,	60,	120,	180,	240,	360,	480,	600,
							720,	960,	1440
Return Period(s) (years)									100
Climate Change (%)									40

	US/MH			Climate	First (X)	, ,	First (Z)		Water	
PN	Name	Storm	Period	Change	Surcharge	Flood	Overflow	Act.	(m)	
1.000	1	15 Winter	100	+40%	100/15 Summer				5.824	
1.001	2	60 Summer	100	+40%					5.274	
1.002	3	60 Summer	100	+40%	100/30 Summer				5.267	
1.003	3	60 Summer	100	+40%	100/30 Summer				5.254	

		Surcharged	Flooded			Pipe		
	US/MH	Depth	Volume	Flow /	Overflow	Flow		Level
PN	Name	(m)	(m³)	Cap.	(1/s)	(1/s)	Status	Exceeded
1.000	1	0.194	0.000	1.29		285.9	FLOOD RISK	
1.001	2	-0.346	0.000	0.15		147.8	OK	
1.002	3	0.237	0.000	0.35		148.7	SURCHARGED	
			01000	010	~ 7 . '			

©1982-2017 XP Solutions

Waterman Infrastructure & Enviro	nment	Page 5
Pickfords Wharf		
Clink Street		
London SE1 9DG		Micco
Date 29/09/2017 11:44	Designed by CSNB2	Desipago
File 170926 CULVERT CHECK.MDX	Checked by	Drainage
Micro Drainage	Network 2017.1.2	

#### Summary of Critical Results by Maximum Level (Rank 1) for Storm

		Surcharged	Flooded			Pipe		
	US/MH	Depth	Volume	Flow /	Overflow	Flow		Level
PN	Name	(m)	(m³)	Cap.	(1/s)	(1/s)	Status	Exceeded
1.003	3	0.274	0.000	0.10		149.6	SURCHARGED	

©1982-2017 XP Solutions



### **H. Surface Water Calculations**



Company: WIE Office: London

Sheet No: 1 of 10 Project No: WIE10667

 By
 N Balboni
 Date
 13/02/2018

 Checked:
 D O'Donovan
 Date
 13/02/2018

Project Title Former Stag Brewery, Mortlake

Calculations Title Existing Discharge Rate - Modified Rational Method

LOCATION		_	_		_			_	_					ATIONS	_	_	_	_	_	_	_	_		_	C	)PTI	ONS
	Cal	cula	tio	ns ba	asec	d on:	Des	ign a	and	Ana	lysis	of u	ırba	n storm c	Irain	age	. Th	e W	allingfo	rd Pi	roce	dure	€,				
	Vol	ume	1	Prin	ciple	s m	ethod	ds a	nd p	ract	ice.																
	Use	er In	שו	ıt Da	ıta																						
	_			area															Ę	5.69	ha						
				om F		)														605							
	_		`				ı FEI	H)												.80							
				mpe	• •															100	%						
	Soi			ľ		Ť														0.40							-
	_	-		Run	off (\	vell	drain	ed s	sanc	lv. lo	amı	or e	earth	ny peat s	oils)					).15							
	_						neabl			-				•	,					0.30							
	_			•			nds,			_	_			•						).40							
	_			•	•		loan						,	,						).45							
	_					•	s of t	-			nds)									).50							
						Τ					,																
Fig. 9.7	UC	WI (	Fr	om F	iaur	e 9.	7 of \	Vall	inaf	ord N	/ //eth	nod)								52							
· · · · · · · · · · · · · · · · · · ·					-3							,															
Eqn. 13	Qρ	(pe	ak	disch	nard	e) =	2.78	Cv	CR	iΑ																	
	Wh		_				Disch				i = 1	rainf	all ir	ntensity				A =	Total A	rea							_
									_					,													
From FEH	Ave	rag	e r	ainfa	ıll Int	tensi	ity (i)																				
		9	_	100_			(.)		1.80	mm	1																-
						<u> </u>					•																_
Eqn 7.20	Cv	= PI	L R/1	00																							-
Eqn 7.3	101				99 P	IMD,	1 + (2	5.0	SOI	1)+	(0 (	178 I	IC\V	VI) - 20.7													_
<u> </u>														pervious	١			100	%								
Page 52					•		o car							Porvious	,			40									_
age oz							of F						70					100									_
	1			Sc		_	.40			UC		5	2					. 55	,,,								
	1	PR	=			+					V V I.		_						76.26								
	Thi	s C		:															0.76								-+
Sec 7.10					ende	d fo	r sim	ulati	on s	and o	desi	an)							1.3								-+
200 7.10		γ. το			71140	J 101		aiati	J.1 6	u (		ອ'' <i>!</i>							1.3								+
	05	for	 1 i:	n 104	n ve	ar 60	) mir	) ) () † ^	q	ratio	n -				21	23	l/s	or	1/	12.8	I/e/k	าล					-
	ζþ	101	_ "	11 100	ye.	ai 00	11111	iute	uul	atio					J 1	2.5	1/3	01	1-	0	1/ 3/1	ıa					
	500	6 of	th	a evi	etina	run	off ra	ate-						405.0	l/e				71.3	1/e/k	12						-+
	307	0 01	1111	S GVI	oui ić	iui	011 16	a1 <del>0</del> –						+05.0	1/3				11.3	1/3/1	ıa					$\vdash$	-+
	-			+		-																					-+



WIE Company: 2 of 10 Sheet No: N Balboni

O O'Donovan

Ву

Checked:

WIE10667 Project No: Date 13/02/2018 13/02/2018 Date

London

Office:

LOCATION			CAL	CULATIONS					OPTI	ONS
	In order to calculate the volume of s Control module, Quick Storage Esti					016.1,	Source			
	50% of existing discharge rate:									
	405.0	I/s								
	71.3	l/s/ha							1	_
Summary	Attenuation volumes required by	Drainage C	Catchment							
	Catchment	Area (ha)		Required attenuation (m3)						
	East - 1	0.30	21.3	140						
	East - 2	0.25	17.8	117						
	East - 3	0.18	12.8	84						
	West - school	2.18	155.2	1017						
	West - 4	1.07	76.2	499						
	West - 5	0.54	38.5	252						
	West - 6	0.38	26.9	177						
	West - 7	0.79	56.3	369						
	Total	5.69	405.0	2655						



WIE Company: Office: London WIE10667 3 of 11 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018

Date

Checked:

In order to calculate the volume of surface water attenuation required for the Site, Windes Microdrainage version 2016.1, Source  Control module, Quick Storage Estimate has been used. The input and output data for which are shown below;  Drainage Catchment - East 1  Area 0.30 ha  50% of existing discharge rate 71.3   //s/ha  Maximum allowable discharge 21.39   //s  Quick Storage Estimate    Quick Storage Estimate	OPTIC				
Area  50% of existing discharge rate  71.3   //s/ha  Maximum allowable discharge  21.39   //s  Maximum allowable discharge  21.39   //s  Quick Storage Estimate    Curck Storage Estimate   Curch Storage Estimate   Curch Storage Estimate   Curch Storage (Auch Storage					
Area 0.30 ha 50% of existing discharge rate 71.3 l/s/ha		+			
Maximum allowable discharge 21.39 I/s    Quick Storage Estimate   Quick Storage   Quic					
Quick Storage Estimate   Quick Storage   Quick Storag					
Variables					
Variables					
		- - - - -			
Enter Hastman Alovadore Uschafge between U u and 353530 U  Et et Maximum Alovadore Uschafge between U u and 3753530 U  Et et Maximum Alovadore Uschafge between U u and 3753530 U	Help	_			
		<b>-</b>			
		t			
Attenuation volume (m3) 140					



WIE Company: Office: London WIE10667 4 of 10 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018

Date

Checked:

LOCATION	CALCULATIONS	OPTION
	In order to calculate the volume of surface water attenuation required for the Site, Windontrol module, Quick Storage Estimate has been used. The input and output data for volume is a surface water attenuation required for the Site, Windontrol module, Quick Storage Estimate has been used. The input and output data for volume is a surface water attenuation required for the Site, Windontrol module, Quick Storage Estimate has been used. The input and output data for volume is a surface water attenuation required for the Site, Windontrol module, Quick Storage Estimate has been used.	
	Drainage Catchment - East 2	
	Area 0.25 ha	
	50% of existing discharge rate 71.3 l/s/ha	
	Maximum allowable discharge 17.83 l/s	
	// Quick Storage Estimate	torage Estimate
	Micro     FEH Rainfall	These values are estimates only and should not be used for design purposes.
	C (tkm)   0.024   0.3 (tkm)   0.219   whitration Coefficient (n/hv)   0.00000	w 2D
	Analyse OK Cancel Help	Analyse OK Cancel Help
	Enter Maximum Allowable Discharge between 0.0 and 999999.0	Enter Maximum Allowable Discharge between 0.0 and 999999.0
	Attenuation volume (m3) 117	
i .	/ Methadion volume (mo)	



WIE Company: Office: London WIE10667 5 of 10 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018

Date

Checked:

LOCATION	CALCULATIONS O	PTIONS
	In order to calculate the volume of surface water attenuation required for the Site, Windes Microdrainage version 2016.1, Source Control module, Quick Storage Estimate has been used. The input and output data for which are shown below;	
	Drainage Catchment - East 3	
	Area 0.18 ha	
	50% of existing discharge rate 71.3  /s/ha	
	Variables   FEH Rainfall	-  -  -  -  -
	Analyse OK Cancel Help  Enter Maximum Allowable Discharge between 0.0 and 999999.0  Enter Maximum Allowable Discharge between 0.0 and 999999.0	Help
	Attenuation volume (m3) 84	



WIE Company: Office: London 6 of 10 WIE10667 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018 Checked: Date

LOCATION				ALCULAT	 											OPT	IONS	;
	In order to calculate the volume of Control module, Quick Storage Est			•					_		2016.1	, Sour	ce					
	Drainage Catchment - School																	
	Area	2.18																
	50% of existing discharge rate		l/s/ha															
	Maximum allowable discharge	155.29	l/s													_	$\sqcup$	
	Variables   Version   199   Version   190   Version   190	Cv (Summer) Cv (Winter) Impermeable Area Maximum Allowable Infiltration Coefficie Safety Factor Climate Change (%	e Discharge (l/s) 155.2 0.000	0	Variable Result Design Overview Vt	es ts n v 2D	Results Global V of betwe	en 833 i	m³ and 12	oproximate : 00 m³. s only and :		be used fo	or design	ı purpos		0		-   -   -   -   -
	Enter Maximum Allowable D	Analyse ischarge between 0.0 ar	OK Cance	Help				Ente	r Maximum	Allowable Disc		Analyse een 0.0 and	OK 999999.0		Cancel	H	lelp	-
	Attenuation volume (m3)	1017														$\perp$		



WIE Company: Office: London WIE10667 7 of 10 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018 Checked: Date

LOCATION			CALCULATIO	NS										OPTI	ONS
	In order to calculate the volume of a Control module, Quick Storage Esti		•				•		016.1,	Sourc	e				
	Drainage Catchment - West 4													H	$\blacksquare$
	Area	1.07 ha													
	50% of existing discharge rate	71.3 l/s/ha													$\Box$
	Maximum allowable discharge	76.29 l/s													
	Variables   Variables   FEH Rainfall   Variables   Variables   FEH Rainfall   Variables   Variables	Cv (Summer) 0.76 Cv (Vinter) 0.84 Impermeable Area (ha) 100 Maximum Allowable Decharge (r/a) 76.0 Infiltration Coefficient (m/hr) 0.00 Safety Factor 2.0 Climate Change (%) 40	10 70 3 30000	Variable Results Design Overview Vt	Results Globa of bet These	l Variables ween 408	require approx m³ and 589 m³. e estimates onl			sed for de	sign purpa	oses.			
	†	Analyse OK Can	cel Help						Analyse		ок	Cance	el le	Help	
	Enter Maximum Allowable D	scharge between 0.0 and 999999.0			+	Ente	r Maximum Allowa	ible Discharge	between 0.0	U and 99999	19.0				
	Attenuation volume (m3)	499													



WIE Company: Office: London WIE10667 8 of 10 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018 Checked: Date

LOCATION			CALCULAT										OPT	IONS			
	In order to calculate the volume of Control module, Quick Storage Es								016.1, 8	Source							
	Drainage Catchment - West 5																
	Area	0.54 ha															
	50% of existing discharge rate	71.3 l/s/ha															
	Maximum allowable discharge	38.50 l/s															
	Variables  Variables  FEH Rainfall  Feturn Period (years)   100  Variables  Variables   Verion   1999   199	Cv (Summer) Cv (Winter)	0.750 0.840 0.540	Quick Storage Micro Drainage	Results Global of betw			eroximate st m³. only and sh	orage	used for de	sign purpo			<b>X</b>			
	Variables	Infiltration Coefficient (m/hr) Safety Factor		Variables Results Design Overview 2D Overview 3D Vt													
	Enter Maximum Allowab	Analyse Of Other Discharge between 0.0 and 999999.				Ente	er Maximum Al	owable Disch	Analy		OK 99.0	Cancel	Help	lp .			
	Attenuation volume (m3)	252											1				



WIE Company: Office: London WIE10667 9 of 10 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018

Date

Checked:

LOCATION			CAL	CULAT	IONS	3											)PTI	ONS
	In order to calculate the volume o Control module, Quick Storage Es		•							_		016.1	, Sourc	e				
	Drainage Catchment - West 6																	=
	Area	0.38 ha	1															
	50% of existing discharge rate	71.3 l/s/	/ha															
	Maximum allowable discharge	26.95 l/s	i															
	✓ Quick Storage Estimate		-		<b>-</b> /	Quick Stora	ige Estimato	e									×	
	Variables   FEH Rainfall   Return Period (years)   100   FEH Rainfall   Return Period (years)   100   Variables   Results   Site   GB 520450 176000 TQ 20450 7 C (1km)   0.024   D3 (1km)   0.216   D1 (1km)   0.322   E (1km)   0.365   C (1km)   0.253   D2 (1km)   0.262   F (1km)   2.539   Vit	Cv (Summer) Cv (Winter) Impermeable Area (ha) Maximum Allowable Discl Inflation Coefficient (m/ Safety Factor Climate Change (%)				Variables  Results  Design  Overview 20  Vt	of bet	al Variabl tween 14	45 m³ ar	ire approxii d 209 m². imates only			sed for des	ign purpor	ses.			
	Enter Maximum Allowable	Analyse  Discharge between 0.0 and 999	OK Cancel	Help	Į.			E	inter Max	imum Allowab	le Discharge	Analys between 0.	0 and 99999	9.0	Cancel	н	elp	
												I				T		
	Attenuation volume (m3)	177																



WIE Company: Office: London WIE10667 10 of 10 Sheet No: Project No: N Balboni Ву Date 13/02/2018 O O'Donovan 13/02/2018

Date

Checked:

LOCATION	CALCULATIONS	OPTIONS
	In order to calculate the volume of surface water attenuation required for the Site, Windes Microdrainage version 2016.1, Source Control module, Quick Storage Estimate has been used. The input and output data for which are shown below;	
	Drainage Catchment - West 7	
	Area 0.79 ha	
	50% of existing discharge rate 71.3 l/s/ha	
	Maximum allowable discharge 56.33 l/s	
	Variables   Version   1599   Variables   Variables   Version   1599   Variables   Variables	
	Analyse OK Cancel Help Analyse OK Cancel Enter Maximum Allowable Discharge between 0.0 and 999999.0 Enter Maximum Allowable Discharge between 0.0 and 999999.0	Help
	Attenuation volume (m3) 369	



I. Existing and Proposed Drainage Plan

