



GUARANTEE / WARRANTY

7 year extended warranty available

BOL LED MAINS / BL03 Straight to mains, wooden LED bollard

FEATURES			
Wattage	5W	Input	Mains AC
IP Rating	IP65	LED Lifetime	70,000h L70, B10
SDCM	3SDCM		

PHOTOMETRICS @ 25°C						
Colour	Beam Angle	Product Code	CRI	lm	lm/W	lx at 1m
4000K	110°	See configurator	>80Ra	246	49	104
3000K	110°	See configurator	>80Ra	160	32	80
2700K	110°	See configurator	>80Ra	156	31	78
			Available on request, p	lease call our t	eam for lead times a	nd MOQ on 01604 495 151

INSTALLATION INFORMATION				
Weight	5.5kg	Inrush Current	17.9A 0.1ms	
Construction Material	See page 284-285	Bathroom Zone	2	
Face Temperature	43°C	Amhient Temperature	35°C	

WIRING INFORMATION NEW 1.5mm SY 2 Core PVC Steel Braid Cable Cable / Flying Lead Type of Wiring Required Parallel (mains) 220-240V AC 50/60Hz

LED DRIVERS					
Product Code	mA	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	-	No	2	-	-

ACCESSORIES		
Product Code	Description	
BOL LED BRACKET	Stainless steel bracket for BOL LED range	288
JB5	Gel filled junction box	375

FEATURES & BENEFITS

NEW armoured cable as standard; no need for additional capping or conduit

Hand-crafted wood and with an IP65 rating, this bollard is both a stunning and $% \left(1\right) =\left(1\right) \left(1\right) \left($ functional addition to outdoor areas

The raw timber weathers over time to a beautiful colour or can be treated to maintain its original colour





