

MAISON ARCHITECTURE & DESIGN	
T. +44 (0)20 7384 13 E. STEVEN@MAISON. 272 KENSINGTON HI SUITE 80, LONDON W	AD.COM British Instruct GH STREET OF Interior
Client:	
Mr Howorth	
44 Lebanon Pa	rk
Twickenham T	W1 3DG
Job Title: New Rear Dormer	
Proposed Drawing:	
r roposed Drawing:	Proposed Elevations
Drawing No:	Drawn:
AD-20-10-033	mds
Checked:	Revision:
sp	A
Scale:	Date:
as shown @ A3	June 2020
Revisions:	
rte ( lorono)	
	nlanning 21 11 2020
	planning 21.11.2020
A - Revised for Notes: All Work is to be constructed	ed in accordance with the relevant Building
A - Revised for Notes: All Work is to be construct Regulations and to the satisi	ed in accordance with the relevant Building faction of the Building Inspector.
A - Revised for Notes: All Work is to be construct Regulations and to the satis All work is to comply with	ed in accordance with the relevant Building
A - Revised for Notes: All Work is to be constructor Regulations and to the satiss All work is to comply with practice	ed in accordance with the relevant Building faction of the Building Inspector.
A - Revised for Notes: All Work is to be construct Regulations and to the satis All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac	d in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 coordance with current edition of BS 5839
A - Revised for Notes: All Work is to be constructor Regulations and to the satis: All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 ccordance with current edition of BS 8301. 1985 nstructions.
A - Revised for Notes: All Work is to be construct Regulations and to the satis: All work is to comply with practice Drainage work is to be in ac CP 301 and manufactures i to be in according to be and CP 301 and manufactures i to be an another the set of	d in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 coordance with current edition of BS 5839
A - Revised for Notes: All Work is to be constructer Regulations and to the satis: All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5266 pt 1	d in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 (cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of
A - Revised for Notes: All Work is to be constructer Regulations and to the satis: All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5266 pt 1	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 ccordance with current edition of BS 8301. 1985 nstructions.
A - Revised for Notes: All Work is to be constructor Regulations and to the satis All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5266 pt 1 Signs and notices are to be i BS 5499 Pt 1. Foundations, structure and I	d in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 (cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of pelow slab drainage are to be detailed by
A - Revised for Notes: All Work is to be constructor Regulations and to the satis: All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in an CP 301 and manufacturers i Emergency lighting is to be BS 5266 pt 1 Signs and notices are to be i BS 5266 pt 1 Foundations, structure and I structural engineer. Drawin	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of pelow slab drainage are to be detailed by gs and calculations are to be submitted to the
A - Revised for Notes: All Work is to be construct Regulations and to the satis All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in as CP 301 and manufactures Emergency lighting is to be BS 5266 pt 1 Signs and notices are to be i BS 5499 Pt 1. Foundations, structure and I structural engineer. Drawin Local Authority for approva	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 ecordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of pelow slab drainage are to be detailed by gs and calculations are to be submitted to the d.
A - Revised for Notes: All Work is to be constructe Regulations and to the satis All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5296 pt 1 Signs and notices are to be i BS 5499 Pt 1. Foundations, structure and I structural engineer. Drawin Local Authority for approva Walls to core areas are to pr	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of pelow slab drainage are to be detailed by gs and calculations are to be submitted to the
A - Revised for Notes: All Work is to be construct Regulations and to the satis All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in a CP 301 and manufactures Emergency lighting is to be BS 5499 Pt 1. Foundations, structure and I structural engineer. Drawin Local Authority for approva Walls to core areas are to pn shafts (extent shown in hatco walls or floor are to be adeque	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 scordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of pelow slab drainage are to be detailed by gs and calculations are to be submitted to the ul. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped
A - Revised for Notes: All Work is to be construct Regulations and to the satis All Work is to comply with practice Fire Alarm installed in acco Drainage work is to be in a CP 301 and manufacturers i Emergency lighting is to be BS 5499 Pt 1. Foundations, structure and I structural engineer. Drawin Local Authority for approva Walls to core areas are to pr shafts (extent shown in hate quals or floor are to be adeq All structural steelwork is to	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of pelow slab drainage are to be detailed by gs and calculations are to be submitted to the u. ovide one hour fire resistance to protected hed) and all services etc. passing through the
A - Revised for Notes: All Work is to be constructor Regulations and to the satist All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in an CP 301 and manufacturers i Emergency lighting is to be BS 52606 pt 1 Signs and notices are to be in BS 52606 pt 1 Signs and notices are to be in BS 52606 pt 1 Signs and notices are to be in BS 52606 pt 1 Signs and notices are to be in BS 52606 pt 1 Signs and notices are to be in BS 52606 pt 1 Signs and notices are to be in BS 52606 pt 1 Signs and notices are to be in Signs and notices are to be in BS 52606 pt 1 Signs and notices are to be in Signs and notices are to be in Signs and notices are to be in Signs and notices are to be adeq All structural steelwork is to and existing)	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 coordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of selow slab drainage are to be detailed by gs and calculations are to be submitted to the al. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o be protected to one hour fire resistance (new
A - Revised for Notes: All Work is to be construct Regulations and to the satis All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in a CP 301 and manufacturers Emergency lighting is to be BS 5499 Pt 1. Foundations, structure and H structural engineer. Drawin Local Authority for approva Walls to core areas are to pain shafts (extent shown in has shafts (extent shown	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of nstalled in accordance with current edition of pelow slab drainage are to be detailed by gs and calculations are to be submitted to the ul. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o be protected to one hour fire resistance (new irculation areas and protected is to be class 'O'
A - Revised for Notes: All Work is to be constructor Regulations and to the satist All Work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5266 pt 1 Signs and notices are to be in BS 5266 pt 1 Signs and notices are to be in Source and a structure and 1 structural engineer. Drawin Local Authority for approva Walls to core areas are to pu shafts (extent shown in hatci walls or floor are to be adeq All structural steelwork is to and existing) Surface spread of flame to co wall and ceilings. All other Dimensions are to be check	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 coordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of selow slab drainage are to be detailed by gs and calculations are to be submitted to the d. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o be protected to one hour fire resistance (new irculation areas and protected is to be class 'O' areas are to be class 'I' walls and ceilings.
A - Revised for Notes: All Work is to be construct Regulations and to the satis All work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5499 Pt 1. Foundations, structure and H structural engineer. Drawin Local Authority for approva Walls to core areas are to be i BS 5499 Pt 1. Foundations, structure and H structural engineer. Drawin Local Authority for approva Walls to core areas are to be and existing) Surface spread of flame to c wall and ceilings. All other Dimensions are to be checkk Any discrepancies are to be	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of nstalled in accordance with current edition of selow slab drainage are to be detailed by gs and calculations are to be submitted to the ul. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o he protected to one hour fire resistance (new irculation areas and protected is to be class 'O' areas are to be class 'I' walls and ceilings. ed on site before fabrication and construction. notified to the designers
A - Revised for Notes: All Work is to be construct Regulations and to the satis: All Work is to comply with practice Practice Practice Signs and notices are to be in BS 5499 Pt 1. Foundations, structure and I structural engineer. Drawin Local Authority for approv Walls to core areas are to pr shafts (extent shown in hatc walls or floor are to be adeq All structural steelwork is to and existing) Surface spread of flame to c wall and ceilings. All other Dimensions are to be check Any discrepancies are to be Structural measurements are	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 coordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of selow slab drainage are to be detailed by gs and calculations are to be submitted to the d. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o be protected to one hour fire resistance (new irculation areas and protected is to be class 'O' areas are to be class 'I' walls and ceilings.
A - Revised for Notes: All Work is to be constructor Regulations and to the satis: All Work is to comply with practice Fire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5266 pt 1 Signs and notices are to be in BS 5266 pt 1 Signs and notices are to be in S 5266 pt 1 Signs and notices are to be in S 5266 pt 1 Signs and notices are to be in a CP 301 and manufacturers i Emergency lighting is to be BS 5266 pt 1 Signs and notices are to be in S 5266 pt 1 Signs and notices are to be in S 5266 pt 1 Signs and notices are to be check All structural steelwork is to and existing) Surface spread of flame to c wall and ceilings. All other Dimensions are to be check Any discrepancies are to be Structural measurements are drawings.	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of nstalled in accordance with current edition of selow slab drainage are to be detailed by gs and calculations are to be submitted to the ul. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o he protected to one hour fire resistance (new irculation areas and protected is to be class 'O' areas are to be class 'I' walls and ceilings. ed on site before fabrication and construction. notified to the designers
A - Revised for Notes: All Work is to be construct Regulations and to the satis: All Work is to comply with practice Practice Practice Signs and notices are to be in BS 5499 Pt 1. Foundations, structure and I structural engineer. Drawin Local Authority for approv Walls to core areas are to pr shafts (extent shown in hatc walls or floor are to be adeq All structural steelwork is to and existing) Surface spread of flame to c wall and ceilings. All other Dimensions are to be check Any discrepancies are to be Structural measurements are	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of nstalled in accordance with current edition of selow slab drainage are to be detailed by gs and calculations are to be submitted to the ul. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o he protected to one hour fire resistance (new irculation areas and protected is to be class 'O' areas are to be class 'I' walls and ceilings. ed on site before fabrication and construction. notified to the designers
A - Revised for Notes: Al Work is to be constructor Regulations and to the satis All Work is to be comply with practice Bire Alarm installed in acco Drainage work is to be in ac CP 301 and manufacturers i Emergency lighting is to be BS 5499 Pt 1. Foundations, structure and h structural engineer. Drawin Local Authority for approva Walls to core areas are to pr shafts (extent shown in hate walls or floor are to be adeq All structural steelwork is tt and existing) Surface spread of flame to c wall and ceilings. All other Dimensions are to be check Any discrepancies are to be Structural measurements are drawings. Do not Scale All arrows point UP steps Copyright reserved by Mais	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 cordance with current edition of BS 5830 installed in accordance with current edition of nstalled in accordance with current edition of sea and calculations are to be submitted to the al. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o be protected to one hour fire resistance (new irculation areas and protected is to be class 'O' areas are to be class 'I' walls and ceilings. et on site before fabrication and construction. notified to the designers ot be taken from the structural engineers
A - Revised for Notes: All Work is to be construct Regulations and to the satis: All Work is to comply with practice Practice Practice Practice BS 5499 Pt 1. Foundations, structure and I structural engineer. Drawin ES 5499 Pt 1. Foundations, structure and I structural engineer. Drawin Local Authority for approva Walls to core areas are to pe ishafts (extent shown in hatc core areas are to pr shafts (extent shown in hatc and existing) Surface spread of flame to c wall and ceilings. All other Dimensions are to be check Any discrepancies are to be Structural measurements are drawings. Do not Scale All arrows point UP steps	ed in accordance with the relevant Building faction of the Building Inspector. the relevant British Standards and codes of rdance with current edition of BS 5839 coordance with current edition of BS 8301. 1985 nstructions. installed in accordance with current edition of nstalled in accordance with current edition of nstalled in accordance with current edition of selow slab drainage are to be detailed by gs and calculations are to be submitted to the ul. ovide one hour fire resistance to protected hed) and all services etc. passing through the uately fire stopped o be protected to one hour fire resistance (new irculation areas and protected is to be class 'O' areas are to be class 'I' walls and ceilings. et on site before fabrication and construction. notified to the designers to be taken from the structural engineers on AD Ltd