



Goundfloor Patios Paving slabs: Mayfield supplied by Tobermore or similar equivalent; Colour: sandstone; non-slip textured slabs installed in accordance with the manufacturer's instructions

FIGURED DIMENSIONS ONLY TO BE USED

drawings for construction.



Access Road & Car parking Bays: Permeable Block Paving: Marshalls or Tobermore or similar equivalent; colour TBC; installed in accordance with the manufacturer's instructions. Use contrasting colour for the car parking bays

Issue Revision



Automatic retractable bollard Stainless steel: Details by engineer

Added path & metal demarcation studs MS 02-03-2023

Initial Date



Permeable Resin Bound surface: Sureset or similar equivalent; colour TBC; installed in accordance with the manufacturer's instructions



Sheffield Cycle Stands: supplied by Broxap or similar equivalent; finish TBC; installed in accordance with the manufacturer's instructions

1. For details on retaining structures - please refer to Engineer's details.

2. Surface finishes to be installed in accordance with the manufacturers

4. All surface materials & play equipment/ furniture installed in accordance with

3. Indicative levels - detailed levels to be provided by engineers.



Pixilated Paving; concrete block paving supplied by Tobermore or similar equivalent; installed in accordance with the manufacturer's instructions



Chess Board Paving; concrete block paving supplied by Tobermore or similar equivalent; installed in accordance with the manufacturer's



450mm x 450mm high x 2000mm lengths, root fixed and installed in accordance with the manufacturer's instructions



Rear Terraces: Timber close board fences, 1200mm high with capping rail and gravel boards



Roard Frontage boundaries: Flat top railings 1200mm high; supplied by Alpha Rail or similar equivalent

All railings and posts to be installed in accordance with manufacturer's

Supplier to provide detail drawings of fences and gates and all measurements to be checked and confirmed on site prior to fabrication and installation. - Posts fixed with welded flat base plate with 4 no. pre-drilled slotted holes. Post fixed to coping stone.


- Gate posts to be 75x75mm SHS with welded flat base plate with 4 no. pre-drilled slotted holes.

www.studioloci.eu

- All fixings to be galvanized.

- All details to be checked and approved by engineer prior to works - All metal gates and railings to comply to BS4092 and BS1722 part 9. Supplied by GreenBlue Urban Guide





Date 30/03/2023 Status PLANNING Studio Loci (Trading name of LDC Ltd) The Charcoal House GU48NQ 01483 573817

Project Number and Title KINGSTON BRIDGE HOUSE, HAMPTON WICK, KT1 4AG

SURFACES FINISHES PLAN

Drawing Number 10263 - GA - 03

3. Any discrepancies found in this drawing or other drawings and specifications in the construction document must be referred to the Designer prior to work commencing. 4. This drawing must not be copied in whole or in part

. This drawing is to be read in conjunction with all other drawings.

2. Do not scale off this drawing for construction purposes. Written dimensions to be taken only. All dimensions are in millimetres and must be checked on site against Engineers setting out

> 5. All hard surfacing laid to falls. 6. Surface Drainage - to be provided by engineers.

the manufacturers recommendations

PLANNING