

Nicolas James Building Ltd Harbour House, 60 Purewell Christchurch Dorset **BH23 1ES**

Account: N0000331

Date: 21/03/2021

Customer Information

Sales Executive: Matthew Blaylock

E-mail: Matthew.Blaylock@mumfordwood.cor

Tel: 07805 806673 Processor: Rob Naylor

Project number: PRJ-19051118 Site: Richmond Harbour Hotel Spa, 152-158 Richmond Hill, Richmond Upon Thames, Surrey,

TW10 6RP

Delivery Terms: Delivery Included Est. Delivery Wk/End: 02/04/2021

Manufacturing Confirmation: 2010077

SUPPLY ONLY		REV 06
Item Summary	Item Qty	
Bifold	1	
Casement windows	4	
Net Total		
Vat @ 20%		
Grand Totals	5	

Current Payment Summary: 50% Deposit / Balance Prior due to dispatch

- Any variation to the quoted prices as a result of changes made to quantities, sizes or specification will be reflected in the final
- Future amendments an administration fee of minimum £250 will apply, and lead time may be extended. I/we will be liable for all costs incurred by Mumford & Wood Ltd as a result of any amendment.
- In the event of cancellation of this order then I/we will be liable for all costs incurred by Mumford & Wood Ltd at the time of cancellation. Such costs will not exceed the contract value.
- All products are sold to our "Standard Conditions of Sale", full details available upon request.
- Mumford & Wood Ltd accept measurement responsibility for all fully formed structural openings measured by Mumford & Wood Ltd at the time of the survey.

Instruction to manufacture. Please complete below and return this covering page.

Please accept this as confirmation our specification has been interpreted correctly at the above cost to begin manufacture

Print Name: Company:

Signature: Position:

te: Purchase Order No. (if applicable):
All timber and wood based components are supplied as FSC Mix 70% under Chain of Custody Registration Number TT-COC-003956

Page 1 of 13



Mumford & Wood Ltd, Tower Business Park, Kelvedon Road, Tiptree, Essex. CO5 0LX

Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Please check your requirements have been interpreted correctly.

No liability will be accepted for any errors that may occur

Item Quantity	Description	No liability will be accepted for any errors that may Per Item Tota
4 TANA	GF STUDIO	- I of nom
	SW 0.20	
	SVV 0.20	
8000	Product: Size: Weight: Frame Timber: Sash Timber: Finish: Colour: Frame Width: Sash Width:	Bifold Sliding Door 8000 mm x 2365 mm 659 kg Red Grandis Red Grandis Fully Finished Stain 3 Coat Teak Base With Cypress Topcoat Head 112 Cill 56 Left 50 Right 50 SNo Top Bottom Left Right 1 94 94 94 94 2 94 94 94 94 2 94 94 94 94 3 94 94 94 94 4 94 94 94 94 5 94 94 94 94 5 94 94 94 94 7 94 94 94 94 7 99 94 94 94
		8 94 94 94 94
		9 94 94 94 94 10 94 94 94
	Frame Profile: Sash Profile: Bar: Sash: Openings: Hardware:	Square Sash TrueBar Outward Bi-fold Door BiFold Door System FSC MATERIAL USED BR Fittings - Satin Stainless Steel Cill - Aluminium Finish Supplied FLATPACK with Loose Sashes. Handle-Operated Multi-point Lock Door Handle - Oaken Satin Chrome Plate Nickel Euro Cylinder Door Handles & Cylinder sent loose Door Magnetic Catch (sent loose)
	Glass Specifica	
		4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 1.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 1.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 1.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 1.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 1.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 2.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 2.2 6.8mm Clear Laminated / 14mm Argon /

Page 2 of 13



Order confirmation: 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Please check your requirements have been interpreted correctly.

No liability will be accepted for any errors that may occur

Item Quantity Description Per Item Total

4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 2.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 2.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 2.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) PLUS. 3.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 3.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 3.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 3.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 3.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 4.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 4.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 4.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 4.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 4.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 5.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 5.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 5.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 5.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) PLUS. 5.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 6.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E

Page 3 of 13



Order confirmation: 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Please check your requirements have been interpreted correctly.

No liability will be accepted for any errors that may occur

Item Quantity Description Per Item Total **PLUS** Black WarmEdge Spacer (Std) 6.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PI US Black WarmEdge Spacer (Std) 6.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 6.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 6.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 7.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 7.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 7.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 7.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 7.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) PI US 8.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 8.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 8.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) 8.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 8.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 9.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) PI US 9.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E Black WarmEdge Spacer (Std) **PLUS** 9.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E **PLUS** Black WarmEdge Spacer (Std) 9.4 6.8mm Clear Laminated / 14mm Argon /

Page 4 of 13

PLUS

PLUS



Mumford & Wood Ltd, Tower Business Park, Kelvedon Road, Tiptree, Essex. CO5 0LX

4mm Clear Toughened Soft Coat Low-E

9.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E

Black WarmEdge Spacer (Std)

Black WarmEdge Spacer (Std)

Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Item	Quantity	Description	Per Item	Tota
Item	Quantity	Description	10.1 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 10.2 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 10.3 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) 10.4 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std) Black WarmEdge Spacer (Std)	Ιοτα
			10.5 6.8mm Clear Laminated / 14mm Argon / 4mm Clear Toughened Soft Coat Low-E PLUS Black WarmEdge Spacer (Std)	



Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Item	Quantity	Description					F	Per Item	Total
2	1 No.	GF STUDIO							
2 + 3 + 98 200		SW 0.19							
1154		Product: Size: Weight: Frame Timber: Sash Timber: Finish: Colour: Frame Width:	Conservation Casement 1154 mm x 2365 mm 117 kg Red Grandis Fully Finished Stain 3 Coat Teak Base With Cypress Topcoat Head 68 Cill 68 Left 68 Right 68 Transom 68 68 68						
		Sash Width:	68 SNo 1 2 3 4	0 0 0 0	Bottom 0 0 0 0	0 0 0	Right 0 0 0 0		
		Frame Profile: Sash Profile: Sash: Openings: Hardware: Attachments:	OO D Direct	re Sash G Fan/l t Glazed C Mater 60mm C	Fixed li d Fixed ial Use	Light ed	0 lo Windo	ow Board	
		Glass Specificat	_	/e					
			1.1 6 4mm PLUS 2.1 6 4mm PLUS 3.1 6 4mm PLUS 4.1 6 4mm PLUS 5.1 6	Clear T B .8mm C Clear T Clear T Clear T Clear T B .8mm C Clear T Clear T Clear T Clear T Clear T	ougher Lack Wilear Wilea	ned So armEd aminate ned So armEd aminate ned So armEd aminate aminate aminate aminate ned So armEd aminate ned So	ft Coat L ge Spaced / 14m ft Coat L	eer (Std) m Argon / Low-E eer (Std)	






Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Item	Quantity	Description					F	Per Item	Total
3	1 No.	GF STUDIO							
2 +		SW 0.21							
1154		Product: Size: Weight: Frame Timber: Sash Timber: Finish: Colour: Frame Width:	Fully Finished Stain 3 Coat Teak Base With Cypress Topcoat Head 68 Cill 68 Left 68 Right 68 Transom 68 68 68						
		Sash Width:	68 SNo 1 2 3 4	Top 0 0 0 0	Bottom 0 0 0 0	Left 0 0 0 0	Right 0 0 0 0		
		Frame Profile: Sash Profile: Sash: Openings: Hardware: Attachments:	OO D Direct FS0	re Sash G Fan/ t Glazeo C Mater 60mm C	Fixed li d Fixed ial Use	Light ed	0 lo Windo	ow Board	
		Glass Specificat	Groo\ tion:	/e					
			1.1 6 4mm PLUS 2.1 6 4mm PLUS 3.1 6 4mm PLUS 4.1 6 4mm PLUS 5.1 6	Clear T B. 8mm (Clear T Clear T Clear T Clear T B. 8mm (Clear T Clear T Clear T Clear T Clear T	ougherlack Wilear Lace Wilack Wilear Lace Wilack Wilear Lace Wilear Lace Wilack Wilear Lace Wilack Wilear Lace Wilack Wilear Lace Wilace Wilac	ned So armEd aminate ned So armEd aminate ned So armEd aminate aminate aminate aminate ned So armEd aminate ned So	ft Coat L ge Spac ed / 14m ft Coat L	er (Std) m Argon / .ow-E er (Std)	





Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Please check your requirements have been interpreted correctly.

No liability will be accepted for any errors that may occur

Item			Quantity	Description					F	Per Item	Total
4	1" 2" 3" 4" 5" 6" 7" 8" 0" 1D	TuT	1 No.	GF STUDIO				-			
	17 12 13 17 15 16 17 18 10 20 21 22 23 21 25	2365		SW 0.18							
	5000			Product: Size: Weight: Frame Timber: Sash Timber: Finish: Colour: Frame Width:	5000 508 k Red 0 Fully Teak Head	mm x g Grandi: Finishe Base \ 68 Cil n Tra	en Casen 2365 mr s ed Stain With Cyp I 68 Left ansom 68 68 68 68	n 3 Coa oress T	opcoat		
				Sash Width:	68 SNo 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	Top 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Bottom 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Left 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Right 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		

Page 8 of 13



Mumford & Wood Ltd, Tower Business Park, Kelvedon Road, Tiptree, Essex. CO5 0LX

(Please Note: Images viewed from outside. Arrow denotes hinge position) Order confirmation: 2010077

							uirements have been inte be accepted for any error	
Item	Quantity	Description				-	Per Item	Tota
			23	0	0	0	0	
			24	0	0	0	0	
			25	0	0	0	0	
		Frame Profile:	Squai					
		Sash Profile:		re Sash		abt		
		Sash: Openings:		G Fan/ t Glaze				
		Hardware:		C Mate		•		
		Attachments:	1 00	Jiviato	iai osc	,u		
		7 1000	BayW	/indow	Post			
						ender N	lo Window Board	
			Groo۱	/e				
		Glass Specifica		_				
							ed / 14mm Argon /	
			4mm PLUS				ft Coat Low-E ge Spacer (Std)	
							ge Spacer (Std) ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon / ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
							ft Coat Low-Ĕ	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
			4mm PLUS				ft Coat Low-E	
				8mm (Clear I	ann⊏u aminate	ge Spacer (Std) ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon / ft Coat Low-E	
			PLUS				ge Spacer (Std)	
			_				ted / 14mm Argon	
							oft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ted / 14mm Argon	
			PLUS				oft Coat Low-E ge Spacer (Std)	
							ted / 14mm Argon	
							oft Coat Low-E	
			PLUS	; E	Black W	armEd	ge Spacer (Std)	
							ted / 14mm Argon	
							oft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ted / 14mm Argon oft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ted / 14mm Argon	
							oft Coat Low-E	
			DLLIC				ac Chacar (Ctd)	

Page 9 of 13

PLUS



Black WarmEdge Spacer (Std)

Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Item	Quantity	Description	Per Item	Total
			16.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			17.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			18.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			19.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			20.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			21.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			22.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			23.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			24.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			25.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
		_	TH LOOSE 93 X 93MM TIMBER POST FOR	
		SITE FITTING		




Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Please check your requirements have been interpreted correctly.

No liability will be accepted for any errors that may occur

14		Over##	December:			ino iiabi	iity Will		ed for any error	
Item 5		Quantity 1 No.	Description GF STUDIO					P6	er Item	Total
5	1 7 2 4 5 9 9 9 9 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	i NO.	SW 0.22							
	5000		Product: Size: Weight: Frame Timber: Sash Timber: Finish: Colour: Frame Width:	5000 508 kg Red 0 Fully l Teak Head	mm x g Grandi Finish Base \ 68 Cil n Tra	on Casen 2365 mn s ed Stain With Cyp I 68 Left ansom 68 68 68 68	n 3 Coat oress T	opcoat		
			Sash Width:	SNo 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	Top 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Bottom 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Left 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Right 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		

Page 11 of 13




Mumford & Wood Ltd, Tower Business Park, Kelvedon Road, Tiptree, Essex. CO5 0LX

(Please Note: Images viewed from outside. Arrow denotes hinge position) Order confirmation: 2010077

							uirements have been inte be accepted for any error	
Item	Quantity	Description				-	Per Item	Tota
			23	0	0	0	0	
			24	0	0	0	0	
			25	0	0	0	0	
		Frame Profile:	Squai					
		Sash Profile:		re Sash		abt		
		Sash: Openings:		G Fan/ t Glaze				
		Hardware:		C Mate		•		
		Attachments:	1 00	Jiviato	iai osc	,u		
		7 1000	BayW	/indow	Post			
						ender N	lo Window Board	
			Groo۱	/e				
		Glass Specifica		_				
							ed / 14mm Argon /	
			4mm PLUS				ft Coat Low-E ge Spacer (Std)	
							ge Spacer (Std) ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon / ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
							ft Coat Low-Ĕ	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
			4mm PLUS				ft Coat Low-E	
				8mm (Clear I	ann⊏u aminate	ge Spacer (Std) ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon /	
							ft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ed / 14mm Argon / ft Coat Low-E	
			PLUS				ge Spacer (Std)	
			_				ted / 14mm Argon	
							oft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ted / 14mm Argon	
			PLUS				oft Coat Low-E ge Spacer (Std)	
							ted / 14mm Argon	
							oft Coat Low-E	
			PLUS	; E	Black W	armEd	ge Spacer (Std)	
							ted / 14mm Argon	
							oft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ted / 14mm Argon oft Coat Low-E	
			PLUS				ge Spacer (Std)	
							ted / 14mm Argon	
							oft Coat Low-E	
			DLLIC				ac Chacar (Ctd)	

Page 12 of 13

PLUS



Mumford & Wood Ltd, Tower Business Park, Kelvedon Road, Tiptree, Essex. CO5 OLX

Black WarmEdge Spacer (Std)

Order confirmation : 2010077 (Please Note: Images viewed from outside. Arrow denotes hinge position)

Item	Quantity	Description	Per Item	Total
			16.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			17.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			18.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			19.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			20.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			21.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			22.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			23.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			24.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
			25.1 6.8mm Clear Laminated / 14mm Argon	
			/ 4mm Clear Toughened Soft Coat Low-E	
			PLUS Black WarmEdge Spacer (Std)	
		_	TH LOOSE 93 X 93MM TIMBER POST FOR	
		SITE FITTING		

