



Goundfloor Patios Paving slabs: Mayfield supplied by Tobermore or similar equivalent; Colour: sandstone; non-slip textured slabs installed in accordance with the manufacturer's instructions

4. This drawing must not be copied in whole or in part



Access Road & Car parking Bays: Permeable Block Paving: Marshalls or Tobermore or similar equivalent; colour TBC; installed in accordance with the manufacturer's instructions. Use contrasting colour for the car parking bays



Automatic retractable bollard Stainless steel: Details by engineer



Permeable Resin Bound surface: Sureset or similar equivalent; colour TBC; installed in accordance with the manufacturer's instructions




Sheffield Cycle Stands: supplied by Broxap or similar equivalent; finish TBC; installed in accordance with the manufacturer's instructions



Pixilated Paving; concrete block paving supplied by Tobermore or similar equivalent; installed in accordance with the manufacturer's instructions; Colours: Graphite, Mid-Grey and



450mm x 450mm high x 2000mm lengths, root fixed and installed in manufacturer's instructions



Rear Terraces: Timber close board fences, 1200mm high with capping rail and gravel boards



Roard Frontage boundaries: Flat top railings 1200mm high; supplied by Alpha Rail or similar equivalent

## **FLAT TOP RAILINGS**

All railings and posts to be installed in accordance with manufacturer's

Supplier to provide detail drawings of fences and gates and all measurements to be checked and confirmed on site prior to fabrication and installation.

- Posts fixed with welded flat base plate with 4 no. pre-drilled slotted holes. Post fixed to coping stone.

- Gate posts to be 75x75mm SHS with welded flat base plate with 4 no. pre-drilled slotted holes.

- All fixings to be galvanized.

- All details to be checked and approved by engineer prior to works

- All metal gates and railings to comply to BS4092 and BS1722 part 9.



Supplied by GreenBlue Urban Guide

## FIGURED DIMENSIONS ONLY TO BE USED Issue Revision Initial Date Added paths, omitted the chess board MS 08-08-2023 . This drawing is to be read in conjunction with all other drawings. 2. Do not scale off this drawing for construction purposes. Written

dimensions to be taken only. All dimensions are in millimetres and must be checked on site against Engineers setting out drawings for construction. 3. Any discrepancies found in this drawing or other drawings and specifications in the construction document must be referred to the Designer prior to work commencing.

1. For details on retaining structures - please refer to Engineer's details.

2. Surface finishes to be installed in accordance with the manufacturers

3. Indicative levels - detailed levels to be provided by engineers. 4. All surface materials & play equipment/ furniture installed in accordance with

the manufacturers recommendations

5. All hard surfacing laid to falls.

6. Surface Drainage - to be provided by engineers.