

13. The Likelihood of Contamination from Allied Ordnance

13.1. Introduction

There are several factors that may serve to either affirm, increase, or decrease the level of risk within a site with a history of military usage. Such factors are typically dependent upon the proximity of the proposed area of works to training activities, munition productions and storage, as well as its function across the years.

This section will examine the history of the proposed site and assess to what degree, if any, the site could have become contaminated as a result of the military use of the surrounding area.

13.2. Evaluation of Contamination Risk from Allied UXO

1st Line Defence has considered the following potential sources of Allied ordnance contamination:

Allied UXO Records Summary	
Sources of Allied UXO Contamination	Conclusion
Military Camps Military camps present an elevated risk from ordnance simply due to the large military presence and likelihood of associated live ordnance training.	1 st Line Defence could find no evidence of a military camp within the site.
Anti-Aircraft Defences Anti-Aircraft defences were employed across the country. Proximity to anti-aircraft defences increases the chance of encountering AA projectiles.	1 st Line Defence could find no evidence of Anti-Aircraft defences such as a HAA or LAA gun emplacement occupying or bordering the site. The closest HAA was located approximately 4.2km south-east of the site, in the vicinity of Thames Ditton. Despite this distance the maximum effective range of an AA projectile can be up to 15km. The conditions in which HAA or LAA projectiles may have fallen unnoticed within a site footprint are generally analogous to those regarding German air delivered ordnance.
Home Guard Activity The Home Guard regularly undertook training and ordnance practice in open areas, as well as burying ordnance as part of anti-invasion defences.	Evidence of Home Guard activity is often difficult to locate, owing to the ad-hoc nature of Home Guard activity within each local area. Such training was often conducted on a small scale at the discretion of individual commanders and as such was seldom recorded officially. As such, no positive evidence could be found to confirm the presence of HG units within proximity to the site.
Defensive Positions Defensive positions suggest the presence of military activity, which is often indicative of ordnance storage, usage or disposal.	There is no evidence of any pillbox, emplacement or other defensive features formerly located on or bordering the site footprint.
Training or firing ranges Areas of ordnance training saw historical ordnance usage in large numbers, often with inadequate disposal of expended and live items. The presence of these ranges significantly impact on the risk of encountering items of ordnance in their vicinity.	No evidence of training or firing ranges could be found within the site or surrounding area.



Defensive Minefields Minefields were placed in strategic areas to defend the country in the event of a German invasion. Minefields were not always cleared with an appropriate level of vigilance.	There is no evidence of defensive minefields affecting the site.
Ordnance Manufacture Ordnance manufacture indicates an increased chance that items of ordnance were stored, or disposed of, within a location.	No information of ordnance being stored, produced, or disposed of within the proposed site could be found.
Military Related Airfields Military airfields present an elevated risk from ordnance simply due to the large military presence and likelihood of associated live ordnance training or bombing practice.	The site was not situated within the perimeters or vicinity of a military airfield.

14. The Likelihood of UXO Contamination Summary

The following table assesses the likelihood that the site was contaminated by items of German air delivered and Allied ordnance. Factors such as the risk of UXO initiation, remaining, and encountering will be discussed later in the report.

UXO Contaminati	ion Summary
Quality of the Historical Record	The research has evaluated pre-WWII and post-WWII Ordnance Survey maps, a WWI map of air raids and naval bombardments, a London WWII bomb density map, Luftwaffe reconnaissance imagery, weekly and consolidated London bomb census mapping. Home Office bombing statistics, a local Richmond bomb census map, Richmond and Twickenham written records, post-WWII high-resolution RAF aerial photography and in-house sources. The record set is of generally good quality, with several sources corroborative of one another regarding bombing incidents and evidence of damage from bomb strikes. Both local bomb mapping and London bomb census mapping do not plot any bomb strikes in a range close enough to the site. Finally, the post-WWII high-resolution 1947 RAF aerial photography allowed for an assessment on the possible wartime condition of the site and immediate surrounding area.
German Air- Delivered Ordnance	 During WWII, the site was situated within the Municipal Borough of Twickenham, which was subject to an overall moderate-high density of bombing according to official Home Office bombing statistics, with an average of 82.8 bombs recorded per 1,000 acres. During WWII, the site composed predominantly open ground and vegetation; with structures present for storing coal, and a section of railway siding running through the site in the north. The site was bordered by Oldfield Road and the Upper Sunbury branch for the industrial railway between the Metropolitan Water Board's pumping stations and coal wharf.⁴ Despite the moderate-high density recorded in the area, a local bomb map, local written records and London Bomb Census mapping does not record any HE bomb strikes on site, or within the immediate vicinity. The closest recorded strike is plotted approximately 60m southwest of the site within the vicinity of Oldfield Road Grammar School. This is recorded as a UXB, falling on 15th October 1941 in the 'Damage to Properties' record set. This incident is however, too far removed to have had any direct impact on the site boundary. As the site predominantly comprised undeveloped land, limited structures were present on site to incur observable damage. However, the MCC War Damage Map does not record any damage to the structures that were present on site, or those within the immediate vicinity. Post-war aerial photography also does not indicate any obvious signs of bomb damage, such as severely disturbed ground, cratering or extensive structural changes. While the structures on site do not appear to have any roofs, they match up with historical OS mapping and are thought to comprise the function of coal bunkers/storage for the <i>Coal Yard</i> on site. Annex O2 highlights some potential coses of disturbed ground in the vicinity, however, this does not directly affect the site boundary. During WWII the terrain on site was predominantly undeveloped. While areas

⁴ https://webblocos.co.uk/history/the-railway



	undeveloped nature of the site has the potential to obscure evidence of UXB entry holes, access to the site is thought to have remained frequent throughout the war due to the sites usage as a <i>Coal Yard</i> . Items of UXO are more likely to be spotted, recorded and dealt with within frequently accessed areas.
	• No evidence has therefore been found to suggest that the risk on site would be above the 'background risk' for this area. As a result, it is not deemed necessary to warrant proactive risk mitigation measures, and the site has therefore been assessed to be of Low Risk from German aerial delivered UXO contamination.
Allied Ordnance	• No evidence could be found to indicate that the site formerly had any military occupation or usage that could have led to contamination with items of Allied ordnance, such as LSA and SAA.
	• The conditions in which HAA or LAA projectiles may have fallen unnoticed within the site boundary are however analogous to those regarding air delivered ordnance.



15. The Likelihood that UXO Remains

15.1. Introduction

It is important to consider the extent to which any explosive ordnance clearance (EOC) activities or extensive ground works have occurred on site. This may indicate previous ordnance contamination or reduce the risk that ordnance remains undiscovered.

15.2. UXO Clearance

Ist Line Defence has found no evidence in the public domain or within internal records that any official ordnance clearance operations have taken place on site. Note however that we have not received confirmation of this fact from the 33 EOD Regiment Archive (now part of 29 EOD & Search Group). It should also be noted that in addition to 29 EOD & Search Group archival information, 1st Line Defence also do not currently have access to data that may be relevant including 5131(BD)SQN Archive, SD Training Technical Advisory Section (TAS) and MACA Records (bomb disposal callouts).

If such information is available at a later date, it is recommended that it be reviewed as it will assist with understanding both levels and types of contamination likely to be present, and may indicate risk reduction in certain areas.

15.3. **Post-War Redevelopment**

Recent aerial imagery indicates that the site has experienced noticeable post-war development. The majority of the site boundary is now occupied by a large commercial structure and associated hardstanding ground.

The risk of UXO remaining is considered to be mitigated at the location of and down to the depth of any postwar redevelopment on site. For example, the risk from deep buried UXO will only have been mitigated within the volumes of any post-war pile foundations or deep excavations for basement levels. The risk will however remain within virgin geology below and amongst these post-war works, down to the maximum bomb penetration depth.



16. The Likelihood of UXO Encounter

16.1. Introduction

For UXO to pose a risk at a site, there should be a means by which any potential UXO might be encountered on that site.

The likelihood of encountering UXO on the site of proposed works would depend on various factors, such as the type of UXO that might be present and the intrusive works planned on site. In most cases, UXO is more likely to be present below surface (buried) than on surface.

In general, the greater the extent and depth of intrusive works, the greater the risk of encountering. The most likely scenarios under which items of UXO could be encountered during construction works is during piling, drilling operations or bulk excavations for basement levels. The overall risk will depend on the extent of the works, such as the numbers of boreholes/piles (if required) and the volume of the excavations.

Generally speaking, the risk of encountering any type of UXO will be minimal for any works planned within the footprint and down to the depth of post-war foundations and excavations.

16.2. Encountering Air Delivered Ordnance

Since an air delivered bomb may come to rest at any depth between just below ground level and its maximum penetration depth, there is a chance that such an item (if present) could be encountered during shallow excavations (for services or site investigations) into the original WWII ground level as well as at depth.



17. The Likelihood of UXO Initiation

17.1. Introduction

UXO does not spontaneously explode. Older UXO devices will require an external event/energy to create the conditions for detonation to occur. The likelihood that a device will function can depend on a number of factors including the type of weaponry, its age and the amount of energy it is struck with.

17.2. Initiating Air Delivered Ordnance

Unexploded bombs do not spontaneously explode. All high explosive filling requires significant energy to create the conditions for detonation to occur.

In recent decades, there have been a number of incidents in Europe where Allied UXBs have detonated, and incidents where fatalities have resulted. There have been several hypotheses as to the reason why the issue is more prevalent in mainland Europe – reasons could include the significantly greater number of bombs dropped by the Allied forces on occupied Europe, the preferred use by the Allies of mechanical rather than electrical fuzes, and perhaps just good fortune. The risk from UXO in the UK is also being treated very seriously in many sectors of the construction industry, and proactive risk mitigation efforts will also have affected the lack of detonations in the UK.

There are certain construction activities which make initiation more likely, and several potential initiation mechanisms must be considered:

UXB Initiation	
Direct Impact	Unless the fuze or fuze pocket is struck, there needs to be a significant impact e.g. from piling or large and violent mechanical excavation, onto the main body of the weapon to initiate a buried iron bomb. Such violent action can cause the bomb to detonate.
Re- starting the Clock	A small proportion of German WWII bombs employed clockwork fuzes. It is probable that significant corrosion would have taken place within the fuze mechanism over the last 70+ years that would prevent clockwork mechanisms from functioning. Nevertheless, it was reported that the clockwork fuze in a UXB dealt with by 33 EOD Regiment in Surrey in 2002 did re-start.
Friction Impact	The most likely scenario resulting in the detonation of a UXB is friction impact initiating the shock- sensitive fuze explosive. The combined effects of seasonal changes in temperature and general degradation over time can cause explosive compounds to crystallise and extrude out from the main body of the bomb. It may only require a limited amount of energy to initiate the extruded explosive which could detonate the main charge.



18. Consequences of Initiation/Encounter

18.1. Introduction

The repercussions of the inadvertent detonation of UXO during intrusive ground works, or if an item or ordnance is interfered with or disturbed, are potentially profound, both in terms of human and financial cost. A serious risk to life and limb, damage to plant and total site shutdown during follow-up investigations are potential outcomes. However, if appropriate risk mitigation measures are put in place, the chances of initiating an item of UXO during ground works is comparatively low.

The consequences of encountering UXO can be particularly notable in the case of high-profile sites (such as airports and train stations) where it is necessary to evacuate the public from the surrounding area. A site may be closed for anything from a few hours to a week with potentially significant cost in lost time. It should be noted that even the discovery of suspected or possible item of UXO during intrusive works (if handled solely through the authorities), may also involve significant loss of production.

18.2. Consequences of Detonation

When considering the potential consequences of a detonation, it is necessary to identify the significant receptors that may be affected. The receptors that may potentially be at risk from a UXO detonation on a construction site will vary depending on the site specific conditions but can be summarised as follows:

- People site workers, local residents and general public.
- Plant and equipment construction plant on site.
- Services subsurface gas, electricity, telecommunications.
- Structures not only visible damage to above ground buildings, but potentially damage to foundations and the weakening of support structures.
- Environment introduction of potentially contaminating materials.



20. 1st Line Defence Risk Assessment

20.1. Risk Assessment Stages

Taking into account the quality of the historical evidence, the assessment of the overall risk from unexploded ordnance is based on the following five considerations:

- 1. That the site was contaminated with unexploded ordnance.
- 2. That unexploded ordnance remains on site.
- 3. That such items will be encountered during the proposed works.
- 4. That ordnance may be initiated by the works operations.
- 5. The consequences of encountering or initiating ordnance.

20.2. Assessed Risk Level

1st Line Defence has assessed that there is an overall **Low Risk** from German and anti-aircraft unexploded ordnance at the site of proposed works. There is an assessed **Megligible Risk** from Allied unexploded ordnance.

	Risk Level				
Ordnance Type	Negligible	Low	Medium	High	
German Unexploded HE Bombs		\checkmark			
German 1kg Incendiary Bombs		\checkmark			
Anti-Aircraft Artillery Projectiles		\checkmark			
Allied Land Service and Small Arms Ammunition	\checkmark				

Please note – although the risk from unexploded ordnance on this site has been assessed as 'Low', this does not mean there is 'no' risk of encountering UXO. This report has been undertaken with due diligence, and all reasonable care has been taken to access and analyse relevant historical information. By necessity, when dealing historical evidence, and when making assessments of UXO risk, various assumptions have to be made which we have discussed and justified throughout this report. Our reports take a common-sense and practical approach to the assessment of risk, and we strive to be reasonable and pragmatic in our conclusions.

It should however be stressed that if any suspect items are encountered during the proposed works, 1st Line Defence should be contacted for advice/assistance, and to re-assess the risk where necessary. The mitigation measures outlined in the next section are recommended as a minimum precaution to alert ground personnel to the history of the site, what to look out for, and what measures to take in the event that a suspect item is encountered. It should also be noted that the conclusions of this report are based on the scope of works outlined in the 'Proposed Works' section of this report. Should the scope of works change or additional works be proposed, 1st Line Defence should be contacted to re-evaluate the risk.



21. Proposed Risk Mitigation Methodology

21.1. General

The following risk mitigation measures are recommended to support the proposed works at Oldfield Road:

Recommended Risk Mitigation Measures				
Activity	Recommended Risk Mitigation Measure			
All Works	 UXO Risk Management Plan It is recommended that a site-specific plan for the management of UXO risk be written for this site. This plan should be kept on site and be referred to in the event that a suspect item of UXO is encountered at any stage of the project. It should detail the steps to be taken in the event of such a discovery, considering elements such as communication, raising the alarm, nominated responsible persons etc. Contact 1st Line Defence for help/more information. Site Specific UXO Awareness Briefings to all personnel conducting intrusive works. As a minimum precaution, all personnel working on the site should be briefed on the basic identification of UXO and what to do in the event of encountering a suspect item. This should in the first instance be undertaken by a UXO Specialist. Posters and information on the risk of UXO can be held in the site office for reference. 			

In making this assessment and recommending these risk mitigation measures, if known, the works outlined in the 'Scope of the Proposed Works' section were considered. Should the planned works be modified or additional intrusive engineering works be considered, 1st Line Defence should be consulted to see if a reassessment of the risk or mitigation recommendations is necessary.

1st Line Defence Limited

11/08/23

This Report has been produced in compliance with the Construction Industry Research and Information Association (CIRIA) C681 guidelines for the writing of Detailed UXO Risk Assessments.



Bibliography

- Bates, H. E., Flying Bombs over England, Frogletts Publications Ltd., 1994
- Castle, I., London 1914-17: The Zeppelin Menace, Osprey Publications Ltd., 2008
- Castle, I., London 1917-18: The Bomber Blitz, Osprey Publications Ltd., 2010
- Clarke, N. J., Adolf Hitler's Holiday Snaps: German Aerial Reconnaissance Photography of London and the Home Counties 1939 1943, N. J. Clarke Publications., 1996
- Clarke, N. J., Adolf Hitler's Holiday Snaps: German Aerial Reconnaissance Photography of Southern England 1939 1943, N. J. Clarke Publications., 1995
- Dobinson, C., AA Command: Britain's Anti-Aircraft Defences of the Second World War, Methuen., 2001
- Fegan, T., The 'Baby Killers': German Air raids on Britain in the First World War, Leo Cooper Ltd., 2002
- Fleischer, W., German Air-Dropped Weapons to 1945, Midland Publishing., 2004
- Jappy, M. J., Danger UXB: The Remarkable Story of the Disposal of Unexploded Bombs during the Second World War, Channel 4 Books., 2001
- Morris, J., German Air Raids on Britain: 1914 1918, The Naval & Military Press., 1993
- Price, A., Blitz on Britain, The Bomber Attacks on the United Kingdom 1939 1945, Purnell Book Services Ltd., 1977
- Ramsey, W., The Blitz Then and Now, Volumes 1,2 & 3, Battle of Britain Prints International Ltd., 1987, 1988
 § 1990
- Scofield, J., Modern Military Matters., Council for British Archaeology., 2004
- Stone, K., et al., Unexploded Ordnance (UXO) A Guide For The Construction Industry (C681)., CIRIA, 2009
- Ward, L., The London County Council: Bomb Damage Maps: 1939 1945, Thames and Hudson., 2015
- Whiting, C., Britain Under Fire: The Bombing of Britain's Cities 1940-1945, Pen & Sword Books Ltd., 1999





This report has been prepared by 1st Line Defence Limited with all reasonable care and skill. The report contains historical data and information from third party sources. 1st Line Defence Limited has sought to verify the accuracy and comprehensiveness of this information where possible but cannot be held accountable for any inherent errors. Furthermore, whilst every reasonable effort has been made to locate and access all relevant historical information, 1st Line Defence cannot be held responsible for any changes to risk level or mitigation recommendations resulting from documentation or other information which may come to light at a later date.

This report was written by, is owned by and is copyrighted to 1st Line Defence Limited. It contains important 1st Line Defence information which is disclosed only for the purposes of the client's evaluation and assessment of the project to which the report is about. The contents of this report shall not, in whole or in part be used for any other purpose apart from the assessment and evaluation of the project; be relied upon in any way by the person other than the client, be disclosed to any affiliate of the client's company who is not required to know such information, nor to any third party person, organisation or government, be copied or stored in any retrieval system, be reproduced or transmitted in any form by photocopying or any optical, electronic, mechanical or other means, without prior written consent of the Managing Director, 1st Line Defence Limited, Unit 3, Maple Park, Essex Road, Hoddesdon EN11 0EX. Accordingly, no responsibility or liability is accepted by 1st Line Defence towards any other person in respect of the use of this report or reliance on the information contained within it, except as may be designated by law for any matter outside the scope of this report.


Tel: +44 (0)1992 245 020

Α





1st line defence	Client:	Brownfield Solutions Limited		Approximate site boundary		
Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX	Project:	Project: Oldfield Road, Hampton				N
	Ref:	DA18413-00	Source:	Google Maps		
Email: info@1stlinedefence.co.uk						



Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX	Client: Brownfield Solutions Limited			— Approximate site boundary	
	Project:	Oldfield Road, Hampt	on		N
	Ref:	DA18413-00	Source: Google Earth		
Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020	Produced	d by and Copyright to 1st Line Defen	ce [®] Ltd. Registered in England and Wales with	n CRN: 7717863. VAT No: 128 8833 79. www. ⁻	lstlinedefence.co.uk

В






С


Õ


Tel: +44 (0)1992 245 020






Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX	Client:	Brownfield Solutions	Limited	Approximate site boundary	
	Project: Oldfield Road, Hampton				N
	Ref:	DA18413-00	Source: Landmark Maps		
Email: info@1stlinedefence.co.uk					





1st line defence	Client:	Brownfield Solutions	Limited	Approximate site boundary	
Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020	Project:	Oldfield Road, Hamp	ton		N
	Ref:	DA18413-00	Source: Landmark Maps		
	Produce	d by and Copyright to 1st Line Defer	ice® Ltd. Registered in England and Wales with	h CRN: 7717863. VAT No: 128 8833 79. www.1s	tlinedefence.co.uk



1ST LINE DEFENCE

Client: Brownfield Solutions Limited

Project: Oldfield Road, Hampton

Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020

Ref:

DA18413-00 Source:

ce: Various sources

Produced by and Copyright to 1st Line Defence® Ltd. Registered in England and Wales with CRN: 7717863. VAT No: 128 8833 79.

E

F1

B B C NEWS

Bermondsey bomb: World War Two device safely removed



An unexploded World War Two bomb found in south London has been driven away safely under police and Army escort.

The 500lb (250kg) device was found on a building site in Grange Walk, Bermondsey on Monday

Two primary schools were closed and hundreds of homes were evacuated as a precaution.

A cordon and 656ft (200m) exclusion zone was lifted at about 18:15 GMT as the bomb was removed to a quarry in Kent to be detonated, police said.

The Metropolitan Police force said the device was a 'SA' 250kg WWII German air-dropped bomb, known to the Army's Royal Logistic Corps bomb disposal experts.

250kg German HE Bomb, March 2015

NEWS В

Exeter WW2 bomb is detonated after homes evacuated

More than 2,600 households and 12 university halls of residence were cleared before the 2,200lb (1,000kg) device was destroyed on Saturday.

Police said the blast left a crater about the size of a double-decker bus.

Police have reported large pieces of metal debris hitting buildings and said some properties in the 100m (330ft) exclusion zone had sustained "structural damage



1000kg German HE bomb, February 2021

Ref:

B B C NEWS

WW2 bomb found near London City Airport blown up



An unexploded World War Two bomb found near London City Airport has been detonated.

The 500kg device was discovered at the King George V Dock on Sunday during planned work at the airport.

It was closed and all flights were cancelled on Monday after an exclusion zone was put in place.

The detonation, which took take place off Shoeburyness, Essex, was postponed on Tuesday because of high winds and dangerous conditions for divers.

The 1.5m-long German bomb - which was found in a bed of silt, 15m underwater - was carefully removed from the Thames and placed in a secure location a mile away from the coast of Essex.

500kg German HE Bomb, February 2018



Great Yarmouth: Huge blast after unplanned WW2 bomb detonation

A World War Two bomb found in Great Yarmouth has detonated while work was being done to defuse it, causing a huge blast that was heard for miles.

Army specialists were attempting to disarm it when there was an unplanned detonation at about 17:00 GMT.

People on social media said they heard a loud bang and felt buildings shake 15 miles (24km) away

There have been no reports of injuries among the Army, emergency services or the public, Norfolk Police said.

Cordons were put in place when the bomb was first discovered close to two gas pipes on Tuesday, and work began to make it safe.

250kg German HE Bomb, February 2023

ST LINE DEFENCE

Client: **Brownfield Solutions Limited**

Project: Oldfield Road, Hampton

DA18413-00

Essex Road, Hoddesdon, Hertfordshire. EN11 0EX Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020

Unit 3, Maple Park,

Source: **BBC** News

F2

BASF has confirmed that an explosive device, most likely a World War II-era bomb, caused the blast that left one person injured Tuesday at a plant construction site in Germany.

The explosion was reported at BASF's Ludwigshafen toluene diisocyanate (TDI) plant, which recently broke ground for a 300,000 metric tons per year TDI production plant and other construction to expand its facilities.



BASF Provides Some Details

Responding to a request from *PaintSquare News* for more information on Wednesday (Feb. 27), BASF's manager of media relations and corporate communications Europe, Ursula von Stetten, wrote in an email, "So here [are] the facts: The detonation took place at 10:00 a.m. One person was injured; the injury is not serious. He will be kept in the hospital for some days.

"Cause of the detonation was an explosive device, presumably a bomb deriving from the Second World War. The device detonated when grounding work was done. No details on [a] delay [are] available. At the moment, the exact circumstances of the incident are [being] evaluated."

1st March 2013

SPIEGEL ONLINE

Blast Kills One

World War II Bomb Explodes on German Motorway

A highway construction worker in Germany accidentally struck an unexploded World War II bomb, causing an explosion which killed him and wrecked several passing cars.



A World War II bomb has exploded during construction work on a German highway, killing one worker and injuring several motorists who were driving past, police said.

The worker had been cutting through the road surface near the southwestern town of Aschaffenburg when his machine struck the bomb and triggered it. Police said they weren't sure yet what type of bomb it was. "The explosion seems to have been too small for it to have been an aircraft bomb," a police spokesman said.

23rd October 2006

Brownfield Solutions Limited

WWII bomb injures 17 at Hattingen construction site



Seventeen people were injured on Friday when a construction crew unwittingly detonated a buried World War II-era bomb in Hattingen. An excavator apparently drove over a 250-kilogramme (550 pound) American bomb, damaging surrounding buildings. Most of the injured suffered auditory trauma from the blast, and the excavator operator suffered injuries to his hands, police in the German state of North Rhine-Westphalia said.

"The hole was astoundingly small for such a large bomb full of so many explosives," Armin Gebhard, head of the Arnsberg department for military ordnance removal, told The Local. "But of course it damaged all the surrounding buildings too. We are really happy it wasn't worse."

19th September 2013



World War II bomb kills three in Germany



A special commission is investigating the causes of the explosion, while prosecutors are considering whether the team leader should face charges of manslaughter through culpable negligence, the BBC's Oana Lungescu reports from Berlin.

The blast happened an hour before the defusing operation was due to start.

Officials said the three men who died were experienced sappers, or combat engineers, who over 20 years had defused up to 700 bombs.

More than 7,000 people were immediately evacuated when the 500kg bomb was found Several schools, a kindergarten and local companies remain closed.

2nd June 2010



June 2006

1ST LINE DEFENCE

Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020

Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX

Client:

Source: BBC News

Sunbury 'unexploded World War Two device' found opposite church near Thames

Surrey Police said a member of the public made the discovery with a cordon in place while the incident was dealt with

 NEWS
 By Christy O'Brien
 Senior multimedia reporter

 15:38, 17 MAY 2023
 UPDATED 15:39, 17 MAY 2023

Police were called to the Thames in Surrey after an unexploded World War Two "device" was discovered. <u>Surrey Police</u> said officers were called to a riverside area opposite St Mary's Church, in <u>Sunbury</u>, following the discovery on Wednesday (May 17).

A cordon was put in place and several roads were closed due to the incident with police warning there would be "localised disruption" while they dealt with the incident. Video taken from the scene shows police vehicles at the scene and people in military uniform walking alongside the <u>Thames</u>.

"Officers were called at 12.15pm today (May 17) to the riverside opposite St Mary's Church, <u>Sunbury</u>, after what is suspected to be an unexploded World War Two device was found by a member of the public," a police spokesperson said.

A member of staff at St Mary's said police had made a visit to their vicar to make them aware of the incident, claiming the bomb had been found in the river, although this has not yet been confirmed by the force. They expected the incident would cause disruption in the area with the 216 and 235 buses diverted.

"I've been told it's an unexploded bomb in the river," they said. "There's a 100-metre exclusion zone and the **traffic** has been redirected up different roads. I wouldn't know anything was going on if I hadn't been told. I had a quick look outside on the road and I could see all the cars coming here so it's going to cause a load of traffic up Green Street."



Client: Brownfield Solutions Limited
Project: Oldfield Road, Hampton

Essex Road, Hoddesdon, Hertfordshire. EN11 0EX **Email:** info@1stlinedefence.co.uk **Tel:** +44 (0)1992 245 020

Unit 3, Maple Park,

Ref:


DA18413-00 Source: Surrey Live

Produced by and Copyright to 1st Line Defence[®] Ltd. Registered in England and Wales with CRN: 7717863. VAT No: 128 8833 79.

www.1stlinedefence.co.uk

www.1stlinedefence.co.uk


G





Produced by and Copyright to 1st Line Defence[®] Ltd. Registered in England and Wales with CRN: 7717863. VAT No: 128 8833 79.

Tel: +44 (0)1992 245 020





Produced by and Copyright to 1st Line Defence® Ltd. Registered in England and Wales with CRN: 7717863. VAT No: 128 8833 79.

Dagenham East Ham Ilford

Leyton Waltham Holy Cross Walthamstow

Wanstead and Woodford West Ham

64

65

66 67 68

69 70 71

Finchley Bushey Barnet U.D.

Hendon

Uxbridge Wembley

Horrow Ruislip and Northwood

46 47 48

Poplar Shoreditch Stepney

Bermondsey Deptford

Greenwich

Lewisham Woolwich

18 19

20 21 22


23

Tel: +44 (0)1992 245 020

Surbiton

Wimbledon Banstead


Banstead Beddington and Wallington Carshalton Couldon and Purley Croydon Mitcham Sutton and Cheam



London – Hampton

- A. Water Works
- B. Water Reservoirs
- TN 1612 Designated Luftwaffe targets


The Mosley Water Works outlined above was located approximately 1.4km south-west of the site.



I

Consolidated London Bomb Census Mapping

Night Bombing up to 7th October 1940



Night Bombing - 7th October 1940 to 28th July 1941



Recorded bomb strike

Client: **1st** Line Defence Project: Oldfield Road, Hampton

Tel: +44 (0)1992 245 020

Brownfield Solutions Limited

Unit 3, Maple Park, Essex Road, Hoddesdon, Ref: DA18413-00 Hertfordshire. EN11 0EX Email: info@1stlinedefence.co.uk


Source: The National Archives, Kew

Ν

Approximate site boundary



21st – 27th February 1944




Produced by and Copyright to 1st Line Defence[®] Ltd. Registered in England and Wales with CRN: 7717863. VAT No: 128 8833 79.

Tel: +44 (0)1992 245 020


N

11th November 1040

Κ



Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX Email: info@Istlinedefence.co.uk Tel: +44 (0)1992 245 020	Client:	Brownfield Solutions I	_imited	Approximate site boundary	
	Project:	Oldfield Road, Hampt	on		N
	Ref:	DA18413-00	Source: The National Archives, Kew		
	Produced	d by and Copyright to 1st Line Defen	ce® Ltd. Registered in England and Wales with	a CRN: 7717863. VAT No: 128 8833 79. www.1:	stlinedefence.co.uk



IST LINE DEFENCE Client: Brownfield Solutions Limited — Approximate site boundary Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN110EX Project: Oldfield Road, Hampton Ref: DA18413-00 Source: Richmond Archives

Produced by and Copyright to 1st Line Defence® Ltd. Registered in England and Wales with CRN: 7717863. VAT No: 128 8833 79.

Tel: +44 (0)1992 245 020

L

23th September 1940

St. Mary's Pl. Fields. C 3 13

29th September 1940



<u>15th October 1941</u>



23th February 1944

Oldfield Rd. Gramma Sch. H. Police IB

<u>24th February 1944</u>

ield, Glafield Rd. Hampton GA. 8 V IB

29th November 1944

St. Nary's Pl. Fields. Ta?!! UXB



Client: **Brownfield Solutions Limited** Project: Oldfield Road, Hampton


Essex Road, Hoddesdon, Hertfordshire. EN11 0EX Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020

Unit 3, Maple Park,

Ref:

DA18413-00 Source: Richmond Archives Produced by and Copyright to 1st Line Defence[®] Ltd. Registered in England and Wales with CRN: 7717863. VAT No: 128 8833 79.

Middlesex County Council War Damage Map





Tel: +44 (0)1992 245 020

Category 1 - "Total damage, building to be demolished."

Category 2 - "Some repairs possible, but could become Cat 1."

Category 3 - "Border line areas, uncertain whether repairs possible, might have to be demolished."

1ST LINE DEFENCE	Client:	Brownfield Solutions	Limited	Approximate site boundary	
Unit 3, Maple Park,	Project:	Oldfield Road, Hampt	ton		
Essex Road, Hoddesdon, Hertfordshire. EN11 0EX	Ref:	DA18413-00	Source: London Metropolitan Archives		
Email: info@1stlinedefence.co.uk					

Ν





1st line defence	Client:	Approximate site boundary			
Unit 3, Maple Park,	Project:	Oldfield Road, Hamp	ton		N
Essex Road, Hoddesdon, Hertfordshire. EN11 0EX	Ref:	DA18413-00	Source: National Monuments Record Of	ffice (Historic England)	
Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020	Produced	d by and Copyright to 1st Line Defen	ce [®] Ltd. Registered in England and Wales with	h CRN: 7717863. VAT No: 128 8833 79. www.1	stlinedefence.co.uk





Potential Ground Disturbance



Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX **Email:** info@1stlinedefence.co.uk **Tel:** +44 (0)1992 245 020


E	Client:	Brownfield Solutions	Approximate site boundary	Λ	
L.	Project:	Oldfield Road, Hampt	ton		N
η, Χ	Ref:	DA18413-00	Source:	National Monuments Record Office (Historic England)	

Examples of German Aerial-Delivered Ordnance

i

Bomb Weight	40-54kg (88-119lb)		
Explosive Weight	25kg (55lb)		
Fuze Type	Impact fuze/electro-mechanical time delay fuze	Tail fin	
Bomb Dimensions	1,090 x 280mm (42.9 x 11.0in)	Intermediate ring	
Body Diameter	200mm (7.87in)	Screws Sprengstoff	
Use	Against lightly damageable materials, hangars, railway rolling stock, ammunition depots, light bridges and buildings up to three stories.	Base plat	
Remarks	The smallest and most common conventional German bomb. Nearly 70% of bombs dropped on the UK were 50kg.	Lip sleeve Fuze pocket Boabenkopf	

SC 250kg High	Explosive Bomb
Bomb Weight	245-256kg (540-564lb)
Explosive Weight	125-130kg (276-287lb)
Fuze Type	Electrical impact/mechanical time delay fuze
Bomb Dimensions	1640 x 512mm (64.57 x 20.16in)
Body Diameter	368mm (14.5in)
Use	Against railway installations, embankments, flyovers, underpasses, large buildings and below-ground installations.
Remarks	It could be carried by almost all German bomber aircraft and was used to notable effect by the Junkers Ju-87 Stuka (<i>Sturzkampffluazeug</i> , or dive-bomber).








SC 500kg High	n Explosive Bomb
Bomb Weight	480-520kg (1,058-1,146lb)
Explosive Weight	250-260kg (551-573lb)
Fuze Type	Electrical impact/mechanical time delay fuze
Bomb Dimensions	1957 x 640mm (77 x 25.2in)
Body Diameter	470mm (18.5in)
Use	Against fixed airfield installations, hangars, assembly halls, flyovers, underpasses, high- rise buildings and below-ground installations.
Remarks	40/60 or 50/50 Amatol TNT, Trialene. Bombs recovered with Trialen filling have cylindrical paper-wrapped pellets, 1-15/16in. in length and diameter.

Tel: +44 (0)1992 245 020








1ST LINE DEFENCE	Client:	Brownfield Solutions Limited	Limited	
Unit 3, Maple Park,	Project:	Oldfield Road, Hampt	iton	
Essex Road, Hoddesdon, Hertfordshire. EN11 0EX	Ref:	DA18413-00	Source: Various sources	
Email: info@1stlinedefence.co.uk				

Examples of German Aerial-Delivered Ordnance

ii

SD2 Anti-Personnel 'Butterfly Bomb'


Bomb Weight	Approx. 2kg (4.41lb)
Explosive Weight	Approx. 7.5oz (225 grams) of Amatol surrounded by a layer of bituminous composition.
Fuze Type	41 fuze (time) , 67 fuze (clockwork time delay) or 70 fuze (anti-handling device)
Body Diameter	3in (7.62 cm) diameter, 3.1in (7.874) long
Use	Designed as an anti-personnel/fragmentation weapon. They were delivered by air, being dropped in containers of 23-144 sub- munitions that opened at a predetermined height, thus scattering the bombs.
Remarks	Quite rare. First used against Ipswich in 1940, but were also dropped on Kingston upon Hull, Grimsby and Cleethorpes in June 1943, amongst various other targets in UK. As the bombs fell the outer case flicked open via springs which caused four light metal drogues with a protruding 5 inch steel cable to deploy in the form of a parachute & wind vane, which armed the device as it span.





Parachute Mine (Luftmine B / LMB)

Bomb Weight	Approx. 990kg (2176lb)
Explosive Weight	Approx. 705kg (1,554lb)
Fuze Type	Impact/time delay/hydrostatic pressure fuze
Dimensions	2.64m x 0.64m (3.04m with parachute housing)
Use	Against civilian, military and industrial targets. Used as blast bombs and designed to detonate above ground level to maximise damage to a wider area.
Remarks	Deployed a parachute when dropped in order to control its descent. Had the potential to cause extensive damage within a 100m radius.








SC 1000kg Hig	h Explosive Bomb
Bomb Weight	Approx. 993-1027kg (2,189-2,264lb)
Explosive Weight	Approx. 530-620kg (1168-1367lb)
Fuze Type	Electrical impact/mechanical time delay fuze.
Filling	Mixture of 40% amatol and 60% TNT, but when used as an anti-shipping bomb it was filled with Trialen 105, a mixture of 15% RDX, 70% TNT and 15% aluminium powder.
Bomb Dimensions	2800 x 654mm (110 x 25.8in)
Body Diameter	654mm (18.5in)
Use	SC-type bombs were General Purpose Bombs used primarily for general demolition work. Constructed of parallel walls with comparatively heavy noses, they are usually of three-piece welded construction.

Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020





1st line defence	Client:	Brownfield Solutions	Limited		
Unit 3, Maple Park,	Project:	Oldfield Road, Hamp	ton		
Essex Road, Hoddesdon, Hertfordshire FN11 0FX	Ref:	DA18413-00	Source:	Various sources	

Examples of German Aerial-Delivered Ordnance

iii


1kg Incendiary	Bomb		
Bomb Weight	Approx. 1.0 - 1.3kg (2.2 and 2.9lb)		
Explosive Weight	Approx. 680g (1.5lb) Thermite 8-15gm Explosive Nitropenta		
Fuze Type	Impact fuze		
Bomb Dimensions	350 x 50mm (13.8 x 1.97in)		
Body Diameter	50mm (1.97in)		
Use	As incendiary – dropped in clusters on towns and industrial complexes.	Default Filler	
Remarks	Magnesium alloy case. Sometimes fitted with high explosive charge. The body is a cylindrical alloy casting threaded internally at the nose to receive the fuze holder and fuze.		

C50 A Incend			
Bomb Weight	Approx. 41kg (90.4lb)		
Explosive Weight	Approx. 0.03kg (0.066lb)		
Incendiary Filling	12kg (25.5lb) liquid filling with phosphor igniters in glass phials. Benzine 85%; Phosphorus 4%; Pure Rubber 10%	Boseplate	Tail Unit
Fuze Type	Electrical impact fuze	Incendiary fill Air space Glass ampule of phosphorous	Bottles
Bomb Dimensions	1,100 x 280mm (43.2 x 8in)	Lifting lug	(Phosphorous Filled)
Use	Against any targets where an incendiary effect is required.	Short ianition charae	Suspension lug
Remarks	Early fill was a phosphorous/carbon disulphide incendiary mixture.	Bomb casing	

Flam C-250 Oil Bomb

Tel: +44 (0)1992 245 020

Bomb Weight	480-520kg (1,058-1,146lb)	
Explosive Weight	250-260kg (551-573lb)	
Fuze Type	Electrical impact/mechanical time delay fuze	
Bomb Dimensions	1957 x 640mm (77 x 25.2in)	
Body Diameter	470mm (18.5in)	
Use	Against fixed airfield installations, hangars, assembly halls, flyovers, underpasses, high- rise buildings and below-ground installations.	
Remarks	40/60 or 50/50 Amatol TNT, Trialene. Bombs recovered with Trialen filling have cylindrical paper-wrapped pellets, 1-15/16in. in length and diameter.	





1ST LINE DEFENCE	Client:	Client: Brownfield Solutions Limited			
Unit 3, Maple Park,	Project:	ject: Oldfield Road, Hampton			
Essex Road, Hoddesdon, Hertfordshire. EN11 0EX	Ref:	DA18413-00	Source: Various sources		
Email: info@1stlinedefence.co.uk					

Examples of Anti-Aircraft Projectiles

iv

Projectile Weight	28lb (12.6 kg)	Λ	
Explosive Weight	2.52lbs		
Fuze Type	Mechanical Time Fuze		A Carl British Bar
Dimensions	3.7in x 14.7in (94mm x 360mm)	2	
Rate of Fire	10 to 20 rounds per minute		Berryway, Smoke box, Buce alute
Use	The 3.7in AA Mks 1-3 were the standard Heavy Anti-Aircraft guns of the British Army and were commonly used on the Home Front.		Rezwww. h. b. pildt criptotor Frit disc. N.T. Pase plate.
Ceiling	30,000ft to 59,000ft		Fuze N°Il Gaine Tracing cloth discs. Paper tube Driving bas


40mm Bofors	Projectile			
Projectile Weight	1.96lb (0.86kg)			
Explosive Weight	300g (0.6lb)	AAAA		GLAZEDBOARD WASHER
Fuze Type	Impact Fuze		1	
Rate of Fire	120 rounds per minute			CR RDX/BWX 919 AS APPLICABLE IIE06
Projectile Dimensions	40 x 180mm			TRACING CLOTH DISCS TEXPLORET INT. HAPER TUBE
Ceiling	23,000ft (7000m)	Mar and Alar		TINT OR SI/9 FELT DISC PAPER TUBE POWDER PELLET
Remarks	Light quick fire high explosive anti-aircraft projectile. Each projectile fitted with small tracer element. If no target hit, shell would explode when tracer burnt out. Designed to engage aircraft flying below 2,000ft.			TRACING CLOTH WASHER WASHER COPPER WASHER TRACER & IGNITER SHELL Nº II BAKELISED PAPER DISC

3in Unrotated Projectile (UP) Anti-Aircraft Rocket (`Z" Battery)

HE Projectile Weight	3.4kg (7.6lb)
Explosive Weight	0.96kg (2.13lb)
Filling	High Explosive – TNT. Fitted with aerial burst fuzing
Dimensions of projectile	236 x 83mm (9.29 x 3.25in)
Remarks	As a short range rocket-firing anti-aircraft weapon developed for the Royal Navy. It was used extensively by British ships during the early days of World War II. The UP was also used in ground-based single and 128-round launchers known as Z Batteries. Shell consists of a steel cylinder reduced in diameter at the base and threaded externally to screw into the shell ring of the rocket motor.

Email: info@1stlinedefence.co.uk Tel: +44 (0)1992 245 020






IST LINE DEFENCE Client: Brownfield Solutions Limited Unit 3, Maple Park, Essex Road, Hoddesdon, Hertfordshire. EN11 0EX Oldfield Road, Hampton Ref: DA18413-00 Source: Various sources

1st Line Defence

Unit 3, Maple Park Essex Road, Hoddesdon Hertfordshire EN11 0EX

Call +44 (0) 1992 245 020 Email info@1stlinedefence.co.uk Web www.1stlinedefence.co.uk







APPENDIX E

Exploratory Hole Logs

Phase I & II Geo-Environmental Assessment Report

									Boreho	e No.	
				ROWNFIEL				Borehole Log	BH		2
			0				00.000		Sheet 2 Hole 1		
	ECT NO:	M547					CO-ORD	b :	CF Sca		
roj	ECT NAM	1E: OLDFI	ELD RO.	AD, HAMPTON			LEVEL:		1:5		ocko
LIEN			GARD LI				DATES:	14/08/23 - 15/08/23	CO		AT
ell	Water Strikes	Sample Depth (m)	and In Type	Situ Testing Results	Depth (m)	Level (m OD)	Legend	Stratum Description			
					0.09	-0.09		MADE GROUND: Asphalt.		/	
		0.30	В		0.30	-0.30		MADE GROUND: Brown gravelly sand with low or Sand is fine to coarse. Gravel is subangular to su		0	
		0.50 0.70	ES B					coarse of asphalt, brick, concrete, flint, and sand			
		0.70	В					are subangular to subrounded of brick.			
		1.00	ES					MADE GROUND: Soft greyish brown slightly grav			1.0
		1.10	В		1.20	-1.20		sandy clay. Sand is fine to medium. Gravel is sub subrounded fine to coarse of asphalt, brick, con-			
ļ		1.50	SPT	N=29				sandstone.			!
				(2,3/4,7,8,10)				Light brown gravelly SAND. Sand is fine to mediu			
		2.00						subangular to subrounded fine to coarse of flint	and sandstone.		_
•		2.00 2.00-2.50	ES LB					Becoming brownish from 2.00m bgl.			2.
•											
•		2.50-3.00 2.50	LB SPT	N=15							
		2.50	5P1	(4,5/4,3,4,4)							
											3.
•		2 50 4 00	1.0								
		3.50-4.00 3.50	LB SPT	N=16				Pockets of clay present from 3.50m bgl.			
				(4,5/3,5,4,4)							
											4.
•		4.50	SPT	N=10	4.40	-4.40	××	Soft brownish grey slightly gravelly slightly sand	/ CLAY. Sand is		1
				(2,3/2,3,3,2)			× × ×	fine. Gravel is subangular to subrounded fine to	medium of flint		
		5.00-5.50	1.0					and sandstone.			5.
		5.00-5.50	LB				XX				5.
							××-				
\mathbb{S}							XX-				
							××				
		6.00	В				××	Becoming firm from 6.00m bal			6.
			SPT	N=12 (1,2/3,2,3,4)			××				
				(1)2/0)2/0/ //			× × ×				
Ø							× × ×				
ÿ							X				
X		7.00	В								7.
X							×				
y		7.50-7.95	U				XX-				
S.							XX				
		8.00	В				××				8.
		0.00	, D				××				0.
							×				
							XX				
Ž.		9.00	В				××-	Becoming stiff from 9.00m bgl.			9.
X			SPT	N=25 (3,5/5,6,7,7)			<u>×</u> ×-				
X				(-,-,-,-,-,,			XX				
y							XX				
S.							××				
		10.00	В				···· · · · ·				- 10.
ma	rks			th Radiodetection a	ind GPR met	thods.			vironmental Sample		
				pit to 1.20m bgl. .70m bgl to 2.50m l	าฮไ			B = Bul	urbed Sample Sample		
		4. Slow seepag	ge ground	dwater encountere	d at 12.0m k			20 minutes. U = Uni	ge Bulk Sample disturbed Sample		
								Soffi to 4.50ffi bgi slotted pipe. Bentonite seal SPT = S	ndisturbed Thin Wall Sam tandard Penetration Test		
		between 4.50r	m and 5.5	50m bgl. 5.50m to 2	20.0m bgl ba	ackfilled with	n arisings.	PPM =	notoionization Detector (Part Per Million	ppm)	
				50m bgl. 5.50m to 2				PID = P PPM =	notoionization Detector (

									Boreh	ole No.
			B B F	ROWNFIELD				Borehole Log	BH	101
									Sheet	t 2 of 2
PRO.	IECT NO:	M547	8				CO-ORDS:			туре
										CP cale
PRO.	IECT NAM	VIE: OLDFI	ELD RO	AD, HAMPTON			LEVEL:			:50
CLIEI	NT:	SHUR	GARD LT	ГD			DATES:	14/08/23 - 15/08/23	Logged CO	Checke AT
Vell	Water Strikes			Situ Testing	Depth (m)	Level (m OD)	Legend	Stratum Descriptio	n	
	JUIKES	Depth (m)	Туре	Results	(111)	(111 0 0)	<u>x : : : : : : : : : : : : : : : : : : :</u>			
							×			
		10.50-10.95	U				×			
							×_×_×			
		11.00	В				××	Becoming very stiff from 11.00m bgl.		11.0
							×			
							×_×_×			
							× × ×			
		12.00	В				× × ×			12.
			SPT	N=32 (4,5/7,7,9,9)			× × ×			
							× × ×			
							× × ×			
		13.00	в							13.
			SPT	N=43 (5,7/9,10,12,12)			× × ×			
				(5,775,10,12,12)			~~~×~			
							~~~×~			
		14.00	в							14.0
		14.00	В							14.
							××-			
							×			
							XX-			
		15.00	B SPT	N=45			××-			15.0
			-	(4,8/9,11,12,13)			×			
							× ×			
							××			
		16.00	В				××			16.0
							× · · · · ×			
		16.50	SPT	N=49			× <u>···×</u> ×			
				(6,9/11,12,12,14)			××			
		17.00	в				××			17.0
							× <u>×</u> ××			
							× × ×			
							× × ×			
X		18.00	в				× × ×			18.0
		10.00	SPT	N≥50			× × ×			16.0
				(7,10/11,13,13,13)			××			
							× × ×			
		19.00	B SPT	N≥50			× × ×			19.0
				(7,10/11,13,14,12)			× × ×			
							X			
							× × ×			
		20.00	B	NINEO	20.00	-20.00	<u>X</u>	End of Borehole at 20.00	)m	20.0
			SPT	N≥50 (8,12/12,14,16,8)						
ema	ırks			th Radiodetection an pit to 1.20m bgl.	d GPR met	thods.			ES = Environmental Sample D = Disturbed Sample	
		3. Water adde	d from 1.	70m bgl to 2.50m bg					B = Bulk Sample LB = Large Bulk Sample	
				dwater encountered alled upon completio				D minutes. Dm to 4.50m bgl slotted pipe. Bentonite seal	U = Undisturbed Sample UT = Undisturbed Thin Wall S	
				50m bgl. 5.50m to 20					SPT = Standard Penetration Te PID = Photoionization Detecto	
									PPM = Part Per Million HSV = Hand Shear Vane	

									Boreh	ole No.	
				<b>COWNFIELD</b>				Borehole Log	BH	102	
								C	Sheet		
PRO.	IECT NO:	M5478	3				CO-ORD	S:		<b>Type</b> P	
				AD, HAMPTON			LEVEL:		Sc	ale	
no.				AD, HAMI TON						50 Che	cko
CLIEI	NT:	SHURG	GARD LT	ΓD			DATES:	16/08/23	Logged CO		AT
/ell	Water Strikes			Situ Testing	Depth	Level	Legend	Stratum Description			
	Strikes	Depth (m)	Туре	Results	(m) 0.09	(m OD) -0.09		MADE GROUND: Asphalt			_
		0.30	ES		0.26	-0.26 -0.70		MADE GROUND: Brown gravelly sand. Sand is fin Gravel is subangular to subrounded fine to coars brick, concrete, flint, and sandstone.	e of asphalt,		
X		1.00	ES				××	MADE GROUND: Soft yellowish brown slightly sa gravelly silty clay. Sand is fine to coarse. Gravel is	subangular to		1.0
					1.20	-1.20	××_	subrounded fine to coarse of asphalt, brick, conc sandstone.	rete, flint, and	ł	
								Firm yellowish brown slightly sandy slightly grave Sand is fine to medium. Gravel is subangular to s			
								to coarse of flint, and sandstone.		le	
								End of Borehole at 1.20m			2.
											3
											4
											5.
											6.
											7.
											8.
											9.
											10.
m	ırks	1. Location scanne	d with Radi	iodetection and GPR me	thods.			FC - Fm.	ironmental Sample		
ema	II KS	<ol> <li>Hand dug inspection</li> <li>Location termination</li> </ol>	ction pit to ated at 1.20			nderground ser	vices.	D = Dist B = Bulk LB = Lar U = Und UT = Un SPT = St PID = PH PPM = P	urbed Sample	st	

									Boreho	ie No.
				OWNFIELD				Borehole Log	BH	03
									Sheet	
ROJ	ECT NO:	M5478	3				CO-ORD	5:	Hole Cl	
ROJ	ECT NAN	<b>//E:</b> OLDFII	ELD RO	AD, HAMPTON			LEVEL:		Sca	le
LIEN	IT.		GARD LT				DATES:	15/08/23 - 16/08/23	1:5 Logged	0 Chec
	Water			Situ Testing	Depth	Level	DAILS.	15/08/25 - 10/08/25	CO	AT
ell	Strikes	Depth (m)		Results	(m)	(m OD)	Legend	Stratum Description		
		0.20			0.19	-0.19		MADE GROUND: Concrete MADE GROUND: Brown gravelly sand. Sand is fi	ne to coarse	
		0.30 0.40	B ES		0.30	-0.30		Gravel is subangular to subrounded fine to coar		
		0.50 0.70	B ES		0.60	-0.60		concrete, flint, and sandstone.		
			LB				<u>××</u> ×	MADE GROUND: Soft yellowish brown slightly s		
		1.00-1.50	LB		1.00	-1.00		gravelly silty clay. Sand is fine to coarse. Gravel i subrounded fine to coarse of brick, concrete, fli		
								sandstone.	int, and	
		1.50	ES					Soft yellowish brown slightly sandy slightly grav	elly silty CLAY.	
÷		1.50-2.00 1.50	LB SPT	N=45				Sand is fine to coarse. Gravel is subangular to su	brounded fine	:0
•		1.50	511	(5,7/9,11,12,13)				coarse of flint, and sandstone.		
								Yellowish brown gravelly SAND. Sand is fine to c subangular to subrounded fine to coarse of flint		
		2.50-3.00	LB							
		2.50	SPT	N=16 (5,4/5,6,3,2)						
		3.00-3.50	LB	(3) 1/ 3/3/3/2/	3.00	-3.00				
		3.00-3.50	LB		3.00	-3.00	XX_	Soft brownish grey slightly gravelly slightly sand		
							XX	fine. Gravel is subangular to subrounded fine to	medium of flint	:
		3.50	SPT	N=3			<u>××</u>	and sandstone.		
				(1,0/1,0,1,1)						
		4.00	В				$\sim$ $\sim$ $\sim$			
$\langle\!\langle$		4.00	5							
Ø							×			
		4.50-5.00	LB				× <u>×</u> ×			
Ø							××			
ÿ										
y							$\sim$ $\sim$ $\sim$			
y							X			
X							×			
							××_			
		6.00	в				<u>××</u>	Decoming from from 6 00m had		
Ø			SPT	N=17				Becoming firm from 6.00m bgl.		
ÿ				(2,3/3,4,5,5)						
X										
y							×			
X		7.00	В				××	Becoming stiff from 7.00m bgl.		
							<u>××</u>			
Ø		7.50	CDT	N. 40			××			
Ø		7.50	SPT	N=19 (3,3/4,4,5,6)			× × ×			
ý							×			
y		8.00	В				×			
y							X X			
Ś							××			
$\langle\!\langle$							× · · · ×			
							× × · ×			
		9.00 9.00-9.45	B U				× × ×	becoming very stiff from 9.00m bgl.		
Ø		5.00-5.45	U							
ÿ		9.50	В				X-X-X-			
ÿ							××			
X		10.00	В							1
		a. 1						I		
ma	rks			h Radiodetection ai pit to 1.20m bgl.	nd GPR me	thods.		D = Dis	ivironmental Sample	
		3. Water adde	d from 1.	50m bgl to 2.50m b				LB = La	lk Sample Irge Bulk Sample	
			-	water encountered		• •		r 20 minutes. U = Un	disturbed Sample ndisturbed Thin Wall Sar	nple
								SPT = S	Standard Penetration Tes	
		Detween ≺ uur	n an <i>d /יי</i> יי	0m bgl. 4.00m to 2	5 Um nor n		n arisinge		hotoionization Detector	(nnm)

								<b>.</b> -	Dorent	ole No.
			BR SO	OWNFIELD			E	Borehole Log	BH	03
										2 of 3
ROJ	ECT NO:	M5478	3				CO-ORDS:		Hole	Туре
										ale
PROJ	ECT NAM	IE: OLDFII	ELD ROA	AD, HAMPTON			LEVEL:		1:	50
LIEN	IT:	SHURG	GARD LT	D			DATES:	15/08/23 - 16/08/23	Logged CO	Check AT
/ell	Water			Situ Testing	Depth	Level	Legend	Stratum Descript	ion	
	Strikes	Depth (m)	Туре	Results	(m)	(m OD)	**************************************			
							×××××			
		10.50	SPT	N=25			× ×			
				(4,5/5,6,7,7)			×			
		11.00	В				×			1
		12.00	в							1
		12.00	SPT	N=33			×— ×			
				(5,5/7,8,8,10)			X-X-X-			
							× × ×			
							××			
		13.00	В				× · · · ×			1
							× ····×			
		13.50	SPT	N=31 (5,5/6,7,8,10)			××-			
×.				(5,5/6,7,8,10)			× × ×			
ÿ		14.00	В				××-			1
ÿ							× × ×			
X							× × ×			
X							× × ×			
))		15.00	В				×			1
X		15.00	SPT	N=34			→ → ^ ★ → →			1
X				(4,5/5,7,9,13)						
X							× ×			
X										
X		16.00	В							1
×.							×			
		16.50	SPT	N=47 (5,7/10,11,12,14)			X			
				(3,7,10,11,12,14)			XX-			
		17.00	В				X X			-
Ś							× ×			
s an							× ×			
s an							× × ×			
Ŵ		18.00	в				× × ×			1
Ś			SPT	N=41 (5,5/7,10,12,12)			× × ×			
s				(0,0,7,10,12,12)			××			
Ŵ							× × ×			
		10.00	2				× × ×			
		19.00	В				××			1
							× × ×			
		19.50	SPT	N=48 (6,7/10,12,13,13)			× × ×			
							× × ×			
¥12		20.00	В							2
mai	rks	1. Location sca	nned wit	h Radiodetection ar	d GPR met	thods.			ES = Environmental Sample	
		2. Hand dug in	spection	pit to 1.20m bgl.					D = Disturbed Sample B = Bulk Sample	
		4. Slow seepag	e ground		at 11.70m		o 11.40m after 20 m		LB = Large Bulk Sample U = Undisturbed Sample	
		5. Monitoring	well insta	lled upon completic	n. 0.00m t	o 1.00m bgl	plain pipe. 1.00m to	o 3.00m bgl slotted pipe. Bentonite seal	UT = Undisturbed Thin Wall Sa SPT = Standard Penetration Te	st
		petween 3.00r	n and 4.0	0m bgl. 4.00m to 2	o.um bgi ba	ackniled with	n arisings		PID = Photoionization Detecto PPM = Part Per Million	r (ppm)

								Boreho	ole No.
		B R SO	OWNFIELD				Borehole Log	BH	03
							-	Sheet	
PROJECT NO	<b>D:</b> M547	'8				CO-ORDS:		Hole	
PROJECT N	ME: OLDF	IELD RO	AD, HAMPTON			LEVEL:		<b>Sca</b>	ale
CLIENT:	сын	GARD LT				DATES:	15/08/23 - 16/08/23	Logged	Checke
				Donth	Loval	DAILS.	13/00/23 10/00/23	CO	AT
Well Wate Strike	-	_	Situ Testing Results N=49 (6,6/9,12,14,14) N=45 (6,7/8,10,13,14) N≥50 (6,8/11,14,14,11) N≥50 (8,12/12,15,14,9)	Depth (m)	Level (m OD)		End of Borehole at 25.0		21.0 22.0 23.0 24.0 25.0 26.0 25.0 25.0 28.0 29.0
temarks	<ol> <li>Hand dug i</li> <li>Water added</li> <li>Slow seepa</li> <li>Monitoring</li> </ol>	nspection ed from 1. ge ground ; well insta	h Radiodetection ar pit to 1.20m bgl. 50m bgl to 2.50m b lwater encountered illed upon completic 00m bgl. 4.00m to 2:	gl. at 11.70m on. 0.00m t	bgl, rising to to 1.00m bgl	plain pipe. 1.00n	minutes. n to 3.00m bgl slotted pipe. Bentonite seal	ES = Environmental Sample D = Disturbed Sample B = Bulk Sample U = Undisturbed Sample U = Undisturbed Sample U = Undisturbed Thin Wall Sa SPT = Standard Penetration Tes PID = Photoionization Detector PPM = Part Per Million HSV = Hand Shear Vane	t

									Window Sa	mpler No.
				OWNFIELI				Borehole Log	WS	01
									Sheet	
PRO.	ECT NO:	M547	'8				CO-ORD	S:	Hole W	
PRO.		ME: OLDF	IELD ROA	AD, HAMPTON			LEVEL:		Sca	
CLIEI	NT:		gard Lt				DATES:	15/08/23	1:3 Logged CO	Checko AT
Vell	Water Strikes		1	Situ Testing	Depth	Level (m OD)	Legend	Stratum Description		
	JUIKES	Depth (m)	Туре	Results	(m)	(1100)		MADE GROUND: Concrete with rebar.		
		0.50	ES		0.19	-0.19 -0.40		MADE GROUND: Brown gravelly sand with low Sand is fine to coarse. Gravel is subangular to su coarse of brick, concrete, flint, and sandstone. G subangular of brick. MADE GROUND: Soft dark grey slightly gravelly clay. Sand is fine to coarse. Gravel is subangular fine to coarse of brick, concrete, flint, and sand	ubrounded fine t Cobbles are slightly sandy to subrounded	to
		1.10 1.20	ES SPT	N=19 (1,1/4,5,3,7)	1.20	-1.20		Becoming yellowish brown from 0.60m bgl to 1.20m bgl. Brown gravelly SAND. Sand is fine to coarse. Grato subrounded fine to coarse of flint and sandst		ar 1
		2.00	ES SPT	N=24 (5,7/6,6,6,6)						2.
		3.00	SPT	N=12 (4,5/4,3,3,2)						3
		4.00	ES SPT	N=23 (3,3/4,6,6,7)	3.70	-3.70	A TA	Firm dark grey slightly sandy slightly gravelly sil fine. Gravel is subangular to subrounded fine to and sandstone.		t 4
		5.00	SPT	N=30 (6,7/7,7,8,8)	5.00	-5.00		End of Borehole at 5.00m		5
										6
lema	ırks	<ol> <li>Hand dug</li> <li>Wet sand</li> <li>borehole</li> </ol>	inspectio encounte collapsed	vith Radiodetecti n pit to 1.20m b ered from 2.00m from 5.00m to 2 talled upon com	gl bgl to 3.00 2.80m bgl.	)m bgl.		D = Di B = Bu LB = L U = U UT = L PiDe PiDe PM =	nvironmental Sample sturbed Sample klk Sample arge Bulk Sample ndisturbed Sample Indisturbed Thin Wall Sar Standard Penetration Tes Photoionization Detector Part Per Million Hand Shear Vane	t

			BR		D			Parahalalaa	Window S		
				LUTIONS LT				Borehole Log		<b>SO2</b>	
										t 1 of 1 • <b>Type</b>	
PRO.	ECT NO:	M5478	3				CO-ORD	S:	V	VS	
PRO.	ECT NAM	1E: OLDFII	ELD RO	AD, HAMPTON			LEVEL:			ale: 30	
CLIEI	<u>лт.</u>	SULIDA	GARD LT				DATES:	15/08/23	Logged	Che	ecke
LIEI							DATES.	13/06/23	CO		AT
/ell	Water Strikes	Sample Depth (m)	and in Type	Situ Testing Results	Depth (m)	Level (m OD)	Legend	Stratum Description			
			- 77 -		0.09	-0.09		MADE GROUND: Asphalt MADE GROUND: Dark brown gravelly sand. Sa coarse. Gravel is subangular to subrounded fir asphalt, brick, concrete, and sandstone.			-
								End of Borehole at 0.40m			2.0
											4.(
											5.
ema	-			vith Radiodetecti		R methods.		D =	Environmental Sample Disturbed Sample		6.
		<ol> <li>Hand dug i</li> <li>No ground</li> <li>Location te</li> <li>Location back</li> </ol>	nspectic water er erminate ackfilled	on pit to 0.40m b	gl. ue to conc n completio	rete obstru		D = B = LB = U = UT SPT PID PPM		est	

				OWNELET	D						No.
				OWNFIEL				Borehole Log	W	503	
										1 of 1 <b>Type</b>	
PROJ	ECT NO:	M5478	3				CO-ORD	S:		VS	
PROJ			ELD ROA	D, HAMPTON			LEVEL:			<b>ale</b> 30	
CLIE	<u>лт.</u>	SULIDA	GARD LT	D			DATES:	15/08/23	Logged	Che	cke
CLILI					<b>a</b>		DAILS.	15/06/25	CO	A	AT
Vell	Water Strikes	Depth (m)	Type	Situ Testing Results	Depth (m)	Level (m OD)	Legend	Stratum Description			
					0.09	-0.09		MADE GROUND: Asphalt MADE GROUND: Brown gravelly sand. Sand is	fina to coorco		
X		0.20	ES		0.27	-0.27		Gravel is subangular to subrounded fine to co			
X								brick, concrete, flint, and sandstone. MADE GROUND: Soft yellowish brown slightly	aroually clightly	/	
X								sandy clay. Sand is fine to medium. Gravel is s			
X		0.70	ES					subrounded fine to coarse of asphalt, concret			
					0.80	-0.80		sandstone. Soft yellowish brown slightly gravelly slightly s	andv CLAY. Sand	is	
X							X-X-X-	fine to coarse. Gravel is subangular to subrou			1
///¥					1.10	-1.10	<u>×.:</u>	of flint, and sandstone. End of Borehole at 1.10m			
											2
											3
											4
											-
											5
											6
											e
ma	rks	1. Location sc	anned w	ith Radiodetecti	on and GPI	R methods		FC	Environmental Sample		
d		2. Hand dug i	nspectio	n pit to 1.10m b		. memous.		D = B =	Disturbed Sample Bulk Sample		
		3. No ground		countered. d at 1.10m bgl c	lua to con-	rato obstru	ction	LB : U =	Large Bulk Sample Undisturbed Sample		
				d at 1.10m bgi c with arisings upo			cuon.	UT SPT	= Undisturbed Thin Wall S = Standard Penetration Te	st	
		6. Asphalt sur		0 1					= Photoionization Detecto		

				OWNFIEL				Borehole Log	Window S		
					-			•	Sheet		
PRO.	IECT NO:	M5478	3				CO-ORD	S:		Type VS	
PRO.		ME: OLDFII	ELD ROA	AD, HAMPTON			LEVEL:			<b>ale</b> 30	
CLIE	NT:	SHURG	GARD LT	D			DATES:	15/08/23	Logged	Che	cke
Vell	Water Strikes			Situ Testing	Depth (m)	Level (m OD)	Legend	Stratum Description			
		Depth (m)	Type	Results	1.10	-0.09 -0.30 -1.10		MADE GROUND: Asphalt MADE GROUND: Brown gravelly sand. Sand is fi Gravel is subangular to subrounded fine to coar brick, concrete, flint, and sandstone. Becoming yellowish brown from 0.14m byt to 0.30m byt. MADE GROUND: Soft dark brown slightly gravel clay. Sand is fine to medium. Gravel is subangul fine to coarse of asphalt, brick, concrete, flint, a End of Borehole at 1.10m	se of asphalt, ly slightly sand ar to rounded	у	1.0 2.0 3.0 4.0
lema	ırks	<ol> <li>Hand dug i</li> <li>No ground</li> <li>Location te</li> <li>Locations b</li> </ol>	nspectio water en erminateo oackfilled	vith Radiodetecti in pit to 1.10m by iccountered. d at 1.10m bgl d d with arisings co epaired with cold	gl. ue to conc mpletion.			D = Dit B = Bui LB = Lz U = Uh UT = U SPT = PID F PPM =	wironmental Sample turbed Sample k Sample disturbed Sample ndisturbed Sample ndisturbed Thin Wall Si tandard Penetration Te hotoionization Detecto Part Per Million Hand Shear Vane	st	6.0

											No.
			BR	OWNFIEL	D D			Borehole Log	WS	03B	3
					-					t 1 of 1	
PROJ	ECT NO:	M5478	3				CO-ORD	S:		<b>Type</b> VS	
PROJ	ECT NAM	1E: OLDFI	ELD ROAI	D, HAMPTON			LEVEL:		Sc	ale	
								15/00/00	Logged	:30 Che	cked
CLIEN			SARD LTD				DATES:	15/08/23	CO		AT
Nell	Water Strikes	Sample Depth (m)	and In S Type	itu Testing Results	Depth (m)	Level (m OD)	Legend	Stratum Description	l		
					0.10	-0.10		MADE GROUND: Asphalt MADE GROUND: Brown gravelly sand. Sand	is fine to coarse.		-
X////X		0.25	ES		0.25	-0.25	~~~~~~~~~~	Gravel is subangular to subrounded fine to c brick, concrete, and sandstone.			
								End of Borehole at 0.25m	l	/	
											1.0
											2.0
											3.0
											4.(
											5.0
											6.0
ema		<ol> <li>Hand dug in:</li> <li>No groundw</li> <li>Location term</li> </ol>	spection pi ater encou minated at	Radiodetection a it to 0.25m bgl. untered. : 0.25m bgl due to h arisings upon co	o concrete o				S = Environmental Sample D = Disturbed Sample = Bulk Sample B = Large Bulk Sample J = Undisturbed Sample JT = Undisturbed Thin Wall S		
		6. Tarmac repa			,			P	PT = Standard Penetration Te ID = Photoionization Detecto PM = Part Per Million		

									Window S	ampler No.
				ROWNFIELD				<b>Borehole Log</b>	WS	504
			_		-			•	Sheet	1 of 1
PRO	JECT NO:	M547	8				CO-ORD	S:		Туре
<u> </u>										VS ale
PRO	JECT NAM	ME: OLDFI	ELD RO	AD, HAMPTON			LEVEL:			30
CLIE	NT:	SHUR	GARD L	ГD			DATES:	15/08/23	Logged co	Checked
Well	Water Strikes			Situ Testing	Depth (m)		Legend	Stratum Description	n	
	Strikes	Depth (m)           0.40           0.70           1.20           1.70           2.00		N=24 (2,2/2,7,7,8) N≥50 (5,6/11,13,15,14)	2.00	-0.09 -0.26 -1.30 -2.00	Legend	Stratum Description MADE GROUND: Asphalt MADE GROUND: Brown gravelly sand. Sanc Gravel is subangular to subrounded fine to brick, concrete, flint, and sandstone. MADE GROUND: Soft dark brown slightly gi clay with rare rootlet. Sand is fine to coarse to subrounded fine to medium of asphalt, of sandstone. Becoming firm from 0.80m bgl to 1.30m bgl. Becoming firm from 0.80m bgl to 1.30m bgl. Light brown gravelly SAND. Sand is fine to coarse of subangular to subrounded fine to coarse of End of Borehole at 2.000	l is fine to coarse. medium of asphalt, ravelly slightly sand e. Gravel is subangui concrete, flint, and coarse. Gravel is flint and sandstone	y lar 1.0
Rema	arks	<ol> <li>Hand dug i</li> <li>No ground</li> <li>SPT refusa</li> <li>Monitoring</li> </ol>	inspectio water e l at 2.00 g well in	m bgl, location fol	l lowed on pletion. 0.0	by dynamic	c probing (se	ee log WS04A). pipe. 0.50m to 1.00m bgl slotted pipe.	ES = Environmental Sample D = Disturbed Sample B = Bulk Sample U = Undisturbed Sample U = Undisturbed Sample U = Undisturbed Sample U = Undisturbed Thin Wall Sa SPT = Standar Penetration Te PID = Photoionization Detecto PPM = Part Per Million HSV = Hand Shear Vane	st