# whitby wood

Hampton Wick Royal Cricket Ground Temporary Facilities

# Flood Risk Assessment

Client: Hampton Wick Royal Cricket

Club

Date: 18/03/2024

P451640-WW-XX-XX-RP-C-0001

# whitby wood

91-94 LOWER MARSH LONDON SE1 7AB UNITED KINGDOM

+44 (0)20 7442 2216

www.whitbywood.com

Whitby Wood Limited reg in England and Wales reg no 07786822

> Pound House 62A Highgate Street London N6 5HX



#### **REVISION RECORD**

Rev	Date	Description	Prepared	Reviewed	Approved
P1	15/03/2024	Stage Issue	AR	RS	RW
P2	18/03/2024	Stage Issue	AR	RS	RW

This report is to be regarded as confidential to our client and is intended for their use only. Any liability to any third party in respect of the whole or any part of its contents is hereby expressly excluded. Before reproduction of its content, circulation or use by any third-party, our written approval and disclosure must be obtained.

Prepared by:	Reviewed by:	Approved by:				
Dayers.	R/Saunders	R.Willa.				
Aaron Rogers	Ryan Saunders	Ryan Williams	_			
Design Engineer – Civils	Senior Engineer - Civils	Associate - Civils				



### **TABLE OF CONTENTS**

1	INTRO	DUCTION	1
	1.1	Sources of Information	1
	1.2	Environment Agency Data	1
2	THE S	ITE	2
	2.1	Site Location	2
	2.2	Watercourses	2
	2.3	Geology	2
	2.4	Proposed Development	3
3	FLOOI	D RISK	4
	3.1	Fluvial (Rivers and Seas)	4
	3.2	Pluvial (Rainfall)	5
	3.3	Groundwater	6
	3.4	Sewer Flooding	6
	3.5	Artificial Sources	7
	3.6	Summary	8
4	MANA	GING FLOOD RISK	9
	4.1	Master Planning	9
	4.2	Safe Access and Egress	9
	4.3	Mitigating Measures	9
5	CONC	LUSIONS AND RECOMMENDATIONS10	0
Al	PPENDI	CIES	
AF	PENDIX	A – SITE LOCATION	
AF	PENDIX	B - BRITISH GEOLOGY SOCIETY	
AF	PENDIX	C -LB OF RICHMOND MAPS	
AF	PENDIX	D - FLOOD MAPS	
Τ,	ABLES		
17	ADLES		
TA	BLE 1 Th	HAMES WATER SEWER FLOODING	7
TA	BLE 2 - F	FLOOD RISK SUMMARY	8
_	GURES		
П	GURES		
FI	GURE 1 -	SITE LOCATION PLAN	2
FI	GURE 2 I	PROPOSED TEMPORARY FACILITIES	3
FI	GURE 3 -	- FLOOD ZONE MAP	4

#### P451640-WW-XX-XX-RP-C-0001



FIGURE 4 - RISK OF SURFACE WATER FLOODING EXTENT MAP	. 5
FIGURE 5 SUSCEPTIBILITY TO GROUNDWATER FLOODING MAP FROM LB OF RICHMOND SWMP	6
FIGURE 6 SEWER FLOODING FROM LB OF RICHMOND SWMP	7
FIGURE 7 - FLOOD RISK FROM RESERVOIRS MAP	. 8



#### 1 INTRODUCTION

This Flood Risk Assessment (FRA) has been prepared in accordance with National Planning Policy Framework (NPPF) in support of the detailed planning and listed building consent application being submitted by Hampton Wick Royal Cricket Club ('the Applicant'). The application will be submitted to London Borough (LB) of Richmond ('the Council') for the temporary installation of Club room and changing facilities at Hampton Wick Royal Cricket Ground, Surrey, KT1 4AZ ('the site'). This assessment has been undertaken to ascertain the constraints in order to redevelop the site, and to assess the impact of the proposals with respect to flood risk.

#### 1.1 Sources of Information

A review of the relevant information from a range of sources has been undertaken and includes the following:

- London Regional Flood Risk Appraisal (Greater London Authority, 2018)
- Level 1 Strategic Flood Risk Assessment (London Borough of Richmond, 2021)
- Surface Water Management Plan (London Borough of Richmond, 2021)
- British National Geology Viewer [Accessed March 2024];
- ➤ Soilscapes Viewer [Accessed March 2024]
- > London Borough of Richmond Local Plan (London Borough of Richmond, 2018) and;
- National Planning Policy Framework (2023);

#### 1.2 Environment Agency Data

The following information has been gathered from DEFRA's Spatial Data Catalogue of data.gov.uk [accessed March 2024]. As the site is situated within Flood Zone 2, no further data has been requested from the Environment Agency (EA).

- Flood Map for Planning (Rivers and Sea) Flood Zone 2;
- Flood Map for Planning (Rivers and Sea) Flood Zone 3;
- Risk of Flooding from Reservoirs Maximum Flood Extent;
- Risk of Flooding from Surface Water Extent (1%, 3.3% and 0.1% AEP);
- Statutory Main River Map; and
- Preliminary Flood Risk Assessment for England, October 2018.



#### 2 THE SITE

#### 2.1 Site Location

The site sits within the Hampton Wick Royal Cricket Ground on Bushey Park, Surrey. The site currently comprises of a pavilion, which has been destroyed, and a storage shed. The approximate centre of the site is located at an easting and northing of 517127 and 169451.

A site location plan has been included in Figure 1 which can also be found in Appendix A.



FIGURE 1 - SITE LOCATION PLAN

#### 2.2 Watercourses

The closest watercourse is an ordinary watercourse between Heron and Leg of Mutton Ponds drainage ditch, which is located approximately 350m to the north of the site. There is another ordinary watercourse approximately 500m to the east of the site. The River Thames is 550m east of the site.

#### 2.3 Geology

The British Geological Survey's Geology of Britain map has been reviewed as shown in **Appendix B** and it indicates a bedrock geology of Lambeth Group (Clay, Silt and Sand), overlain with Kempton Park Gravel Member (Sand and gravel). The site belongs to soilscape 6 – freely draining slightly acid loamy soils.



#### 2.4 Proposed Development

The proposed development will include the installation of four free-standing cabins to provide temporary kitchen and changing facilities. A marquee is proposed to act as the temporary club room.

The club is used for cricket during the summer and rugby during the winter. The four portacabins will be there and used all year round. The likelihood is that the marquee will be only used in the summer, but this is yet to be agreed.

The temporary facilities are expected to be in place for approximately a year, until work is completed on a new pavilion. These structures are all to be located in the northeastern corner of the site. See Figure 2.




FIGURE 2 PROPOSED TEMPORARY FACILITIES



#### 3 FLOOD RISK

#### 3.1 Fluvial (Rivers and Seas)

The Environment Agency's (EA) Flood Risk Data shows the majority of the site is situated within Flood Zone 1 as demonstrated in Figure 3, where Flood Zone 1 is shown by the absence of a raster. The site is therefore at very low risk of fluvial flooding. There is however a small part of the eastern boundary and southeastern corner which lies within Flood Zone 2 where the risk of flooding is slightly greater. The definition of each flood zone can be found below.

- > Land in Flood Zone 1 has a 0.1% or less annual probability of river or sea flooding;
- Land in Flood Zone 2 has between 0.1% and 1% annual probability of river flooding and between 0.1% and 0.5% annual probability of sea flooding; and
- Land in **Flood Zone 3** has a 1% or greater annual probability of river flooding and a 0.5% annual probability of sea flooding.



FIGURE 3 - FLOOD ZONE MAP



#### 3.2 Pluvial (Rainfall)

The definitions for each surface water flood risk category have been detailed below:

- > Very low risk means that each year this area has a chance of flooding of less than 0.1%.
- > Low risk means that each year this area has a chance of flooding of between 0.1% and 1%.
- Medium risk means that each year this area has a chance of flooding of between 1% and 3.3%. Flooding from surface water is difficult to predict as rainfall location and volume are difficult to forecast. In addition, local features can greatly affect the chance and severity of flooding.
- High risk means that each year this area has a chance of flooding of greater than 3.3%.

The risk of surface water flooding has been assessed by viewing the Risk of Flooding from Surface Water (RoFSW) maps, which have been replicated in Figure 4. This shows for the majority of the site the risk is 'very low'. The LB of Richmond Surface Water Management Plan (SWMP) recognises that the site does not lie within a Critical Drainage Area (CDA) and there have been no historic flooding events at this location. Refer to **Appendix C.** 

It should be noted that, flooding from surface water is difficult to predict as rainfall location and volume are not easy to forecast. In addition to this, local features can greatly affect the chance and severity of flooding. It is therefore important to consider exceedance routes and overland flow paths of surface water.



FIGURE 4 - RISK OF SURFACE WATER FLOODING EXTENT MAP



#### 3.3 Groundwater

The LB of Richmond SWMP includes a broad scale assessment of the susceptibility of groundwater flooding across the borough. Figure 5 is taken from the flood maps and illustrates that the site is within an area that has a high (50-75%) potential for groundwater flooding to occur at the surface. The western boundary of the site is in the very high (>75%) zone.

Existing Borehole record for the well TQ16NE70 adjacent to Hampton Wick Pond show the groundwater level at 2.80m below ground level. The well is approximately 225m south of the Site. Borehole TQ17SE186 is located 500m north of site and was dry down to 5.95m. TQ16NE113 is located 450m east of site and was also dry down to 6.4m (21 feet). Refer to **Appendix B**. There have been no historic reports of groundwater flooding.

It is envisaged that the temporary cabins will be installed above ground and that the entry thresholds will be raised to prevent water ingress. Subterranean basements are not being proposed for this scheme.




FIGURE 5 SUSCEPTIBILITY TO GROUNDWATER FLOODING MAP FROM LB OF RICHMOND SWMP

#### 3.4 Sewer Flooding

According to the LB of Richmond SWMP, there has been <5 reported incidence of flooding reported by Thames Water as shown in Figure 6 sewer flooding. A closer look into the data provided in the SWMP shows that there were 4 flood incidents in the KT1 4 postcode. The risk of sewer flooding of the site is therefore assessed as low. It has been assumed that all foul discharge will be either self-contained within the temporary units or connected to the existing septic tank on site.



TABLE 1 THAMES WATER SEWER FLOODING

Dootoodo	in	ternal Floodir	ng	E	Total		
Postcode	2in10year	1in10year	1in20year	2in10year	1in10year	1in20year	Total
KT1 4	0	0	2	0	2	0	4




FIGURE 6 SEWER FLOODING FROM LB OF RICHMOND SWMP

#### 3.5 Artificial Sources

Figure 7 indicates that there is a low risk of reservoir flooding to the site during a Dry Day event. However, the site would be inundated if there was also fluvial flooding. This risk is extremely low, and mitigation will not need to be considered given the nature of the development.




FIGURE 7 - FLOOD RISK FROM RESERVOIRS MAP

#### 3.6 Summary

The table below provides a summary of the 5 sources of flood risk. The site is deemed to have an overall flood risk of low from fluvial and pluvial sources. While the site is in an area of high susceptibility to groundwater flooding, historic borehole records suggest the water table is at least 2.8m below ground and there have been no historic records of flooding. The risk has been assessed as Medium, which should be considered during the installation of the temporary facilities. Artificial and Sewer flood risk is characterised as low for this site. All data maps, and flood maps can be located in **Appendix C** and **Appendix D** respectfully.

Flood Type

Low

Medium

High

Fluvial

V

Pluvial

Groundwater

Sewer

Artificial

V

Risk

Medium

High

High

TABLE 2 - FLOOD RISK SUMMARY



#### 4 MANAGING FLOOD RISK

#### 4.1 Master Planning

The temporary facilities have been located outside of the extents of Flood Zone 2 to minimise the potential risk of flood. It is recommended that during the progression of the masterplan, the proposed development is continued to be designed with flood risk and drainage implications in mind. Proposed ground levels will need to consider potential exceedance flow pathways from onsite drainage. Any displaced surface water flooding should be mitigated against to avoid increasing flooding elsewhere.

#### 4.2 Safe Access and Egress

As most of the site sits within Flood Zone 1, it is considered that there will always be safe access and egress provided and no site-specific flood evacuation plan is required. It should be noted that, while the car park area and main access road are in Flood Zone 2, there is both vehicular and pedestrian access in all other directions, should this route become impassable.

#### 4.3 Mitigating Measures

Additional measures can be implemented to minimise the likelihood or severity of flooding. As flood risk for the site is mostly low, no specialist flood measures are required.



#### 5 CONCLUSIONS AND RECOMMENDATIONS

The main conclusions from this flood risk assessment are detailed below. These conclusions and recommendations may change if further Site investigations become available and the proposals are developed.

- The majority of the site is located in Flood Zone 1 with a small section of the eastern boundary lying in Flood Zone 2. The area located on Flood Zone 2 constitutes the car park and yard area behind the existing pavilion. The temporary facilities are to be located outside of the Flood Zone 2 extents. Overall, the risk of flooding from Rivers and Seas is low.
- The site is situated in an area of high potential for groundwater flooding. However, local borehole records show the ground water to be at least 2.8m below ground level and the temporary facilities will be placed above ground with raised thresholds. There have been no reports of previous historical flooding.
- There is a risk of the site flooding due to artificial sources on a wet-day scenario. This possibility is recognised as extremely unlikely.
- It is assumed that the foul discharge will be contained by the temporary units or make use of the existing septic tank.
- No formal drainage design is envisaged for the temporary structures. The structures have a small footprint so the impact on runoff rates will be negligible.
- > A separate FRA is to be prepared for the permanent works on site to construct a new pavilion.




## Appendix A – Site location





## Appendix B – British Geology Society

# GeoIndex Report





Contains OS data © Crown Copyright and database right 2020

GeoIndex Onshore Data Sources: NERC, Natural England, English Heritage and Ordnance Survey


# **Map Key**


Bedrock geology 1:50,000 scale

LONDON CLAY FORMATION - CLAY AND SILT

**CLAYGATE MEMBER - SAND, SILT AND CLAY** 

# GeoIndex Report





Contains OS data © Crown Copyright and database right 2020

GeoIndex Onshore Data Sources: NERC, Natural England, English Heritage and Ordnance Survey

## **Map Key**

#### Superficial deposits 1:50,000 scale

**KEMPTON PARK GRAVEL MEMBER - SAND AND GRAVEL** 

ALLUVIUM - CLAY, SILT, SAND AND PEAT

**ALLUVIUM - CLAY, SILT, SAND AND GRAVEL** 


TAPLOW GRAVEL MEMBER - SAND AND GRAVEL


BLACK PARK GRAVEL MEMBER - SAND AND GRAVEL

**HEAD - CLAY, SILT, SAND AND GRAVEL** 

LANGLEY SILT MEMBER - CLAY AND SILT

# GeoIndex Report






Contains OS data © Crown Copyright and database right 2020

GeoIndex Onshore Data Sources: NERC, Natural England, English Heritage and Ordnance Survey

# **Map Key**

#### Borehole records

- Unknown Length
- Confidential
- 0 10m
- 10 30m
- 30m+



Appendix 1 Sheet 1

BOREHOLE NO	1 TO 16 NE 11	3
Ground Level	Diameter of Boring	
Water Struck 4'6"	Method Shell and Auger	
Standing Water Level 5'0"	Start. 13.1.70 Finish 13.1.70	
REMARKS:	(ALL 8	

	Description of Strata	Thickness	Depth	Reduced Level	Disturbed Samples	Undisturbed Sample and Insitu Tests
Made	Sand, topsoil and rubble	.1'6"	1'6"		1'0" J6466	
	Soft grey silty clay with brick fragments	3'0"			3'0" J6467	
Ground	and gravel		416"		4'6" W6474 5'0" J6468	
Soft g	grey silty clay	5'2"			7'0" ]6469	
			9*8"		101011 27.70	
Soft t	brown silty clay	2'4"	12'0"		10'0" J6470	
	•				13'0" B6471 W6475	
Medium gravel	n to coarse flint l	6'6"	10121			
Firm l	brown clay	1'6"	18'6" 20'0"		19'0" J6472	
Firm	to stiff grey clay	1,0,,	21'0"		21'0" J6473	
Botto	m of Borehole				:	
					(BCS)	
-				-		
			6 um.	rentin .		
	TOTALS	21'0"			1	

NOTES: Descriptions in accordance with C.P.2001 "Site investigations"


J = Jar Sample 8 = Bulk Sample W = Water Sample

U = Undisturbed Core Samples, 4 in dia. × 18 in long. Depth shown to top of sample. U\* = Sample not recovered.

N = Number of blows per ft. penetration in Standard Penetration Test.

V = Shear strength in 16/in 2 given by Insitu Vane Text.

Contract Name	HAMPTON WICK	
Terresearch Ltd.	Report No. S,606/20	Borehole No. 1



Record of Borehole No.4

Location NPL TEDDINGTON

PROPERTY SERVICES AGENCY

Type of boring LIGHT CABLE PERCUSSION

Sheet | of 1 1706 7002

186

Job No. 17311519

Client


Ground level 8.00m 0.D.

Diameter / 150mm


Casing / 150mm to 5.95m

Daily	Ground	Depth	Şər	nples		S	Strate			Lesserd	G
Progress	water levels	of casing	Depth	No.	Туре	a	Depth	Reduced	Description of strata		Ŷ
18,1,88.		· ·	0.40 - 1.00	1,	В	-	G.L. D.30	8:00 7.70	MADE GROUND: {100mm of CONCRETE overlying rubble}.  Brown medium to coarse SAND and fine	$\boxtimes$	, y
		1.00	1.00 - 1.45	2	BC(43)		1.90		to medium occasionally coarse angular to sub-rounded flint GRAYEL becoming dense SAND with much fine to medium gravel.	0000	
		2.00	2.00 - 2.45	3	8C(39)	2				0 0	AAVEL
	<b>▼ 2-95</b> 2.85	3.00	2.85 3.00 - 3.45	5 4	¥ 8C(28)	3	2.90		becoming medium dense mottled dark greyish brown to brown SAND and fine to coarse GRAYEL, maloderous (very).	0 0 0 0 0 0 0 0	PLAIN
-	2.90	4.00	4.00 - 4.45	6	8C(24)	4	4.00		becoming mottled dark grey to brown	000000000000000000000000000000000000000	ğ
-	2.80	5.00	5.00 - 5.45	7	BC (23)	, m				00000	
	5: 95 Sealed	5.95	5.80 5.90 6.00 - 5.45	8 9 10	D (SJ)	ا ا	5.70 5.85	2.30 2.15	Stiff intact mottled dark grey and brown silty CLAY with small pockets of medium to coarse sand and fine gravel, maloderous.  Stiff to Very stiff thinly lamina-	, i i	≱
		G	6.75 7.05 - 7.50	12 13	D DS(19)	7.			ted poorly very closely fissured dark brownish grey silty CLAY with partings of fine to medium sand, occasional shell fragments and occasional weak pyrites nodules.	4.  *∀	LONDON CL
(7.50m)	DRY	5.95				1 60 1	7.50	0.50	BOREHOLE COMPLETED.	•4	۲٥
							35)				
D B W S( ). s C( ). c (33). s	undisturbed disturbed jar disturbed but water sample standard pen sone penetre pumber of bi proundwater	sample ik sample it sample ietration te ition test lows ("N" v	alue)	Star Gros Stra	atum high ndpipe in	st hly nst er fil	ruck at poliute alled at zone 6.5	2.85m, di d between	ົ່ງທະ. ປີຫ.		


GROUND ENGINEERING




•		TO 16NE 70 1725-6915 For Institute use only Licence No.	
	RECORD OF WELL	N	
KASLOWA	RECORD OF WEEL		
· 1.5.	AI HAMPTON WICK POND	TQ16 52	
Threme's	HAMPTON COURT PALACE		
MRA	Town or Village , EAST, MOLESLEY	·····	
Ļ	County, KTS 9AU,		
FXMCESTIE		270. 1916NG	
OF WELL	Six-inch National Grid sheet and reference HARRIS GROUP OF COMPANIES For		
	State whether owner, tenant, builder, conn-	ctor, consultant, etc.:	
	Address (it different from above)	DE WHARF, DOCK ROAD, BRENTFORD,	
	Level of ground surface above sea level (O.)	0.)	
*BFTELE		lan above:*	
7.6	SHAFFft (	linseer	
NECESSARY	HEADINGS (please attach details-dimens	ons and directions)	
	450	я); diameter: at topйг (ir (ir);	
	at bestomin (in		
	1 6 60 metres of 150mm diameter	osition, length, inner and outer diameters, plain slotted etc.): polypropylene lining tube installed with	
	the lower 3.00 metres slotted.		
	Water carry bear departure of	2.80	
,	Rest to clud water ft ( 2.80	m) below well top. Suction at	
j		at1,250galls per boux (	
TEST		n) below well top. Recovery to rest level in 10 mins*	
CONDITIONS	Capacity of pump. 1,250 g.p.h. (		
	Date of measurements8th March. 1		
	DESCRIPTION OF PERMANENT PUM		
		ubmersible Motive power Electric	
NORMAL.	Capacity, 1,250 galls (	5,80 (m)	
CONDITIONS	below well top. Amount pumped 30	000galls (n³) per day. Estimated	
	consumption 210,000galls (		
•	Well made by Smith & Webb (Drill)	ng) Ltd. Date of sinking. 15th February 1991	
	i	lease attach copy if available)	
1.06 OF	the property of the state of th	Received born Smither Velb	
SERATA	RECHIVED N.CD.C.	Received from 197000000000000000000000000000000000000	
OVERLEAF	DATE: 800 Oct 90	Date . 8th Hay 1992	
	SiGi Aff	Observation well	
		Recorder	
		Site marked on 1" map	
Institute of Hybrogeol	F GEOLOGICAL SCIENCES SORY UNIT	6" map—Grid Sheet	
EXHIBITION LONDON SW		(reg symbol)	
		,	
	E.2 5441 10 000 1 48	ST+ Date	




n <i>Tustitute use o</i> Eological	NATURE OF STRATA	Tma	FINCKNESS DEPTH				
ASSETTE A PION	If measurements start below ground surface, state how far.	Fret	faches	Metres	Feet	Inches	Metres
<u></u>	Topsoil			1.00	ļ		1.00
	Firm brown and grey clay			1.40	<u></u>		2.40
		]		3,10	1		5,50
	Brown sand and gravel	1	· [ · · · · · ·	0.10	l		5,60
	Brown clay	ļ	·	1.00	1		6,60
	. Blue clay	ļ	1	1.,1,09	<b></b>	1	1.0100
		<b></b>	• • • • • • • • • • • • • • • • • • • •			1	.,
		<b></b>			ļ,.,	<b>†····</b>	
		ļ,,		.		·····	· · · · ·
		<b></b>			<b></b>	<b></b>	· · · · · ·
		<b></b>			ļ		·····
		<b>.</b>	<b></b>	.]	ļ		
		ļ			<b></b>	<b></b>	
					<b></b>	<b>.</b>	
		<b>,</b> [,					
					J		<b></b> ,
				.].,,,,,			<b></b>
		1					
			`` ````	`			[
				1	' [ ' ' '		
			• • • • • • • • • • • • • • • • • • • •			1	
				69.1	·†···		
					-∤…		
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				,		
		, ,					
	···········			6			
		•			··\	• •	1
					···{···		
	1	- 1	1	ł	ł	•	3



		For Institute use	only Licence No.					
Rastern	RECORD OF WELL		N					
4.8.	T AL HAMPTON WICK POND	ایسا	(122)					
	HAMPTON COURT PALACE	7010	52					
Thames	THE THE TAX TH	, 41						
N.R.A	Town or Village . EAST, MOLESLEY.		•					
	County KTS 9AU.	Į						
EXACT SIT	F	70 1725 6915	TOILNE					
OF WEL	Six-inch National Grid sheet and reference	10 1723 0913						
OI WEL	For							
	State whether owner, tenant, builder, contractor, o	onsultant, etc.:CON	TRACTOR					
	Address (if different from above) BRENTSIDE WH	ARF, DOCK ROAD, B	RENTFORD,					
-	MIDDLESEX. TWO BAQ.	,,	,					
	Level of ground surface above sea level (O.D.)	, ,	. ft ( <sup>10</sup> ,00,)					
*DELETE	If well top is not at ground level state how far abo	ove:*	ft (m)					
A.S								
NECESSARY	HEADINGS (please attach details—dimensions ar	nd directions)						
	BORE	iameter: at top	in (150mm);					
	at bottomin (							
	Full details of permanent lining tubes (position	, Jength, inner and ou						
	6.60 metres of 150mm diameter polyp the lower 3.00 metres slotted.	ropylene lining to	upe installed with					
	ene lower 3.00 metres stotted.							
		.,						
)	Water struck at depths of		2.80m) below well top					
	Rest level of waterft (							
	Yield on4 hours * test pumping at1, 250galls perhour (							
TEST	depression to							
CONDITIONS	Capacity of pump							
	Date of measurements8th .March .1991.	(4 hour pump	test)					
	DESCRIPTION OF PERMANENT PUMPING E	OUIPMENT:						
	Make and/or type Grundfos SPSA.4 submer	-	nower Electric					
NORMAL			•					
CONDITIONS								
	consumption .210,000 galls (		, , , , , , , , , , , , , , , , , , ,					
	Well made by Smith & Webb (Drilling) L	-	sinking 15th February 1991					
	ADDITIONAL NOTES ANALYSIS (please at							
	MIDITATING NOTES ANALYTOIS (please at	tach copy it available)						
1.0G OF	( BG	)	Received from Smither Valb					
STRATA			***************************************					
OVER1.EAF			Date . 8th How 1992					
			Observation well					
		]	ER log					
Institute	of Geological Sciences		Site marked on  1" map					
Нуркосео Ехнівітю	PLOGY UNIT	***************************************	6" map-Grid Sheet					
LONDON S			(use symbol) Copy to					
	3GS 2494 10 000 7/75		Date					
		,						




EOLOGICAL	NATURE OF STRATA	THICKNESS DEPTH					
LASSIFICATION	If measurements start below ground surface, state how far.	Feet Inches		Metres	Feet	Inches	Metres
	Topsoil	ļ.,	ļ	1.00	<b>.</b>	ļ	1.00
	Firm brown and grey clay	ļ		1.40	<b></b>		.2.40
	Brown sand and grayel			3,10			5,50
	Brown clay	,,	ļ	.,0,10	ļ		5,60
				.1,00			.6,60
		<b></b> .					
		ļ			ļ		
		ļ					
		<b></b> .			<b> </b>		
				ļ	<b> </b>		
		<b></b>			ļ		
		ļ		<b>.</b>		<b></b>	
			· <b>k</b>		<del> </del> , <u>-</u>	<del> </del>	
		ļ		. ]	<b></b>	<b></b>	
		<b></b> .		.	<b> </b>		
		<b> </b>		.]	·····	<b></b>	
		ļ,		.			
		<b> </b>			ļ		
		<b>.</b>					· · · · · ·
		<b></b>	<b>†····</b>		1	1	<b>.</b>
		ļ	• • • • • • • • • • • • • • • • • • • •			<b>†</b> ·····	<b>.</b>
				.	ļ	<b>†·····</b>	
		ļ			1	1	
		ļ	1		1		1
		1			· · · · ·	1	
		1	1		1	1	
			1		1	1	1
		1			1,,,,,	1	******
		1				1	1
		1	1		1	1	1




wner				Licence No. 40 1 14 1		Nat. Grid Ref. TQ 1725 6915 Status				
ccupier IGS Ref. No.										
round Level m					tt. OD		0			
el of Wel	Тор		m QD		ft. OD	Aquiter Gravels				
ost Water Level m bwt					ft. bwt	Summary of Geological Section Thickness			Depth	
)ate	)	) m OD								
onstruction										
Depth bwt	Dia	Linings (below well top)								
		From	Τø	Dia.	Туре					
6 M	150	٥	6.6 M	150 mm	UPVC					
		3.3	6.6 M	t,	Slotte	The state of the s				
				<u> </u>						
ostraction Rates Type of Pump			ļ							
gph Che			hem./Bact. /	Anal. Y	ES NO	\\				
gpd W			Vell Driller			4				











## Appendix C -LB of Richmond Maps


















































## Appendix D - Flood Maps







## whitby wood

91-94 LOWER MARSH LONDON SE1 7AB, UNITED KINGDOM +44 (0)20 7442 2216 www.whitbywood.com