


Notes:
 Building Regulation Approval: The owners of the property are advised that an approval of the calculations and drawings by the Local Authority Building Control should be obtained prior to any ordering of material or fabrication. No liability is accepted for any changes that may be required as a result of work having commenced prior to such an approval having been obtained. This drawing remains the copyright of Express plans and is not to be copied, altered or changed without permission.
 This drawing to be read in conjunction with architects and project specifications. Any discrepancy between this drawing and all other project drawings should be brought to the attention of Express plans for clarification prior to commencing the works.
 Local Authority's building inspector is to be informed by the contractor in writing at least 48 hours prior to the works starting on site and their agreement obtained that work can commence.
 Structural Steelwork: All steel members grade to be BS EN 10025 S275 J0 (Hollow sections to be S355). Length of the beams and the columns should be provided by the contractor allowing minimum bearing. DO NOT SCALE THE DRAWING.
 Steel Corrosion Protection: Preparation: Shot blast to SA2.5. Shop primer, Zinc phosphate (zinc micron).
 Fire Protection to steel Beams & columns: Box around all steels with 50 x 50 s.w. framework and 2 layers of 12.5mm Fire line plasterboard with staggered joints and 3.5mm skim finish.
 Flat stones: Flat stones to be grade C30 concrete. Beam bearing on pad stones to be minimum 100mm unless otherwise noted specified on Structural Timber.
 All timber grade C24 unless otherwise stated. Joints may be notched over bearing, maximum depth of notch 1/3 joist depth. Use steel beam with solid timber packing plates bolted through web of beams.
 M12@500 centres behind joists hangers and for and step fixing. Temporary Works: The contractor is to accept full responsibility for the stability and safety of the works during the total construction period. No undermining of existing structure is to be carried out prior to consultation of structural engineer.

Protected Fire escape route- Doors
 Contractor to establish the current build-up of doors upon inspection on site (with the presence of Building Control officer). If necessary, upgrade doors and frames to achieve min. FD30 status. New frames to incorporate intumescent seal.

Protected Fire escape route- Floors & Ceilings
 Contractor to establish the build-up of floors & ceilings includes the stairs. with fire rated plasterboards and Flooring grade WBP to achieve a minimum 30-minute fire resisting construction (REI)

all stud partition are to be 100x50mm sawn timber @ 400c/c & horizontally nogged @ 600c/c to be lined with 15mm soundbloc plaster board by gyproc & 5mm skim on both sides. all partitions to have 100mm fiber glass insulation

Boundary Line




New Fire doors :
 New Fire doors located as shown. All doors fitted as per manufacturers instructions, & to comply with Part B regulations. Use appropriate ironmongery, UKAS fire certified, along with appropriate intumescent seals. The entrance door requires self-closers and intumescent strips

Protected Fire escape route- Partitions
 Contractor to establish the build-up partitions with fire rated plasterboards, to achieve a minimum 30-minute fire resisting construction (REI)

A carbon monoxide alarm should be provided in the same room as the new fixed gas, oil or solid fuel appliance complying with BS EN 50291, the alarm should incorporate a warning device to alert users when it requires replacing. The alarm should be located on the ceiling between 1 and 3m horizontally from the appliance, and installation should comply with BS EN 50292:2002.

Boundary Line

PROPOSED FIRST FLOOR PLAN



Issue	Notes	Drawn	Date
Express Plans			
Suite 12, 29 Belmont Road, Uxbrdge, UB8 1QS Tel: 07375 455206 Email: info@expressplans.co.uk			
Client J&N. Properties Ltd 56 Ashley Drive Twickenham TW2 6HW			
Drawing Title PROPOSED FIRST FLOOR PLAN			
Scale 1:50	Date 29/06/24	Checked AZ	Drawn By AZ
Drawing Number D04			Revision