



MAIN ROOF AREA MEASURE AT ROOF PLAN 72m2



MAIN ROOF TO BE EXTENDED TO THE REAR
REQUIRED DEMOLISHED ROOF AREA MEASURE AT ROOF PLAN 9.6m2




MAIN ROOF TO BE EXTENDED TO THE BOTH SIDES

REQUIRED DEMOLISHED ROOF AREA MEASURE AT ROOF PLAN 9.9m2 + 11.5m2


TOTAL REQUIRED DEMOLISHED ROOF AREA MEASURE AT ROOF PLAN

9.6m2 + 9.9m2 + 11.5m2 = 31m2 (43% OF EXISTING ROOF - REMAIN 57%)

TYPICAL SEMI DETACHED HOUSE WITH GABLE END AND REAR DORMER SAMPLE NORMALLY APPROVE UNDER PERMITTED DEVELOPMENT FOR LOFT CONVERSION




MAIN ROOF AREA MEASURE AT ROOF PLAN 61m2



BUILDING STAGE ONE — GABLE END TO THE SIDE

MAIN ROOF TO BE EXTENDED TO THE SIDE

REQUIRED DEMOLISHED ROOF AREA MEASURE AT ROOF PLAN 19m2



BUILDING STAGE TWO — REAR DORMER

MAIN ROOF TO BE EXTENDED TO THE REAR

REQUIRED DEMOLISHED ROOF AREA MEASURE AT ROOF PLAN 18.5m2

TOTAL REQUIRED DEMOLISHED ROOF AREA MEASURE AT ROOF PLAN 19m2 + 18.5m2 = 37.5m2 (61% OF EXISTING ROOF - REMAIN 39%)



PLANNING STATEMENT

WILL REMAIN

THE PROPOSAL WILL NOT REQUIRED TO

MORE THEN 50% OF THE ORIGINAL ROOF

PLEASE REFER TO THE CALCULATIONS

CONVERSION WITH GABLE END AND REAR

DORMER REQUIRED MORE THEN 50% OF

NORMALLY IS ACCEPTABLE UNDER

ORIGINAL ROOF TO BE DEMOLISHED AND

DEMOLISHED THE WHOLE ROOF

TO COMPARE STANDARD LOFT

PERMITTED DEVELOPMENT

NOTE! THE MATERIALS USED IN THE CONSTRUCTION OF THE EXTENSION WILL BE OF SIMILAR APPEARANCE TO THOSE USED IN CONSTRUCTION OF THE EXTERIOR OF THE EXISTING DWELLINGHOUSE

