



Drainage:
 Hand car wash drainage consist of an overlarge impermeable concrete wash pad with centralized silt separator, silt separator is connected to a 2000L two chamber interceptor. Treated effluent is discharged to foul manhole. Please see accompanying design and access for more information.

KEY:

	Fence
	Installed Walkway
	Ducting (Power & Foul)
	Ducting (Power & Water)
	Ducting (Power & Water Hose)
	Ducting (Data)
	Ducting (Power)
	Composite Manhole
	Service Manhole
	Silt Trap
	Silt Trap Outlet Pipe
	Interceptor
	Submersible Foul Pump
	Flood Lights
	Gradient Direction



REV:	DESCRIPTION:	BY:	DATE:
STATUS:			
PLANNING			
Gilmore Consultancy			
1 Castle Court Brewhouse Lane London SW15 2JJ			
07975852755 planning@gilmoreconsultancy.com			
SITE: Homebase Hanworth Twickenham Road, Twickenham, Feltham TW13 6EZ			
TITLE: Hand car wash drainage plan			
SCALE AT A3: 1:50	DATE: 28.02.24	DRAWN: JB	CHECKED: JB
PROJECT NO: n/a	DRAWING NO: HB-hcw-install-02/24-005	REVISION: n/a	

