





Context

The proposed works comprises the demolition of an existing two storey dwellinghouse and the construction of a new three storey dwellinghouse at 26 Washington Road, London, SW13 9BH.

The proposed dwellinghouse comprises ground, first and second floor levels. The second floor level has a relevant height in fire safety terms of less than 7.5m (measured from existing ground level). The proposed dwellinghouse does not exceed a floor area of 1,000m² and therefore is not designated as a Major Development under Annex 6 of the London Plan 2021. The dwellinghouse does not contain a lift. Accordingly, this Planning Fire Safety Statement (PFSS) is structured to address London Plan Policy 12A only and is presented in that order prescribed in Policy D12A, i.e. Policies D12A(1) through D12A(6).

Competence

This Planning Fire Safety Statement (PFSS) has been prepared by Dr. Raymond Connolly of Fire Safety dotLondon Ltd. who is a suitably qualified and experienced Chartered Engineer and Member of the Institution of Fire Engineers, meeting the competency standards contained in Clause 3.12.9 of Policy D12.

Design Objective

In the first instance the fire safety objectives are those contained outlined in the Greater London Authority's London Plan 2021 *Policy D12A – Fire Safety.*

It is confirmed that London Plan Policies D12B (Fire Safety - Major Developments) and D5(B5) (Evacuation Lifts) do not apply to the subject development. The proposed development has been evaluated in terms of its capacity to deliver the stated Policy 12A objectives, specifically:-

- Identification of suitably positioned unobstructed outside spaces for (a) fire appliances and (b) evacuation assembly.
- Measures to ameliorate risk to life and of serious injury due to fire (active & passive fire safety precautions).
- Fire safety performance in respect of the building's inherent construction and the fitness for purpose of the materials used therein to limit fire spread.
- Adequate, dignified and universal means of escape in case of fire for all potential building users.
- 5) Evacuation Strategy.
- 6) Access and facilities for London Fire Brigade.

Design Development

<u>Building Regulations 2010 (as amended in 2018, 2020 and 2022)</u>
During detailed design, these London Plan policy objectives will be further supplemented by the minimum requirements of Part B to Schedule 1 of the Building Regulations, namely:-

- To ensure the life safety in case of fire of all building, i.e. to permit all building occupants to safety
- To inhibit the spread of fire via the internal wall/ ceiling linings.
- To design and construct the building such that it will retain its stability for a reasonable period during a fire.
- To appropriately sub-divide the building to restrict the internal spread of fire and to inhibit the unseen spread of smoke and fire within concealed spaces.
- To prevent the spread of fire from the building beyond the site boundaries to adjacent buildings.
- To enable access to the building to assist fire-fighting.

These statutory objectives shall be met to the extent determined by the Building Control Body (identity to be confirmed) in consultation with London Fire Brigade as being sufficient to achieve compliance with the specific requirements of Part B to the Building Regulations 2010 (as amended).

The dwellinghouse is served by a protected escape stairway at the ground, first and second floor levels that extends directly to the final exit at ground floor level. The dwellinghouse is defined under Building Regulations as:-

Purpose Group * Dwellinghouse that contains a habitable storey 1(b) with a floor level a minimum of 4.5m above ground level

*Table 0.1 of HM Government Approved Document B Vol. 1

Table 1. Building Regulations Purpose Group

Relevant Fire Safety Design Code

This PFSS outlines a means for delivering future compliance with Part B to the Building Regulations (as amended), as will be further developed during the detailed design process within the formal statutory regime under the jurisdiction of the appointed Building Control Body and London Fire Brigade. This approach shall include adoption of the appropriate quidance contained in:-

 BS 9991, Fire safety in the design, management and use of residential buildings - Code of practice (2015).

Future Modifications (The Golden Thread)

The fire safety strategy underpinning the building design shall be maintained into the design and construction stages (RIBA Stages 3-6), allowing for future modifications as might arise. It is highlighted that the Building Regulations (as amended) will apply to this building.


Specific construction products and manufacturer's verification of performance shall be proposed in due course by the Design Team to comply with the statutory obligation of Regulation 7 and specifically Regulation 7(2) with regard to delivery on the principles contained in this Planning Statement, i.e. specification of appropriate materials and standards of workmanship.

As per Regulation 38, all relevant design fire safety information (including operations, maintenance and routine testing of fire safety systems) shall be formally handed over to the responsible persons on completion.

The *Materials Information Register* contained within this PFSS shall be passed to any third party engaged in the future construction phase to maintain the "golden thread" of fire safety design. It is noted that this PFSS is a document of public record and will be available to the Building Control Body overseeing the design and construction stages.

London Policy Objective D12A(1)a Fire Service Access (Building Regulation B5)

The dwellinghouse will be accessed off the main public highway i.e. Washington Road. This extent of Fire Service access is sufficient for a building of this size with access to all locations in the proposed dwellinghouse as being within 45 metres of the hard-standing – as measured along the line of a laid hose. The notional hard-standing (shown in red in *Figure 1*) sits on Washington Road, which is sufficiently wide to accommodate same without undue obstruction. As a public highway, the hard-standing shall be available during the construction process.










Figure 1. Fire Service Access within Site

London Policy Objective D12A(1)b Evacuation Assembly (Building Regulation B1)

The proposed development sits on a private site that is accessed by means of a main public highway (Washington Road) and the site is of sufficient size to offer unobstructed space for evacuation, mustering and emergency intervention. Further evacuation onto the public pavement on Washington Road is available and may be used during the construction process. (Figure 2 refers).



Figure 2. External Assembly Point

London Policy Objectives D12A(2) Fire Safety Systems (Building Regulation B1)

Active Fire Precautions

The proposed dwellinghouse shall be provided with an automatic fire detection and alarm to BS 5839-6:2019+A1:2020 (Type LD2). Detection shall be minimum **Grade D**, i.e. mains powered interlinked detection and alarm.

Passive Fire Precautions (Figures 4 to 6 refer)

Good design practice and construction standards shall be employed throughout, so as to reduce ignition risks, e.g. suitably sized unjointed electrical wiring, fire-resisting non-combustible post boxes. All electrical wiring shall meet current IET National Wiring Regulations (BS 7671).

The stairway in the dwellinghouse shall be enclosed at the ground, first and second floor levels and lead to a final exit at the ground floor level. (Figures 4 to 6 refer)

The gable walls within 1 metre of the legal site boundary shall include minimum 60 minutes fire-resisting construction, e.g. min. 100mm thick brickwork.

Fire Safety Management (Regulation 38)

The homeowners shall be appraised of the fire safety systems installed within the dwellinghouse including advice on the routine testing and maintenance of the fire detection and alarm system to BS 5839:Part 6 requirements.

London Policy Objective D12A(3) Building Construction (Building Regulations B2, B3, B4 & Regulation 7)

Materials Information Register (Regulation B2)

Notwithstanding that the building is not yet procured, it is proposed to restrict future construction materials by means of performance classification to BS EN 13501-1 as follows:-

- Roof (clay/slate finished tiles) to minimum Class B_{ROOF}(t4)
- External walls (cement board, masonry & brickwork/render) to Class C_{s3,d2}
- Internal walls and ceilings to escape routes to Class C_{s3,d2}
- Other internal walls/ceilings generally to minimum Class $C_{s3,d2}$, with the exception of small rooms (having areas < 4m^2), which may be relaxed to Class $D_{s3,d2}$.

The proposed dwellinghouse is not a "relevant building" as defined

in Building Regulation 7(4) and where the spatial separation of the external walls to the relevant site boundary is more than 1 metre, the components within the external wall assembly are unrestricted. Where the spatial separation of the external walls to the relevant site boundary is less than 1 metre, the components within the external wall assembly are required a Class B-s3, d2 or better

Electrical sockets shall be provided within all rooms in sufficient locations and numbers to minimise any end-user need to introduce portable adapters and extension leads as might pose an increased risk of electrical fire ignitions.

<u>Protection against undue fire spread via structure (Regulation B3)</u>
The proposed building shall be designed to retain its stability in the event of a fire for a reasonable period. This shall be verified during detailed design through:

- Specification of gable walls as 60 minutes fire-resisting as described in Figures 4, 5 & 6. Red Lines= 60 mins fireresisting:
- Other internal walls to be provided with fire ratings as described in Figures 4, 5 & 6. Blue Lines= 30 mins fireresisting:
- Provision of elements of structure (beams, columns and floor slabs) having minimum fire resistance ratings of 30 minutes.
- Enclosure of the internal escape stair with 30 minutes fireresisting construction, accessed via FD30 doorsets at the ground, first and second floor levels.

Protection against undue fire spread externally (Regulation B4)

The relevant boundaries are identified in *Figure 3*. The buildings' elevations shall be controlled as necessary to include fire-resisting construction as necessary to ensure that fire does not spread beyond the site's relevant boundaries.

The gable walls adjoining adjacent properties shall be constructed as separating walls and will provided a minimum of 60 minutes fire-resisting construction.

The gable walls within 1 metre of the legal site boundary shall be provided with a minimum of 60 minutes fire-resistance and no unprotected openings. External wall surfaces within 1 metre of the site boundary shall be Class B _{\$3.42}.

Planning Fire Safety Statement for Residential Development at 26 Washington Road, London, SW13 9BH



Figure 3. Overview of Relevant Boundaries

The front and rear elevations of the dwellinghouse do not need to be controlled to avoid undue fire spread beyond the site's relevant boundaries.

The eastern and western elevations adjoining adjacent properties at the ground floor level shall be constructed as separating walls and will provided a minimum of 60 minutes fire-resisting construction as indicated on the floor plans (*Figure 4* refers).

The western elevation adjoining the adjacent property at the first and second floor levels shall be constructed as a separating wall and will provided a minimum of 60 minutes fire-resisting construction as indicated on the floor plans. The eastern elevation at the first and second floor levels is a minimum of 1 metre to the legal site boundary but will be fire-rated as indicated on the floor plans to ensure space separation compliance in accordance with Diagram 11.7 of Approved Document B, Volume 1, 2019. (Figures 5 & 6 refer)

Materials and Workmanship (Regulation 7)

Specific new construction products and manufacturer's verification of performance shall be proposed in due course by the Design Team to comply with the statutory obligation of Regulation 7 and specifically Regulation 7(2) with regard to delivery on the principles contained in this Planning Statement, i.e. specification of appropriate new materials and standards of workmanship.

London Policy Objectives D12A(4) Means of Escape for all building users (Building Regulation B1)

Design Philosophy

The proposed dwellinghouse has been appraised in terms of the means of escape infra-structure for all occupants comprising a

single family dwellinghouse. The fire safety design shall deliver compliance with Part B1 of the Building Regulations by adhering to the principles contained in BS 9991, Fire safety in the design, management and use of residential buildings - Code of practice, 2015.

Proposed Means of Escape

The dwellinghouse is not provided with a lift. Evacuation shall not rely on Fire Service intervention. The sounding of the automatic fire detection and alarm system shall motivate the simultaneous single-phase evacuation of all residents.

The dwellinghouse may be summarised in fire safety terms as equivalent to single protected stair building with no storey in excess of 7.5 metres above ground floor level. Therefore, a protected internal escape route is required. It is proposed that the protected stair will extend directly to fresh air at the ground floor level. In accordance with best practice, no inner room habitable rooms are proposed. The importance of maintaining the integrity of the protected stair infra-structure through closing of fire doors shall be emphasized in writing to the end-user occupier as part of handover.

London Policy Objective D12A(5) Evacuation Strategy (Building Regulation B1)

A household specific Escape Plan should be developed by the final building occupier that recognises:-

- The critical reliance of the protected escape stairway on fire doors being closed at all material times.
- (ii) The need for self-reliance in terms of escape with appropriate assistance provided from within the household where necessary for younger, older or cognitively/mobility impaired occupants.

It is highlighted that this latter responsibility is likely to evolve over time and the Evacuation Plan shall be subject of periodic review (not less than annually).

It is recommended that the Evacuation Plan should also be extended to consideration of wider fire safety matters such as regular weekly testing and maintenance of the fire alarm system.





Figure 4. Proposed Ground Floor Plan





Figure 5. Proposed First Floor Plan










Figure 6. Proposed Second Floor Plan

London Policy Objective D12A(6) Fire Service Access in and around the building (Building Regulation B5)

The dwellinghouse is located within 100 metres of an existing fire hydrant and as a result does not require provision of any specialist fire-fighting facilities or dedicated fire hydrant. It was previously confirmed in *Figure 1* that all locations within the proposed dwellinghouse are within the 45 metres range of a hose laid from the Fire Service vehicle (pumping appliance) notional hard-standing on Washington Road.

The notional vehicle hard-standing is served by the existing public fire hydrant located on Washington Road as shown in *Figure 6*. This provides a supplementary water supply for residential fire-fighting and is in addition to the London Fire Brigade pumping appliance on-board water storage capacity.

These facilities shall remain available during the construction phase, with a number of secondary vehicular hard-standings available on Washington Road should there be a temporary instance of a construction vehicle obstructing the preferred location.



Figure 6. Existing Fire Hydrant Location on Washington Road

Declaration by Expert Assessor

This Planning Fire Safety Statement has been prepared in good faith using our specific fire safety expertise to meet our best understanding of the requirements of Policies D12A of *The London Plan 2021* using the recommended checklist therein.

The subject building is amenable to achieving full compliance with Part B (Fire Safety) to the Building Regulations, 2010 (as amended). Any future modifications to the building as described in this PFSS should be assumed to adversely affect this declaration, unless demonstrated to the contrary by a competent person.

- Reduction in any fire resistance ratings contained in this PESS
- Omission of fire-resisting enclosure to protected stairway.

Der 1 Couly

Dr Raymond J. Connolly BE, PhD, CEng, MIEI, MIFINE, MSFPE Chartered Engineer & Fire Safety Specialist For Fire Safety dotLondon Ltd

Supporting Schedule of Relevant Planning Drawings

This Fire Statement has been prepared following our appraisal of the drawings (as prepared by CHP Consultants) as per Table 2.

Ref.	Title
127-FP-006	Location and Site Plan
127-FP-007/8/9	Proposed Plans

Table 2. Schedule of Relevant Planning Drawings

A3.2 Form 2 – Planning Fire Safety Strategy template (London Plan Policy D12A) for non-major development as set out in Appendix 1

Form 2 – Planning Fire Safet non-major development	y Strategy template (Londor	n Plan Policy D12A) for
Site address	✓	
Description of development	✓	
Name, qualifications, professional memberships and experience of author	✓	
Has a Gateway One Statement been submitted?	THIS REPORT IS NOT SUBJECT TO THE GATEWAY ON STATEMENT REQUIREMENT AS IT IS LESS THAN 18m	
Policy considerations		Potential Gateway One cross reference
Identifies suitably positioned space for fire appliances to b		Gateway One Q12
Identifies suitably positioned unobstructed outside space appropriate for use as an evacuation assembly point		Gateway One Q6h
Designed to incorporate appropriate features which reduce the risk to life and the risk of serious injury in the event of a fire, including appropriate fire alarm systems and passive and active fire safety measures		Gateway One Q6i (part)
Constructed in an appropriate way to minimise the risk of fire spread		Gateway One Q6g