









Reference	Illustration	Description	Manufacturer	Dimensions
EX1		Wall mounted LED. IK06, IP65, 11.6W, lumen output of 1468lm, colour temperature 3000K. Non-Dimmable. Finished in black. 127 lumens / watt.	Deltalight NOCTA RD80 DOWN-UP 930 DIM5 N	
EX2		IP67 1100lm LED linear grazer complete with custom wrap with cowl to match RAL of building façade. Colour temperature 3000K. DALI drivers.	LED Linear Adonis Arc EXL SW 11 W930 IP67 with 10ø Optic	Length (Measure on Site) x 205mm (H) x 285mm (W)
EX3	N/A	-	-	-
EX4	Specialist Signage (By Tenant)			
EX5		Surface mounted IK03, IP53, 14.2W, lumen output of 779lm, colour temperature 3000K. Finished in black. Mains Dimmable. 115 lumens / watt.	DELTALIGHT Boxy Square L+	

Reference	Illustration	Description	Manufacturer	Dimensions
EX6		<p>IP65 rated surface mounted linear LED profile with remote DALI drivers. 3000K LED.</p>	<p>Deltalight FEMTOLINE 25</p>	 <p>Vertical bending</p>  <p>TOP LIT</p>
EX7		<p>Wall mounted LED. IK06, IP65, 11.6W, lumen output of 1468lm, colour temperature 3000K. DALI Dimmable. Finished in black. 127 lumens / watt.</p>	<p>Deltalight NOCTA RD80 DOWN-UP 930 DIM5 N</p>	