

PRODUCT NAME ERGA04-08EVA

			ERGA04EAV3A	ERGA06EAV3A	ERGA08EAV3A
Dimensions	Unit	Height	740	740	740
		Width	884	884	884
		Depth	388	388	388
Weight	Unit		58.5	58.5	58.5
Operation range	Cooling	Min.	10	10	10
		Max.	43	43	43
	Domestic hot water	Max.	35	35	35
Piping connections	Liquid	Min.	-25	-25	-25
		OD	6	6	6
	Gas	OD	15.9	15.9	15.9
	Drain	OD	18	18	18
Level difference	IU - OU	Max.	20.0	20.0	20.0
Sound power level	Heat insulation		Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes
	Heating	Nom.	58 (1)	60 (1)	62 (1)
	Cooling	Nom.	61 (1)	62 (1)	62 (1)
Sound pressure level	Heating	Nom.	44 (1)	47 (1)	49 (1)
	Cooling	Nom.	48 (1)	49 (1)	50 (1)
Refrigerant	Type		R-32	R-32	R-32
	GWP		675.0	675.0	675.0
	Charge	kg	1.50	1.50	1.50
Power supply	Name		V3	V3	V3
	Phase		1N~	1N~	1N~
	Frequency	Hz	50	50	50
Current	Voltage	V	230	230	230
Notes	Recommended fuses	A	16	16	16
			(1) - Cooling Ta 35°C - LWE 18°C (DT = 5°C); Heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)	(1) - Cooling Ta 35°C - LWE 18°C (DT = 5°C); Heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)	(1) - Cooling Ta 35°C - LWE 18°C (DT = 5°C); Heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C)