L. А

External Brickwork -Brickwork is to be stripped of the modern paint finish. - Any flaking and loose paint is to be removed by hand using a soft

- Surjourding areas are to be suitably protected, in particular the

surrounding ground and adjacent areas of stonework, to avoid

surrounding ground and adjacent areas of stonework, to avoid damage and contamination. - All areas of painted brick are to be treated with a combination of KEIM and FUZE paint strippers, which are appropriate for heritage projects. (Both products will be tested on a discreet area to ensure they are effective and do not damage the underlying brick). - Once the paint stripper has lifted the paint from the surface of the brickwork, the Therma Tech steam cleaning system will be used to remove the locae paint.


- It is anticipated that the above stages 5.4 and 5.5 will need to be carried out several times in order to successfully strip all of the existing

clined out of set at the point. point. - It is anticipated that following stripping of the paintwork, the pointing on the external walls may need to be renewed. Should this be required, the existing mortar will be raked out by hand to a depth of 20mm, and the brickwork will be repointed using a hydraulic lime mortar. - Once the paint is successfully removed the brickwork condition and

appearance will also be reviewed and the next stages of finishing will

Option 1 (preferred) - If the brickwork is in good condition and of an attractive appearance, it will be left as exposed brick.

Option 2 - if the brickwork is not attractive, and is in poor condition, we will paint over it with a breathable lime wash.



+10.000 [DATUM]

MICHAEL JONES ARCHITECTS

020 8948 1863 | 129 Kew Road, Richmond, TW9 2PN www.mjarchitects.co.uk | studio@mjarchitects.co.uk

drav job title Chapel in The Woods Pr client drav St.Mary's University, Twickenham 19

2m



Other Roof Works

All gutters and downpipes are to be thoroughly cleaned and all connections and brackets are to be inspected and tested. Where failures have occurred repairs are to be carried out. All new parts to be in matching design and materials to existing.

- Slate roof covering is to be thoroughly cleaned and inspected. Any damaged or broken slates are to be removed and replaced with reclaimed slates to match existing. - All lead flashings to be inspected. Any leadwork that is damaged or lifted

is to be re-set and/or repaired using materials to match existing. Particular attention to be paid to the leadwork above the east elevation, where it is flashing up the back of the damaged stone parapet. This will likely need to be redone once the stonework repairs have been

completed. - Sections of rotting timber fascia beneath gutters are to be cut out and replaced with new hardwood fascia, to be joined carefully to existing. - All existing and repaired timber fascia to be rubbed down and thoroughly prepared, to be redecorated.

Stone Repairs

- Failed hanging finials to be repaired by specialist as follows: - Failed hanging finials to be replaced in portland stone to match originals, to be fixed using stainless steel threaded dowels and stone resin.

- Where stone is cracked and failing, it is to be cut back and portland stone indents are to be installed. - The portland stone carved shield from the parapet of the stone elevation is missing,

to be replicated and replaced in portland stone. - See also our Design and Access/Heritage Statement, and drawing 1943.01.03 Stonework Damage, showing the location of each of these areas on the elevation.

Stone Cleaning

 East facing stone facade to be cleaned by specialist as follows: - Stone to be gently brushed with soft brush to remove any loose or superficial dirt

and debis. - Apply a combination of alkali stone sympathetic chemicals (to be tested on a small

 Sone to be brushed with light to stiff brushes.
Sone to be brushed with light to stiff brushes.
Therma Tech steam cleaning system applied with very low pressure to avoid damage to the stonework. The heat from the steam cleaning system will lift the remaining dirt from the surface of the stone.

awing title		scale	1:50@A3
roposed East Elevation		date	June 2024
awing number	rev	drawn by	XD
943.03.03.Pln.060		checked by	AB